ALLIANCE 284 Sheffield Street, Mountainside New Jersey 07092

NEW JERSEY LAB ID#: 20012: NEW YORK LAB ID#: 11376

GC/MS VOA CONFORMANCE/NON-CONFORMANCE SUMMARY

MATRIX: Water

CHEMTECH PROJECT NUMBER: P3451

10.

Analysis Holding Time Met

If not met, list number of days exceeded for each sample:

METHOD: 8260D NA NO YES 1. Chromatograms Labeled/Compounds Identified. (Field samples and Method Blanks) 2. GC/MS Tuning Specifications BFB Meet Criteria (NOTE THAT THERE ARE DIFFERENT CRITERIA FOR NY ASP CLP, CLP AND NJ) 3. GC/MS Tuning Frequency - Performed every 24 hours for 600 series and 12 hours for 8000 Series. 4. GC/MS Calibration - Initial Calibration performed before sample analysis and continuing calibration performed within 24 hours of sample analysis for 600 series and 12 hours for 8000 series. 5. GC/MS Calibration Requirements. The Initial Calibration met the requirements . The Continuous Calibration met the requirements . 6. Blank Contamination - If yes, list compounds and concentrations in each blank: 7. Surrogate Recoveries Meet Criteria If not met, list those compounds and their recoveries which fall outside the acceptable ranges. 8. Matrix Spike/Matrix Spike Duplicate Recoveries Meet Criteria If not met, list those compounds and their recoveries which fall outside the acceptable range. The MS recoveries met the requirements for all compounds. The MSD recoveries met the acceptable requirements . The RPD met criteria. The Blank Spike met requirements for all samples. 9. Internal Standard Area/Retention Time Shift Meet Criteria Comments:

ALLIANCE 284 Sheffield Street, Mountainside New Jersey 07092

NEW JERSEY LAB ID#: 20012: NEW YORK LAB ID#: 11376

GC/MS VOA CONFORMANCE/NON-CONFORMANCE SUMMARY (CONTINUED)

NA NO YES

ADD	ITION	AI.	COMN	JENT	'S '

Samples for MS/MSD for VOC analysis were not provided with this set of samples therefore lab used from another project.

Please use %D calculated based on Avg RF and CCRF for all compounds using Average Response Factor when the %RSD value for a compound is <15% for the Initial Calibration curve and use %D calculated based on Amount added and Calculated amount for all compounds using Linear Regression when the %RSD value for a compound is >15% for the Initial Calibration curve for SW-846 analysis.

QA REVIEW	Di	ate