## ALLIANCE 284 Sheffield Street, Mountainside New Jersey 07092 NEW JERSEY LAB ID#: 20012: NEW YORK LAB ID#: 11376

## GC/MS SEMI-VOLATILE ANALYSIS CONFORMANCE/NON-CONFORMANCE SUMMARY

MATRIX: Solid

CHEMTECH PROJECT NUMBER: P4495

METHOD: 8270E/3541

METIN	3D. 8210E/3341			
		37.4	wo	, ma
1.	Chromatograms Labeled/Compounds Identified. (Field samples and Method Blanks)	NA	NO	YES ✓
2.	GC/MS Tuning Specifications. DFTPP Meet Criteria. (NOTE THAT THERE ARE DIFFERENT CRITERIA FOR NY ASP CLP, CLP AND NJ)			✓
3.	GC/MS Tuning Frequency - Performed every 24 hours for 600 series and 12 hours for 8000 Series.			✓
4.	GC/MS Calibration - Initial Calibration performed within 30 days before sample analysis and continuing calibration performed within 24 hours of sample analysis for 600 series and 12 hours for 8000 series.			✓
5.	GC/MS Calibration Requirements.			✓
	The Initial Calibration met the requirements .  The Continuous Calibration met the requirements .			
6.	Blank Contamination - If yes, list compounds and concentrations in each blank:		✓	
7.	Surrogate Recoveries Meet Criteria			✓
	If not met, list those compounds and their recoveries which fall outside the acceptable ranges.			
8.	Matrix Spike/Matrix Spike Duplicate Recoveries Meet Criteria			✓
	If not met, list those compounds and their recoveries which fall outside the acceptable range.			
	The Blank Spike met requirements for all samples .			
9.	Internal Standard Area/Retention Time Shift Meet Criteria			✓
	Comments:			
10.	Extraction Holding Time Met			$\checkmark$
	If not met, list number of days exceeded for each sample:			

## ALLIANCE 284 Sheffield Street, Mountainside New Jersey 07092 NEW JERSEY LAB ID#: 20012: NEW YORK LAB ID#: 11376

## GC/MS SEMI-VOLATILE ANALYSIS CONFORMANCE/NON-CONFORMANCE SUMMARY (CONTINUED)

		NA	NO	YES
11.	Analysis Holding Time Met			✓
	If not met, list number of days exceeded for each sample:			
ADDIT	IONAL COMMENTS:			
Γhe For	m 6 is not included in the data package because the Initial Calibration was performed using	7 points	S.	
Please u	ise %D calculated based on Avg RF and CCRF for all compounds using Average Response	Factor v	vhen the	
%RSD	value for a compound is <15% for the Initial Calibration curve and use %D calculated based	l on Am	ount add	ed
and Cal	culated amount for all compounds using Linear Regression when the %RSD value for a con	npound i	is > 15%	for
he Initi	al Calibration curve for SW-846 analysis.			
OA RE'	VIEW Date			