

284 Sheffield Street, Mountainside, New Jersey 07092, Phone : 908 789

8900, Fax: 908 789 8922

## **Prep Standard - Chemical Standard Summary**

Order ID :	P4498
Test :	Mercury
Prepbatch ID :	PB164551,
Seguence ID/Oc Ra	teh ID: 1 B133224

Sequence ID/Qc Batch ID: LB133224,
Standard ID: MP82652,MP82654,MP82961,MP82962,MP82963,MP82964,MP82965,MP82966,MP82967,MP82968,MP82969,MP829 70,MP82971,MP82974,MP82975,
Chemical ID: M4371,M4916,M5062,M5501,M5882,M5953,M6095,M6104,W3112,



284 Sheffield Street, Mountainside, New Jersey 07092, Phone: 908 789 8900,

Fax: 908 789 8922

### Metals STANDARD PREPARATION LOG

Recipe ID	NAME.	NO.	Prep Date	Expiration Date	<u>Prepared</u> <u>By</u>	<u>ScaleID</u>	<u>PipetteID</u>	Supervised By Sarabjit Jaswal
65	POTASSIUM PERMANGANATE SOLUTION 5 %	MP82652	09/30/2024	04/03/2025		METALS_SCA LE_3 (M SC-3)		10/04/2024

**FROM** 100.00000gram of M4916 + 2000.00000ml of W3112 = Final Quantity: 2000.000 ml

Recipe ID	NAME	<u>NO.</u>	Prep Date	Expiration Date	<u>Prepared</u> <u>By</u>	<u>ScaleID</u>	<u>PipetteID</u>	Supervised By Sarabjit Jaswal
67	SODIUM CHLORIDE - HYDROXYL- CHLORIDE	MP82654	09/30/2024	04/03/2025		METALS_SCA LE_3 (M SC-3)		10/04/2024

FROM 2000.00000ml of W3112 + 240.00000gram of M4371 + 240.00000gram of M5501 = Final Quantity: 2000.000 ml



284 Sheffield Street, Mountainside, New Jersey 07092, Phone: 908 789 8900,

Fax: 908 789 8922

### Metals STANDARD PREPARATION LOG

Recipe ID	NAME_	NO.	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipetteID</u>	Supervised By Sarabjit Jaswal
871	MERCURY INTERMEDIATE B 250PPB WORKING STD.	MP82961	10/30/2024	10/31/2024	Mohan Bera		METALS_PIP ETTE_5 (HG	
							A)	

FROM 1.00000ml of M6104 + 2.50000ml of M5062 + 96.50000ml of W3112 = Final Quantity: 100.000 ml

Recipe ID	NAME	<u>NO.</u>	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipetteID</u>	Supervised By Sarabjit Jaswal
1340	Hg 0.00 PPB STD	MP82962	10/30/2024	10/31/2024	Mohan Bera		METALS_PIP ETTE_5 (HG	•

**FROM** 2.50000ml of M6104 + 247.50000ml of W3112 = Final Quantity: 250.000 ml





**Metals STANDARD PREPARATION LOG** 

Recipe ID	<u>NAME</u>	<u>NO.</u>	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipettelD</u>	Supervised By Sarabjit Jaswal
1341	Hg 0.2 PPB STD	MP82963	10/30/2024	10/31/2024	Mohan Bera	None	METALS_PIP ETTE_5 (HG	

**FROM** 2.50000ml of M6104 + 247.30000ml of W3112 + 0.20000ml of MP82961 = Final Quantity: 250.000 ml

Recipe ID	<u>NAME</u>	NO.	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipetteID</u>	Supervised By Sarabjit Jaswal
1342	Hg 2.5 PPB STD	MP82964	10/30/2024	10/31/2024	Mohan Bera		METALS_PIP ETTE_5 (HG	•

FROM 2.50000ml of M6104 + 245.0000ml of W3112 + 2.50000ml of MP82961 = Final Quantity: 250.000 ml





**Metals STANDARD PREPARATION LOG** 

ID N	NAME	<u>NO.</u>	Prep Date	<u>Date</u>	Ву	<u>ScaleID</u>	<u>PipetteID</u>	Supervised By Sarabjit Jaswal
1343 H	Hg 5.0 PPB STD	MP82965	10/30/2024	10/31/2024	Mohan Bera		METALS_PIP ETTE_5 (HG	

FROM 2.50000ml of M6104 + 242.50000ml of W3112 + 5.00000ml of MP82961 = Final Quantity: 250.000 ml

Recipe ID	NAME	<u>NO.</u>	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipetteID</u>	Supervised By Sarabjit Jaswal
1344	Hg 7.5 PPB STD	MP82966	10/30/2024	10/31/2024	Mohan Bera	None	METALS_PIP ETTE_5 (HG	•

FROM 2.50000ml of M6104 + 240.00000ml of W3112 + 7.50000ml of MP82961 = Final Quantity: 250.000 ml



 $284 \; Sheffield \; Street, \; Mountainside, \; New \; Jersey \; 07092, \; Phone \; : \; 908 \; 789 \; 8900, \\$ 

Fax: 908 789 8922

### **Metals STANDARD PREPARATION LOG**

Recipe ID	NAME	NO.	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipetteID</u>	Supervised By Sarabjit Jaswal
1345	Hg 10.0 PPB STD	MP82967	10/30/2024	10/31/2024	Mohan Bera		METALS_PIP ETTE_5 (HG	
							A)	

FROM 2.50000ml of M6104 + 237.50000ml of W3112 + 10.00000ml of MP82961 = Final Quantity: 250.000 ml

Recipe ID	NAME	<u>NO.</u>	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipettelD</u>	Supervised By Sarabjit Jaswal
1346	Hg ICV SOLUTION	MP82968	10/30/2024	10/31/2024	Mohan Bera		METALS_PIP ETTE_5 (HG	•

**FROM** 2.50000ml of M5953 + 2.50000ml of M6104 + 245.00000ml of W3112 = Final Quantity: 250.000 ml



284 Sheffield Street, Mountainside, New Jersey 07092, Phone: 908 789 8900,

Fax: 908 789 8922

### **Metals STANDARD PREPARATION LOG**

Recipe ID	NAME	NO.	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipetteID</u>	Supervised By Sarabjit Jaswal
1351	ICB (Hg 0.00 PPB SOLUTION)	MP82969	10/30/2024	10/31/2024	Mohan Bera		METALS_PIP ETTE_5 (HG	
							A)	

**FROM** 2.50000ml of M6104 + 247.50000ml of W3112 = Final Quantity: 250.000 ml

Recipe				Expiration	Prepared			Supervised By
<u>ID</u>	<u>NAME</u>	<u>NO.</u>	Prep Date	<u>Date</u>	<u>By</u>	<u>ScaleID</u>	<u>PipetteID</u>	Sarabjit Jaswal
1358	CCV (Hg 5.0 PPB SOLUTION)	MP82970	10/30/2024	10/31/2024	Mohan Bera		METALS_PIP	
							ETTE_5 (HG	10/31/2024

FROM 485.00000ml of W3112 + 5.00000ml of M6104 + 10.00000ml of MP82961 = Final Quantity: 500.000 ml



 $284 \; Sheffield \; Street, \; Mountainside, \; New \; Jersey \; 07092, \; Phone \; : \; 908 \; 789 \; 8900, \\$ 

Fax: 908 789 8922

### **Metals STANDARD PREPARATION LOG**

Recipe ID	NAME_	NO.	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipetteID</u>	Supervised By Sarabjit Jaswal
1352	CCB (Hg 0.00 PPB SOLUTION)	MP82971	10/30/2024	10/31/2024	Mohan Bera		METALS_PIP ETTE_5 (HG	
							A)	

**FROM** 495.00000ml of W3112 + 5.00000ml of M6104 = Final Quantity: 500.000 ml

Recipe ID	NAME	<u>NO.</u>	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipettelD</u>	Supervised By Sarabiit Jaswal
887	AQUA REGIA FOR HG ON 7471A	MP82974	10/30/2024	10/31/2024	Mohan Bera		METALS_PIP ETTE_5 (HG	,

FROM 150.00000ml of M6095 + 50.00000ml of M6104 = Final Quantity: 200.000 ml



284 Sheffield Street, Mountainside, New Jersey 07092, Phone: 908 789 8900,

Fax: 908 789 8922

### **Metals STANDARD PREPARATION LOG**

Recipe ID 68		NO. MP82975	Prep Date 10/30/2024	Expiration Date 10/31/2024		ScaleID METALS_SCA	Supervised By Sarabjit Jaswal
	SOLUTION					LE_3 (M SC-3)	10/31/2024
FROM	450.0000ml of W3112 + 50.00000gr	ram of M588	32 + 50.00000	oml of M6095 =	Final Quantity	: 500.000 ml	



## **CHEMICAL RECEIPT LOG BOOK**

Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
Seidler Chemical	BA-2196-01 / Hydroxylamine Hydrochloride, Crystal (cs/4x500g)	0000215387	06/25/2025	07/01/2019 / RICHARD	06/07/2019 / RICHARD	M4371
Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
Seidler Chemical	BA-3227-05 / Potassium Permanganate (2.5kg)	210800	03/31/2026	11/30/2022 / mohan	07/28/2021 / mohan	M4916
Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
Inorganic Ventures	MSHG-10PPM / MERCURY HCI 125mL 10ug/mL	S2-HG709270	09/22/2026	05/28/2022 / mohan	01/27/2022 / mohan	M5062
Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
Seidler Chemical	BA-3624-05 / Sodium Chloride, Crystal	0000281938	07/06/2026	07/24/2023 / mohan	04/14/2023 / mohan	M5501
	(cs/4x2.5kg)					
Supplier	(cs/4x2.5kg)  ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date /	Chemtech Lot #
Supplier Seidler Chemical	<u> </u>	Lot # 232820		=		
	ItemCode / ItemName  BA-3980-01 / Stannous		Date	Opened By 04/30/2024 /	<b>Received By</b> 04/25/2024 /	Lot #



Fax: 908 789 8922

## **CHEMICAL RECEIPT LOG BOOK**

Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
Seidler Chemical	BA-9530-33 / Hydrochloric Acid, Instra-Analyzed (cs/6x2.5L)		03/17/2029	10/26/2024 / Janvi	10/21/2024 / Janvi	M6095

Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
Seidler Chemical	BA-9598-34 / Nitric Acid, Instra-Analyzed (cs/4x2.5L)	24D1062002	04/30/2025	10/30/2024 / Eman	09/29/2024 / Janvi	M6104

Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
Seidler Chemical	DIW / DI Water	Daily Lab-Certified	07/03/2029	07/03/2024 / lwona	07/03/2024 / Iwona	W3112





1 Reagent Lane Fair Lawn, NJ 07410 201,796,7100 tel

Thermo Fisher Scientific's Quality System has been found to conform to Quality Management System

Standard ISO9001:2015 by SAI Global Certificate Number CERT - 0120633 201,796,1329 fax

This is to certify that units of the lot number below were tested and found to comply with the specifications of the grade listed. Certain data have been supplied by third parties. Thermo Fisher Scientific expressly disclaims all warranties, expressed or implied, including the implied warranties of merchantability and fitness for a particular purpose. Products are for research use or further manufacturing. Not for direct administration to humans or animals. It is the responsibility of the final formulator and end user to determine suitability based upon the intended use of the end product. Products are tested to meet the analytical requirements of the noted grade. The following information is the actual analytical results obtained.

Catalog Number	T142	Quality Test / Release Date	08/17/2023				
Lot Number	232820						
Description	STANNOUS CHLORIDE, DIHYDRATE CERTIFIED ACS (Suitable for Mercury Determination)						
Country of Origin	United States	Suggested Retest Date	Aug/2028				
Chemical Origin	Inorganic-non animal						
BSE/TSE Comment	No animal products are used as sta processing aids, or any other mater	arting raw material ingredients, or used rial that might migrate to the finished pr	in processing, including lubricants, oduct.				

N/A	H. M. C. S. C.		Was I will still
Result Name	Units	Specifications	Test Value
APPEARANCE		REPORT	Clear crystals
ASSAY	%	Inclusive Between 98 - 103	100.65
CALCIUM	%	<= 0.005	0.0017
IDENTIFICATION	PASS/FAIL	= PASS TEST	PASS TEST
IRON (Fe)	%	<= 0.003	0.0011
LEAD (Pb)	%	<= 0.01	0.0006
MERCURY (Hg)	ppm	<= 0.05	<0.05
POTASSIUM (K)	%	<= 0.005	0.0001
SODIUM (Na)	%	<= 0.01	<0.01
SOLUBILITY IN HCL	PASS/FAIL	= PASS TEST	PASS TEST
SULFATE (SO4)	PASS/FAIL	= P.T. (ABOUT 0.003%)	P.T. (ABOUT 0.003%)

Harout Sahagian - Quality Control Supervisor - Fair Lawn

M4371

Hydroxylamine Hydrochloride, Crystal BAKER ANALYZED® A.C.S. Reagent

Suitable for Mercury Determination (hydroxylammonium chloride)

Rec - 06.07.12





Material No.: 2196-01

Batch No.: 0000215387

Manufactured Date: 2018/06/27 Retest Date: 2025/06/25

Revision No: 1

## Certificate of Analysis

Meets ACS Reagent Chemical Requirements,

Specification	Result
>= 96.0 %	99.1
Passes Test	PT
<= 0.050 %	0.017
<= 0.25	0.19
Passes Test	PT
<= 0.005 %	< 0.003
<= 5 ppm	4
<= 5 ppm	< 3
<= 0.050 ppm	< 0.005
	>= 96.0 % Passes Test <= 0.050 % <= 0.25 Passes Test <= 0.005 % <= 5 ppm <= 5 ppm

For Laboratory, Research or Manufacturing Use

Country of Origin:

CN

Packaging Site:

Paris Mfg Ctr & DC



Phillipsburg, NJ 9001:2015, FSSC22000
Paris, KY 9001:2008
Mexico City, Mexico 9001:2008
Gliwice, Poland 9001:2015, 13485:2012
Selangor, Malaysia 9001:2008
Dehradun, India, 9001:2008, 14001:2004, 13485:2003
Mumbai, India, 9001:2015, 17025:2005
Panoli, India 9001:2015

Jamie Ethier
Vice President Global Quality



M4913- 16



## Certificate of Analysis

1 Reagent Lane Fair Lawn, NJ 07410 201.796.7100 tel 201.796.1329 fax

Thermo Fisher Scientific's Quality System has been found to conform to Quality Management System Standard ISO9001:2015 by SAI Global Certificate Number CERT – 0120632

This is to certify that units of the lot number below were tested and found to comply with the specifications of the grade listed. Certain data have been supplied by third parties. Thermo Fisher Scientific expressly disclaims all warranties, expressed or implied, including the implied warranties of merchantability and fitness for a particular purpose. Products are for research use or further manufacturing. Not for direct administration to humans or animals. It is the responsibility of the final formulator and end user to determine suitability based upon the intended use of the end product. Products are tested to meet the analytical requirements of the noted grade. The following information is the actual analytical results obtained.

Catalog Number	P279	Quality Test / Release Date	01/12/2021
Lot Number	210306		
Description	POTASSIUM PERMANGANATE, A.C.S.		
Country of Origin	United States	Suggested Retest Date	Jan/2026

N/A				
Result Name	Units	Specifications	Test Value	
APPEARANCE		REPORT	Dark purple to purple green crystals	
ASSAY	%	>= 99	99.3	
CHLORIDE & CHLORATE	%	<= 0.005	<0.005	
IDENTIFICATION	PASS/FAIL	= PASS TEST	pass test	
INSOLUBLE MATTER	%	<= 0.2	<0.2	
MERCURY (Hg)	ppm	<= 0.05	<0.004	
SULFATE (SO4)	%	<= 0.02	<0.02	

Julian Burton

Julian Burton - Quality Control Manager - Fair Lawn



# Certificate of Analysis

300 Technology Drive Christiansburg, VA 24073 USA inorganicventures.com M5062 M5063

P: 800-669-6799/540-585-3030 F: 540-585-3012 info@inorganicventures.com

#### 1.0 ACCREDITATION / REGISTRATION

**INORGANIC VENTURES** is accredited to ISO 17034, "General Requirements for the Competence of Reference Material Producers" and ISO/IEC 17025, "General Requirements for the Competence of Testing and Calibration Laboratories". Inorganic Ventures is also an ISO 9001 registered manufacturer (QSR Certificate Number QSR-1034).



#### 2.0 PRODUCT DESCRIPTION

Product Code:

Single Analyte Mass Spec Solution

Catalog Number:

MSHG-10PPM

Lot Number:

S2-HG709270

Matrix:

10% (v/v) HCI

Value / Analyte(s):

10 μg/mL ea:

Mercury

Starting Material:

Hg metal

Starting Material Lot#:

1959

Starting Material Purity:

99.9994%

#### 3.0 CERTIFIED VALUES AND UNCERTAINTIES

**Certified Value:** 

 $10.001 \pm 0.053 \,\mu g/mL$ 

Density:

1.020 g/mL (measured at 20 ± 4 °C)

#### **Assay Information:**

ANALYTE	METHOD	NIST SRM#	SRM LOT#
Hg	ICP Assay	3133	160921
Hg	EDTA	928	928
Ha	Calculated		See Sec. 4.2

The following equations are used in the calculation of the certified value and the uncertainty. Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of k = 2.

#### Characterization of CRM/RM by Two or More Methods

Certified Value, X<sub>CRM/RM</sub>, where two or more methods of characterization are used is the weighted mean of the results:

 $X_{CRM/RM} = \Sigma(w_i) (X_i)$ 

 $\mathbf{X_i}$  = mean of Assay Method i with standard uncertainty  $\mathbf{u_{char}}$  i

w<sub>i</sub> = the weighting factors for each method calculated using the inverse square of

the variance.

 $\mathbf{w_i} = (1/u_{chari})^2 / (\Sigma (1/(u_{chari})^2)$ 

CRM/RM Expanded Uncertainty (±) =  $U_{CRM/RM} = k (u_{char}^2 + u_{bb}^2 + u_{its}^2 + u_{ts}^2)^{1/2}$ 

k = coverage factor = 2

 $u_{char} = [\Sigma((w_i)^2 (u_{char})^2)]^{\frac{1}{2}}$  where  $u_{char}$  i are the errors from each characterization method

u<sub>bb</sub> = bottle to bottle homogeneity standard uncertainty

ults = long term stability standard uncertainty (storage)

uts = transport stability standard uncertainty

#### Characterization of CRM/RM by One Method

Certified Value,  $X_{CRM/RM}$ , where one method of characterization is used is the mean of individual results:

X<sub>CRM/RM</sub> = (X<sub>a</sub>) (u<sub>char a</sub>)

Xa = mean of Assay Method A with

uchar a = the standard uncertainty of characterization Method A

CRM/RM Expanded Uncertainty (±) = U<sub>CRM/RM</sub> = k (u<sup>2</sup>char a + u<sup>2</sup>bb + u<sup>2</sup>lts + u<sup>2</sup>ts) 1/2

k = coverage factor = 2

u<sub>char a</sub> = the errors from characterization

ubb = bottle to bottle homogeneity standard uncertainty

u<sub>lts</sub> = long term stability standard uncertainty (storage)

uts = transport stability standard uncertainty

#### 4.0 TRACEABILITY TO NIST

- This product is traceable to NIST via an unbroken chain of comparisons. The uncertainties for each certified value are reported, taking into account the SRM/RM uncertainty error and the measurement, weighing and volume dilution errors. In rare cases where no NIST SRM/RM are available, the term 'in-house std.' is specified.

#### 4.1 Thermometer Calibration

- All thermometers are NIST traceable through thermometers that are calibrated by an accredited calibration laboratory.

#### 4.2 Balance Calibration

- All analytical balances are calibrated by an accredited calibration laboratory and procedure. The weights used for testing are annually compared to master weights and are traceable to NIST.

#### 4.3 Glassware Calibration

- An in-house procedure is used to calibrate all Class A glassware used in the manufacturing and quality control of CRM/RMs.

#### 5.0 TRACE METALLIC IMPURITIES (TMI) DETERMINED BY ICP-MS AND ICP-OES (µg/mL)

CRM/RMs are tested for trace metallic impurities by Axial ICP-OES and ICP-MS. The result from the most sensitive method for each element, is reported below. Solutions tested by ICP-MS were analyzed in an ULPA-Filtered Clean Room. An ULPA-Filter is 99.9985% efficient for the removal of particles down to 0.3 µm.

```
O Ag
          0.000011 M Eu <
                            0.000201 O Na
                                              0.000004 M Se <
                                                               0.015915 O Zn <
                                                                                 0.001510
0
   Al
          0.000001 O Fe
                            0.000001 M Nb <
                                              0.000201 O Si
                                                                0.000005 M Zr <
                                                                                 0.000201
M
   As <
          0.000402 M Ga <
                            0.000201 M Nd <
                                              0.000201 M Sm <
                                                               0.000201
M
   Au <
          0.003631 M Gd <
                            0.000201 M Ni <
                                              0.000402 M
                                                        Sn <
                                                               0.001007
M
   B <
          0.001208 M
                    Ge <
                            0.000201 M Os <
                                              0.000605 M
                                                        Sr <
                                                               0.000201
M Ba <
          0.000201 M Hf <
                            0.000201 O P <
                                              0.032370 M
                                                        Ta <
                                                               0.000201
M
  Be <
          0.000201 s
                                   M Pb <
                    Hq <
                                              0.000201 M Tb <
                                                               0.000201
M Bi <
          0.000201 M
                    Ho <
                            0.000201 M Pd <
                                              0.000403 M
                                                        Te <
                                                               0.002216
0
  Ca
          0.000007 M In <
                            0.000201 M Pr <
                                              0.000201 M Th <
                                                               0.000201
M
  Cd <
          0.000201 M Ir
                            0.000201 M
                                      Pt <
                                              0.000402 M Ti <
                                                               0.000402
                                              0.000201 O TI <
M
  Ce <
          0.000201 O K
                            0.000020 M
                                      Rb <
                                                               0.016508
  Co <
M
          0.000201 M La <
                            0.000201 M
                                      Re <
                                              0.000201 M Tm <
                                                               0.000201
  Cr <
0
          0.003021 O Li <
                            0.000107 M
                                      Rh <
                                              0.000201 M U <
                                                               0.008058
M
  Cs <
          0.001208 M Lu <
                            0.000201 M Ru <
                                              0.000201 M V <
                                                               0.000201
M
  Cu <
          0.000402 O
                    Mg
                            0.000001 O
                                      S <
                                             0.053950 M W <
                                                               0.000604
M Dy <
          0.000201 M Mn <
                            0.000604 M Sb <
                                             0.001208 M Y <
                                                               0.000201
M Er <
          0.000201 M Mo
                           0.000009 M Sc <
                                             0.000201 M Yb <
                                                               0.000201
```

M - Checked by ICP-MS O - Checked by ICP-OES i - Spectral Interference n - Not Checked For s - Solution Standard Element

#### 6.0 INTENDED USE

- For the calibration of analytical instruments and validation of analytical methods as appropriate.

#### 7.0 INSTRUCTIONS FOR THE CORRECT USE OF THIS REFERENCE MATERIAL

#### 7.1 Storage and Handling Recommendations

- Store between approximately 4° 30° C while in sealed TCT bag.
- While stored in the sealed TCT bag, transpiration of this CRM/RM is negligible. After opening the sealed TCT bag transpiration of the CRM/RM will occur, resulting in a gradual increase in the analyte concentration(s). It is the responsibility of the user to account for this effect. When the bottle is weighed both before and after being placed in storage, the mass difference observed will be a measure of transpiration mass loss.
- After opening the sealed TCT bag, keep cap tightly sealed when not in use and store between  $4^{\circ}$   $24^{\circ}$  C to minimize the effects of transpiration. Use at  $20^{\circ} \pm 4^{\circ}$  C to minimize volumetric dilution error when using the reported density. Do not pipette from the container. Do not return removed aliquots to container.
- For more information, visit www.inorganicventures.com/TCT

**Atomic Weight; Valence; Coordination Number; Chemical Form in Solution -** 200.59 +2 4 Hg(OH)(aq) 1+ **Chemical Compatibility -** Stable in HNO3. Avoid basic media forming insoluble carbonate. The sulfide, basic carbonate, oxalate, phosphate, arsenite, arsenate and iodide are insoluble in water.

**Stability -** 2-100 ppb levels not stable in 1% HNO3 / LDPE container, stable in 10% HNO3 packaged in borosilicate glass. 1-100 ppm levels stable in 7% HNO3 packaged in borosilicate glass. 1000-10,000 ppm solutions are chemically stable for years in 5-10% HNO3 / LDPE container.

**Hg Containing Samples (Preparation and Solution) -** Metal (soluble in HNO3); Oxide (Soluble in HNO3); Ores and Organic based (The literature has more references to the preparation of Hg containing samples than any other element. Please consult the literature for your specific sample type, since such preparations are prone to error. Or e-mail our technical staff and we will contact you to discuss your particular sample preparation questions in further detail.).

Atomic Spectroscopic Information (ICP-OES D.L.s are given as radial/axial view):

Technique/Line	Estimated D.L.	Order	Interferences (underlined indicates severe)
ICP-MS 202 amu	9 ppt	n/a	186W16O
ICP-OES 184.950 nm	0.03 / 0.005 μg/mL	1	
ICP-OES 194.227 nm	0.03 / 0.005 µg/mL	1	V
ICP-OES 253.652 nm	0.1 / 0.03 µg/mL	1	Ta, Co, Th, Rh, Fe,
			U

#### 8.0 HAZARDOUS INFORMATION

- Please refer to the Safety Data Sheet for information regarding this CRM/RM.

#### 9.0 HOMOGENEITY

- This solution was mixed according to an in-house procedure and is guaranteed to be homogeneous. Homogeneity data indicate that the end user should take a minimum sample size of 0.2 mL to assure homogeneity.

#### 10.0 QUALITY STANDARD DOCUMENTATION

#### 10.1 ISO 9001 Quality Management System Registration

- QSR Certificate Number QSR-1034

#### 10.2 ISO/IEC 17025 "General Requirements for the Competence of Testing and Calibration Laboratories"

- Chemical Testing - Accredited / A2LA Certificate Number 883.01

#### 10.3 ISO 17034 "General Requirements for the Competence of Reference Material Producers"

- Reference Material Producer - Accredited / A2LA Certificate Number 883.02

Inorganic Ventures, 300 Technology Drive, Christiansburg, Va. 24073, USA; Telephone: 800.669.6799; 540.585.3030, Fax: 540.585.3012; inorganicventures.com; info@inorganicventures.com

#### 11.0 CERTIFICATION, LOT EXPIRATION AND PERIOD OF VALIDITY

#### 11.1 Certification Issue Date

September 22, 2021

- The certification is valid within the measurement uncertainty specified provided the CRM/RM is stored and handled in accordance with instructions given in Sec 7.1. This certification is nullified if instructions in Sec 7.1 are not followed or if the CRM/RM is damaged, contaminated, or otherwise modified.

#### 11.2 Lot Expiration Date

- September 22, 2026
- The date after which this CRM/RM should not be used.
- The lot expiration date reflects the period of time that the stability of a CRM/RM can be supported by long term stability studies conducted on properly stored and handled CRM/RMs. Lot expiration is limited primarily by transpiration (loss of water from the solution) and infrequently by chemical stability.

#### 11.3 Period of Validity

Sealed TCT	Bag	Open Date	:		

- This CRM/RM should not be used longer than one year (or six months in the case of a 30 mL bottle) from the date of opening the aluminized bag or after the date given in Sec. 11.2, whichever comes first. This is contingent upon the CRM/RM being stored and handled in accordance with the instructions given in Sec. 7.1.

## 12.0 NAMES AND SIGNATURES OF CERTIFYING OFFICERS Certificate Prepared By:

Uyen Truong
Supervisor, Product Documentation

Mya Truong


#### Certificate Approved By:

Michael Booth Director, Quality Control Michael 2 Booth

#### Certifying Officer:

Paul Gaines Chairman / Senior Technical Director Paul R Laines

Sodium Chloride, Crystal







Material No.: 3624-01

Batch No.: 0000281938

Manufactured Date: 2021-06-07

Retest Date: 2026-06-07

Revision No.: 2

## **Certificate of Analysis**

Test	Specification	Result
Assay (NaCl) (by Ag titrn)	≥ 99.0 %	100.0 %
pH of 5% Solution at 25°C	5.0 - 9.0	6.3
Insoluble Matter	≤ 0.005 %	0.003 %
lodide (I)	≤ 0.002 %	< 0.002 %
Bromide (Br)	≤ 0.01 %	< 0.01 %
Chlorate and Nitrate (as NO₃)	≤ 0.003 %	< 0.001 %
ACS - Phosphate (PO <sub>4</sub> )	≤ 5 ppm	< 5 ppm
Sulfate (SO <sub>4</sub> )	≤ 0.004 %	< 0.004 %
Barium (Ba)	Passes Test	Passes Test
ACS - Heavy Metals (as Pb)	≤ 5 ppm	< 5 ppm
Iron (Fe)	≤ 2 ppm	< 1 ppm
Calcium (Ca)	≤ 0.002 %	< 0.001 %
Magnesium (Mg)	≤ 0.001 %	< 0.001 %
Potassium (K)	≤ 0.005 %	0.001 %

For Laboratory, Research, or Manufacturing Use Meets Reagent Specifications for testing USP/NF monographs Country of Origin: USA Packaging Site: Paris Mfg Ctr & DC





## QUALITY ASSURANCE TECHNICAL SUPPORT LABORATORY "An ISO 9001:2015 Certified Program"

Instructions for QATS Reference Material: Inorganic ICV Solutions

### QATS LABORATORY INORGANIC REFERENCE MATERIAL INITIAL CALIBRATION VERIFICATION SOLUTIONS (ICV1, ICV5, AND ICV6)

These instructions are for advisory purposes only. If any apparent conflict exists between these instructions and the analytical protocol or your contract, disregard these instructions.

APPLICATION:

For use with the CLP SFAM01.0 SOW and revisions.

**CAUTION:** 

Read instructions carefully before opening bottle(s) and proceeding with

the analyses.

Contains Metals in Dilute Acidic or Cyanide in Basic Aqueous Solutions HAZARDOUS MATERIAL

> Safety Data Sheets Available Upon Request

### (A) SAMPLE DESCRIPTION

Enclosed is a set of one (1) or more Aqueous Inorganic Reference Materials containing various analyte concentrations. ICV1 and ICV5 are in a matrix of dilute nitric acid. ICV6 is in a matrix of dilute basic solution. For the reference material source in reporting ICVs use "USEPA". For the reference material lot number for the ICV1, ICV5, and ICV6 solutions use "ICV1-1014", "ICV5-0415", and "ICV6-0400", respectively.

## (B) BREAKAGE OR MISSING ITEMS

Check the contents of the shipment carefully for any broken, leaking, or missing items. Check that the seal is intact on each bottle. Refer to the enclosed chain of custody record. Report any problems to Mr. Keith Strout, APTIM Federal Services, LLC, at (702) 895-8722. If requested, return the chain-of-custody record with appropriate annotations and signatures to the address provided

> QUALITY ASSURANCE TECHNICAL SUPPORT LABORATORY **APTIM Federal Services, LLC** 2700 Chandler Avenue - Building C Las Vegas, NV 89120

### (C) ANALYSIS OF SAMPLES

The Initial Calibration Verification Solutions (ICVs) are to be used to evaluate the accuracy of the initial calibrations of ICP, AA, and Cyanide colorimetric instruments, and are to be used with the CLP SOWs and revisions. The values for each element in the ICVs are listed below in µg/L (ppb) for the resulting solution(s) after the dilution of the concentrate(s) according to the following instructions. Use Class 'A' glassware to prepare the solution(s).

ICV1-1014

For ICP-AES analysis, use a 10-fold dilution by pipetting 10 mL of the ICV1 concentrate into a 100 mL volumetric flask and dilute to volume with 2% (v/v) nitric

Page 1 of 2









## QUALITY ASSURANCE TECHNICAL SUPPORT LABORATORY "An ISO 9001:2015 Certified Program"

# Instructions for QATS Reference Material: Inorganic ICV Solutions

ICV1-1014

For ICP-MS analysis, use a 50-fold dilution by pipetting 2 mL of the ICV1 concentrate into a 100 mL volumetric flask and dilute to volume with 1% (v/v) nitric acid.

ICV5-0415

For the cold vapor analysis of mercury by AA, use a 100-fold dilution by pipetting 1 mL of the ICV5 concentrate into a 100 mL volumetric flask and dilute to volume with 2% (v/v) nitric acid. The ICV5 concentrate is prepared in 0.05% (w/v) K<sub>2</sub>Cr<sub>2</sub>O<sub>7</sub> and 5% (v/v) nitric acid.

ICV6-0400

For the analysis of cyanide, use a 100-fold dilution by pipetting 1 mL of the ICV6 concentrate into a 100 mL volumetric flask and dilute to volume with Type II water. Distill this solution along with the samples before analysis. The cyanide concentrate is prepared from K₃Fe(CN)₅, Type II water, and 0.1 % sodium hydroxide, and will decompose rapidly if exposed to light.

NOTE: USE TYPE II WATER AND HIGH-PURITY ACIDS FOR ALL DILUTIONS.

# (D) CERTIFIED CONCENTRATIONS OF QATS ICV1, ICV5, AND ICV6 SOLUTIONS

	ICV1-1014	
Element	Concentration (µg/L) (after 10-fold dilution)	Concentration (µg/L)
Al	2500	(after 50-fold dilution
Sb	1000	500
As	1000	200
Ba	520	200
Be	510	100
Cd	510	100
Ca	10000	100
Cr	520	2000
Co		100
Cu	520	100
Fe	510	100
Pb	10000	2000
Mg	1000	200
Mn	6000	1200
Ni	520	100
K	530	110
Se	9900	2000
Ag	1000	200
Na	250	50
TI	10000	2000
V	1000	210
Zn	500	100
	1000	200


	ICV5-0415		ICV6-0400
Element	Concentration (µg/L) (after 100-fold dilution)	Analyte	Concentration (µg/L) (after 100-fold dilution
Hg	4.0	CN-	99

Hydrochloric Acid, 36.5-38.0% BAKEŘ INSTRA-ANALYZED® Reagent For Trace Metal Analysis





M6095.



Material No.: 9530-33 Batch No.: 24D1562005 Manufactured Date: 2024-03-18 Retest Date: 2029-03-17

Revision No.: 0

## Certificate of Analysis

Test	Specification	Result
ACS - Assay (as HCl) (by acid-base titrn)	36.5 - 38.0 %	37.6 %
ACS - Color (APHA)	≤ 10	5
ACS – Residue after Ignition	≤ 3 ppm	< 1 ppm
ACS - Specific Gravity at 60°/60°F	1.185 - 1.192	1.192
ACS - Bromide (Br)	≤ 0.005 %	< 0.005 %
ACS - Extractable Organic Substances	≤ 5 ppm	< 1 ppm
ACS - Free Chlorine (as Cl2)	≤ 0.5 ppm	< 0.5 ppm
Phosphate (PO <sub>4</sub> )	≤ 0.05 ppm	0.03 ppm
Sulfate (SO <sub>4</sub> )	≤ 0.5 ppm	< 0.3 ppm
Sulfite (SO <sub>3</sub> )	≤ 0.8 ppm	0.3 ppm
Ammonium (NH <sub>4</sub> )	≤ 3 ppm	< 1 ppm
Trace Impurities - Arsenic (As)	≤ 0.010 ppm	< 0.003 ppm
Trace Impurities - Aluminum (AI)	≤ 10.0 ppb	< 5.0 ppb
Arsenic and Antimony (as As)	≤ 5.0 ppb	< 3.0 ppb
Trace Impurities - Barium (Ba)	≤ 1.0 ppb	< 1.0 ppb
Trace Impurities - Beryllium (Be)	≤ 1.0 ppb	< 1.0 ppb
Trace Impurities - Bismuth (Bi)	≤ 10.0 ppb	< 10.0 ppb
Trace Impurities - Boron (B)	≤ 20.0 ppb	2.2 ppb
Trace Impurities - Cadmium (Cd)	≤ 1.0 ppb	< 1.0 ppb
Trace Impurities - Calcium (Ca)	≤ 50.0 ppb	31.0 ppb
Trace Impurities - Chromium (Cr)	≤ 1.0 ppb	0.5 ppb
Trace Impurities - Cobalt (Co)	≤ 1.0 ppb	0.2 ppb
Trace Impurities - Copper (Cu)	≤ 1.0 ppb	< 0.1 ppb
Trace Impurities – Gallium (Ga)	≤ 1.0 ppb	< 0.2 ppb
Trace Impurities - Germanium (Ge)	≤ 3.0 ppb	< 2.0 ppb
Trace Impurities - Gold (Au)	≤ 4.0 ppb	< 0.2 ppb
Heavy Metals (as Pb)	≤ 100 ppb	< 50 ppb
Trace Impurities - Iron (Fe)	≤ 15 ppb	3 ppb

>>> Continued on page 2 >>>





Material No.: 9530-33 Batch No.: 24D1562005

Test	Specification	Result
Trace Impurities – Lead (Pb)	≤ 1.0 ppb	< 0.2 ppb
Trace Impurities - Lithium (Li)	≤ 1.0 ppb	< 0.1 ppb
Trace Impurities – Magnesium (Mg)	≤ 10.0 ppb	2.2 ppb
Trace Impurities – Manganese (Mn)	≤ 1.0 ppb	< 0.2 ppb
Trace Impurities - Mercury (Hg)	≤ 0.5 ppb	< 0.1 ppb
Trace Impurities – Molybdenum (Mo)	≤ 10.0 ppb	< 5.0 ppb
Trace Impurities - Nickel (Ni)	≤ 4.0 ppb	0.2 ppb
Trace Impurities - Niobium (Nb)	≤ 1.0 ppb	< 0.2 ppb
Trace Impurities - Potassium (K)	≤ 9.0 ppb	< 1.0 ppb
Trace Impurities - Selenium (Se), For Information Only		< 1.0 ppb
Trace Impurities - Silicon (Si)	≤ 100.0 ppb	< 10.0 ppb
Trace Impurities - Silver (Ag)	≤ 1.0 ppb	< 0.3 ppb
Trace Impurities - Sodium (Na)	≤ 100.0 ppb	2.0 ppb
Trace Impurities – Strontium (Sr)	≤ 1.0 ppb	< 0.2 ppb
Trace Impurities – Tantalum (Ta)	≤ 1.0 ppb	< 0.9 ppb
Trace Impurities – Thallium (Tl)	≤ 5.0 ppb	< 2.0 ppb
Trace Impurities - Tin (Sn)	≤ 5.0 ppb	< 0.4 ppb
Trace Impurities – Titanium (Ti)	≤ 1.0 ppb	0.2 ppb
Trace Impurities - Vanadium (V)	≤ 1.0 ppb	< 0.2 ppb
Trace Impurities – Zinc (Zn)	≤ 5.0 ppb	< 0.2 ppb
Trace Impurities – Zirconium (Zr)	≤ 1.0 ppb	< 0.1 ppb

Hydrochloric Acid, 36.5-38.0%

BAKER IÑŚTRA-ANALYZED® Reagent
For Trace Metal Analysis





Material No.: 9530-33 Batch No.: 24D1562005

Test Specification Result

For Laboratory, Research, or Manufacturing Use Product Information (not specifications): Appearance (clear, fuming liquid) Meets ACS Specifications Storage Condition: Store below 25 °C.

Country of Origin: USA

Packaging Site: Phillipsburg Mfg Ctr & DC



Receive date: Avantor



Material No.: 9606-03 Batch No.: 24D1062002 Manufactured Date: 2024-03-26 Retest Date: 2029-03-25 Revision No.: 0

# Certificate of Analysis

Assay (HNO₂) Appearance Passes Test Passes Test Passes Test Color (APHA)  Residue after Ignition  Chloride (Cl) Phosphate (PO₄)  Sulfate (SO₄)  Sulfate (SO₄)  Trace Impurities - Barrium (Ba)  Trace Impurities - Cadmium (Cd)  Trace Impurities - Cadmium (Cd)  Trace Impurities - Cobper (Cu)  Trace Impurities - Cooper (Cu)  Trace Impurities - Cooper (Cu)  Trace Impurities - Cooper (Cu)  Trace Impurities - Gold (Au)  Frace Impurities - Germanium (Ge)  Trace Impurities - Germanium (Ge)  Trace Impurities - Gold (Au)  Frace Impurities - Gold (Au)  Frace Impurities - Gold (Mu)  Frace Impurities - Cooper (Fe)  Trace Impurities - Cooper (Cu)  Trace Impurities - Lithium (Li)  Trace Impurities - Manganese (Mn)  Trace Impurities - Manganese (Mn)  Trace Impurities - Manganese (Mn)  Trace Impurities - Manganese (Mn)	Test	Specification	Result
Appearance Color (APHA) ≤ 10 5 Residue after Ignition ≤ 2 ppm 1 ppm Chloride (Cl) ≤ 0.08 ppm < 0.03 ppm Phosphate (PO4) ≤ 0.10 ppm < 0.03 ppm Sulfate (SO4) ≤ 0.10 ppm < 0.2 ppm < 0.2 ppm Trace Impurities - Aluminum (Al) ≤ 40.0 ppb < 1.0 ppb Trace Impurities - Barium (Ba) ≤ 10.0 ppb < 1.0 ppb Trace Impurities - Birmuth (Bi) ≤ 20.0 ppb < 10.0 ppb Trace Impurities - Birmuth (Bi) ≤ 20.0 ppb < 10.0 ppb Trace Impurities - Cadmium (Cd) ≤ 50 ppb < 5.0 ppb Trace Impurities - Cadmium (Cd) ≤ 50 ppb < 1.0 ppb Trace Impurities - Calcium (Ca) ≤ 50.0 ppb < 1.0 ppb Trace Impurities - Calcium (Ca) ≤ 50.0 ppb < 1.0 ppb Trace Impurities - Cobalt (Co) ≤ 10.0 ppb < 1.0 ppb Trace Impurities - Cobalt (Co) ≤ 10.0 ppb < 1.0 ppb Trace Impurities - Copper (Cu) ≤ 10.0 ppb < 1.0 ppb Trace Impurities - Gold (Au) ≤ 20 ppb < 1.0 ppb Trace Impurities - Gold (Au) ≤ 20 ppb < 1.0 ppb Trace Impurities - Gold (Au) ≤ 20 ppb < 5 ppb Trace Impurities - Gold (Au) ≤ 20 ppb < 1.0 ppb Trace Impurities - Lead (Pb) ≤ 20.0 ppb < 1.0 ppb Trace Impurities - Lead (Pb) ≤ 20.0 ppb < 1.0 ppb Trace Impurities - Lead (Pb) ≤ 20.0 ppb < 1.0 ppb Trace Impurities - Lead (Pb) ≤ 20.0 ppb < 10.0 ppb Trace Impurities - Lead (Pb) ≤ 20.0 ppb < 10.0 ppb Trace Impurities - Lead (Pb) ≤ 20.0 ppb < 10.0 ppb Trace Impurities - Lead (Pb) ≤ 20.0 ppb < 10.0 ppb Trace Impurities - Lead (Pb) ≤ 20.0 ppb < 10.0 ppb Trace Impurities - Magnesium (Mg) ≤ 20 ppb < 1.0 ppb	Assay (HNO <sub>3</sub> )	69.0 - 70.0 %	
Color (APHA)       ≤ 10       5         Residue after Ignition       ≤ 2 ppm       1 ppm         Chloride (Cl)       ≤ 0.08 ppm       < 0.03 ppm	Appearance		
Residue after Ignition       ≤ 2 ppm       1 ppm         Chloride (Cl)       ≤ 0.08 ppm       < 0.03 ppm	Color (APHA)	≤ 10	
Chloride (Cl)       ≤ 0.08 ppm       < 0.03 ppm	Residue after Ignition	≤ 2 ppm	
Phosphate (PO4)         ≤ 0.10 ppm         < 0.03 ppm	Chloride (CI)		
Sulfate (SO <sub>4</sub> )       ≤ 0.2 ppm       < 0.2 ppm	Phosphate (PO <sub>4</sub> )	, ,	
Trace Impurities – Aluminum (AI)  Arsenic and Antimony (as As)  Soloppb  Coloppb  Trace Impurities – Barium (Ba)  Trace Impurities – Beryllium (Be)  Trace Impurities – Beryllium (Be)  Trace Impurities – Bismuth (Bi)  Coloppb  Trace Impurities – Boron (B)  Trace Impurities – Cadmium (Cd)  Trace Impurities – Cadmium (Cd)  Trace Impurities – Cadmium (Cr)  Trace Impurities – Cobalt (Co)  Trace Impurities – Cobalt (Co)  Trace Impurities – Cobalt (Co)  Trace Impurities – Copper (Cu)  Trace Impurities – Collium (Ga)  Trace Impurities – Cold (Au)  Expendition – Companium (Ge)  Trace Impurities – Cold (Au)  Trace Impurities – Iron (Fe)  Trace Impurities – Lithium (Li)  Trace Impurities – Manganese (Mn)	Sulfate (SO <sub>4</sub> )		• •
Arsenic and Antimony (as As)  S 5.0 ppb  C 2.0 ppb  Trace Impurities - Barium (Ba)  Trace Impurities - Barium (Be)  Trace Impurities - Barium (Be)  Trace Impurities - Barium (Be)  S 10.0 ppb  C 1.0 ppb  Trace Impurities - Bismuth (Bi)  S 20.0 ppb  C 10.0 ppb  Trace Impurities - Cadmium (Cd)  Trace Impurities - Cadmium (Cd)  Trace Impurities - Calcium (Ca)  Trace Impurities - Calcium (Ca)  Trace Impurities - Chromium (Cr)  Trace Impurities - Cobalt (Co)  Trace Impurities - Cobalt (Co)  Trace Impurities - Copper (Cu)  Trace Impurities - Callium (Ga)  Trace Impurities - Gallium (Ga)  Trace Impurities - Gold (Au)  Trace Impurities - Cold (Au)  Trace Impurities - Iron (Fe)  Trace Impurities - Lead (Pb)  Trace Impurities - Manganese (Mn)  Trace Impurities - Manganese (Mn)  Trace Impurities - Manganese (Mn)  Trace Impurities - Manganese (Min)  Trace Impurities - Manganese (Min)  Trace Impurities - Manganese (Min)	Trace Impurities - Aluminum (AI)	≤ 40.0 ppb	• •
Trace Impurities – Barium (Ba)	Arsenic and Antimony (as As)	• •	**
Trace Impurities – Beryllium (Be)  Frace Impurities – Bismuth (Bi)  Frace Impurities – Bismuth (Bi)  Frace Impurities – Boron (B)  Frace Impurities – Cadmium (Cd)  Frace Impurities – Cadmium (Cd)  Frace Impurities – Calcium (Ca)  Frace Impurities – Calcium (Ca)  Frace Impurities – Calcium (Cr)  Frace Impurities – Chromium (Cr)  Frace Impurities – Cobalt (Co)  Frace Impurities – Cobalt (Co)  Frace Impurities – Copper (Cu)  Frace Impurities – Copper (Cu)  Frace Impurities – Gallium (Ga)  Frace Impurities – Gallium (Ga)  Frace Impurities – Gold (Au)  Frace Impurities – Gold (Au)  Frace Impurities – Copper (Ce)  Frace Impurities – Iron (Fe)  Frace Impurities – Lead (Pb)  Frace Impurities – Lead (Pb)  Frace Impurities – Lead (Pb)  Frace Impurities – Lead (Mi)  Frace Impurities – Lead (Mi)  Frace Impurities – Magnesium (Mg)  Frace Impurities – Magnese (Mn)	Trace Impurities - Barium (Ba)		• •
Trace Impurities – Bismuth (Bi)	Trace Impurities - Beryllium (Be)	••	• •
Trace Impurities – Boron (B) ≤ 10.0 ppb < 5.0 ppb  Trace Impurities – Cadmium (Cd) ≤ 50 ppb < 1 ppb  Trace Impurities – Calcium (Ca) ≤ 50.0 ppb	Trace Impurities - Bismuth (Bi)	≤ 20.0 ppb	• •
Trace Impurities - Cadmium (Cd) ≤ 50 ppb < 1 ppb  Trace Impurities - Calcium (Ca) ≤ 50.0 ppb 2.3 ppb  Trace Impurities - Chromium (Cr) ≤ 30.0 ppb < 1.0 ppb  Trace Impurities - Cobalt (Co) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Copper (Cu) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Gallium (Ga) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Germanium (Ge) ≤ 20 ppb < 10 ppb  Trace Impurities - Gold (Au) ≤ 20 ppb < 5 ppb  Heavy Metals (as Pb) ≤ 100 ppb 100 ppb  Trace Impurities - Iron (Fe) ≤ 40.0 ppb < 1.0 ppb  Trace Impurities - Lead (Pb) ≤ 20.0 ppb < 10.0 ppb  Trace Impurities - Lithium (Li) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Magnesium (Mg) ≤ 20 ppb < 1 ppb  Trace Impurities - Magnesium (Mg) ≤ 20 ppb < 1.0 ppb	Trace Impurities - Boron (B)		
Trace Impurities - Calcium (Ca) ≤ 50.0 ppb 2.3 ppb  Trace Impurities - Chromium (Cr) ≤ 30.0 ppb < 1.0 ppb  Trace Impurities - Cobalt (Co) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Copper (Cu) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Gallium (Ga) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Germanium (Ge) ≤ 20 ppb < 10 ppb  Trace Impurities - Gold (Au) ≤ 20 ppb < 5 ppb  Heavy Metals (as Pb) ≤ 100 ppb 100 ppb  Trace Impurities - Iron (Fe) ≤ 40.0 ppb < 1.0 ppb  Trace Impurities - Lead (Pb) ≤ 20.0 ppb < 10.0 ppb  Trace Impurities - Lithium (Li) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Magnesium (Mg) ≤ 20 ppb < 10.0 ppb  Trace Impurities - Manganese (Mn) ≤ 10.0 ppb	Trace Impurities - Cadmium (Cd)		
Trace Impurities - Chromium (Cr) ≤ 30.0 ppb < 1.0 ppb  Trace Impurities - Cobalt (Co) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Copper (Cu) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Gallium (Ga) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Germanium (Ge) ≤ 20 ppb < 10 ppb  Trace Impurities - Gold (Au) ≤ 20 ppb < 5 ppb  Heavy Metals (as Pb) ≤ 100 ppb 100 ppb  Trace Impurities - Iron (Fe) ≤ 40.0 ppb < 1.0 ppb  Trace Impurities - Lead (Pb) ≤ 20.0 ppb < 10.0 ppb  Trace Impurities - Lithium (Li) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Magnesium (Mg) ≤ 20 ppb < 1 ppb  Trace Impurities - Manganese (Mn) ≤ 10.0 ppb < 1.0 ppb	Trace Impurities - Calcium (Ca)	≤ 50.0 ppb	
Trace Impurities – Cobalt (Co) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities – Copper (Cu) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities – Gallium (Ga) ≤ 10.0 ppb < 10 ppb  Trace Impurities – Germanium (Ge) ≤ 20 ppb < 10 ppb  Trace Impurities – Gold (Au) ≤ 20 ppb < 5 ppb  Heavy Metals (as Pb) ≤ 100 ppb 100 ppb  Trace Impurities – Iron (Fe) ≤ 40.0 ppb < 1.0 ppb  Trace Impurities – Lead (Pb) ≤ 20.0 ppb < 10.0 ppb  Trace Impurities – Lithium (Li) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities – Magnesium (Mg) ≤ 20 ppb < 1 ppb  Trace Impurities – Magnesium (Mg) ≤ 20 ppb < 1.0 ppb	Trace Impurities - Chromium (Cr)	≤ 30.0 ppb	
Trace Impurities - Copper (Cu) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Gallium (Ga) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Germanium (Ge) ≤ 20 ppb < 10 ppb  Trace Impurities - Gold (Au) ≤ 20 ppb < 5 ppb  Heavy Metals (as Pb) ≤ 100 ppb 100 ppb  Trace Impurities - Iron (Fe) ≤ 40.0 ppb < 1.0 ppb  Trace Impurities - Lead (Pb) ≤ 20.0 ppb < 10.0 ppb  Trace Impurities - Lithium (Li) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Magnesium (Mg) ≤ 20 ppb < 1 ppb  Trace Impurities - Magnesium (Mg) ≤ 20 ppb < 1 ppb	Trace Impurities - Cobalt (Co)	• •	• •
Trace Impurities - Gallium (Ga)       ≤ 10.0 ppb       < 1.0 ppb	Trace Impurities - Copper (Cu)	••	
Trace Impurities – Germanium (Ge) ≤ 20 ppb < 10 ppb  Trace Impurities – Gold (Au) ≤ 20 ppb < 5 ppb  Heavy Metals (as Pb) ≤ 100 ppb 100 ppb  Trace Impurities – Iron (Fe) ≤ 40.0 ppb < 1.0 ppb  Trace Impurities – Lead (Pb) ≤ 20.0 ppb < 10.0 ppb  Trace Impurities – Lithium (Li) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities – Magnesium (Mg) ≤ 20 ppb < 1 ppb  Trace Impurities – Manganese (Mn) ≤ 10.0 ppb < 1.0 ppb	Trace Impurities – Gallium (Ga)	≤ 10.0 ppb	• •
Trace Impurities – Gold (Au) $\leq 20 \text{ ppb}$ $< 5 \text{ ppb}$ Heavy Metals (as Pb) $\leq 100 \text{ ppb}$ $100 \text{ ppb}$ Trace Impurities – Iron (Fe) $\leq 40.0 \text{ ppb}$ $< 1.0 \text{ ppb}$ Trace Impurities – Lead (Pb) $\leq 20.0 \text{ ppb}$ $< 10.0 \text{ ppb}$ Trace Impurities – Lithium (Li) $\leq 10.0 \text{ ppb}$ $< 1.0 \text{ ppb}$ Trace Impurities – Magnesium (Mg) $\leq 20 \text{ ppb}$ $< 1 \text{ ppb}$ Trace Impurities – Manganese (Mn) $\leq 10.0 \text{ ppb}$ $< 1.0 \text{ ppb}$	Trace Impurities - Germanium (Ge)	≤ 20 ppb	• •
Heavy Metals (as Pb) ≤ 100 ppb 100 ppb  Trace Impurities – Iron (Fe) ≤ 40.0 ppb < 1.0 ppb  Trace Impurities – Lead (Pb) ≤ 20.0 ppb < 10.0 ppb  Trace Impurities – Lithium (Li) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities – Magnesium (Mg) ≤ 20 ppb < 1 ppb  Trace Impurities – Manganese (Mn) ≤ 10.0 ppb < 1.0 ppb	Trace Impurities - Gold (Au)	* *	
Trace Impurities – Iron (Fe) $\leq 40.0 \text{ ppb}$ $< 1.0 \text{ ppb}$ Trace Impurities – Lead (Pb) $\leq 20.0 \text{ ppb}$ $< 10.0 \text{ ppb}$ Trace Impurities – Lithium (Li) $\leq 10.0 \text{ ppb}$ $< 1.0 \text{ ppb}$ Trace Impurities – Magnesium (Mg) $\leq 20 \text{ ppb}$ $< 1 \text{ ppb}$ Trace Impurities – Manganese (Mn) $\leq 10.0 \text{ ppb}$ $< 1.0 \text{ ppb}$	Heavy Metals (as Pb)		
Trace Impurities – Lead (Pb)       ≤ 20.0 ppb       < 10.0 ppb	Trace Impurities - Iron (Fe)		
Trace Impurities – Lithium (Li) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities – Magnesium (Mg) ≤ 20 ppb < 1 ppb  Trace Impurities – Manganese (Mn) ≤ 10.0 ppb < 1.0 ppb	Trace Impurities - Lead (Pb)	≤ 20.0 ppb	• • • • • • • • • • • • • • • • • • • •
Trace Impurities – Magnesium (Mg) ≤ 20 ppb < 1 ppb  Trace Impurities – Manganese (Mn) ≤ 10.0 ppb < 1.0 ppb	Trace Impurities – Lithium (Li)		
Trace Impurities - Manganese (Mn) ≤ 10.0 ppb < 1.0 ppb	Trace Impurities – Magnesium (Mg)		
Trace Impurities   Nichol (NI)	Trace Impurities – Manganese (Mn)		
	Trace Impurities - Nickel (Ni)	≤ 20.0 ppb	< 5.0 ppb

>>> Continued on page 2 >>>





Material No.: 9606-03 Batch No.: 24D1062002

Test	Specification	Result
Trace Impurities - Niobium (Nb)	≤ 50.0 ppb	< 1.0 ppb
Trace Impurities – Potassium (K)	≤ 50 ppb	16 ppb
Trace Impurities - Silicon (Si)	≤ 50 ppb	< 10 ppb
Trace Impurities - Silver (Ag)	≤ 20.0 ppb	< 1.0 ppb
Trace Impurities – Sodium (Na)	≤ 150.0 ppb	< 5.0 ppb
Trace Impurities – Strontium (Sr)	≤ 30.0 ppb	< 1.0 ppb
Trace Impurities – Tantalum (Ta)	≤ 10.0 ppb	< 5.0 ppb
Trace Impurities - Thallium (TI)	≤ 10.0 ppb	< 5.0 ppb
Trace Impurities - Tin (Sn)	≤ 20.0 ppb	< 10.0 ppb
Trace Impurities - Titanium (Ti)	≤ 10.0 ppb	< 1.0 ppb
Trace Impurities - Vanadium (V)	≤ 10.0 ppb	< 1.0 ppb
Trace Impurities – Zinc (Zn)	≤ 20.0 ppb	< 1.0 ppb
Trace Impurities - Zirconium (Zr)	≤ 10.0 ppb	< 1.0 ppb
Particle Count – 0.5 µm and greater	≤ 60 par/ml	10 par/ml
Particle Count - 1.0 µm and greater	≤ 10 par/ml	3 par/ml

Nitric Acid 69% **CMOS** 





Material No.: 9606-03 Batch No.: 24D1062002

Test Specification Result

For Microelectronic Use

Country of Origin: USA Packaging Site: Phillipsburg Mfg Ctr & DC

Director Quality Operations, Bioscience Production