



# **CASE NARRATIVE**

**Weston Solutions** 

Project Name: Ft Meade Tipton Airfield Parcel RI - PO 0111169

Project # N/A

Chemtech Project # P5117 Test Name: TCLP BNA

## A. Number of Samples and Date of Receipt:

2 Solid samples were received on 12/05/2024.

#### **B.** Parameters

According to the Chain of Custody document, the following analyses were requested: Anions Group1, Cyanide, Ignitability, Mercury, Metals ICP-TAL, METALS-TAL, PCB, pH, Sulfide, TCLP BNA, TCLP Extraction, TCLP Herbicide, TCLP ICP Metals, TCLP Mercury, TCLP METALS, TCLP Pesticide, TCLP VOA, TCLP ZHE Extraction, TOC and TS. This data package contains results for TCLP BNA.

### C. Analytical Techniques:

The samples were analyzed on instrument BNA\_F using GC Column DB-UI 8270D which is 20 meters, 0.18 mm ID, 0.36 um dfThe analysis of TCLP BNA was based on method 8270E and extraction was done based on method 3510 and TCLP extraction method was 1311.

## D. QA/ QC Samples:

The Holding Times were met for all analysis.

The Surrogate recoveries met the acceptable criteria.

The Internal Standards Areas met the acceptable requirements.

The Retention Times were acceptable for all samples.

The MS recoveries met the requirements for all compounds.

The MSD recoveries met the acceptable requirements.

The RPD for {P5095-04MSD} with File ID: BF140792.D met criteria except for Nitrobenzene[22%] due to difference in results of MS and MSD.

The Blank Spike met requirements for all samples.

The Blank analysis did not indicate the presence of lab contamination.

The Initial Calibration met the requirements.

The Continuous Calibration met the requirements.

The Tuning criteria met requirements.

### E. Additional Comments:

The Form 6 is not included in the data package because the Initial Calibration was performed using 8 points.



The not QT review data is reported in the Miscellaneous.

Please use %D calculated based on Avg RF and CCRF for all compounds using Average Response Factor when the %RSD value for a compound is <15% for the Initial Calibration curve and use %D calculated based on Amount added and Calculated amount for all compounds using Linear Regression when the %RSD value for a compound is > 15% for the Initial Calibration curve for SW-846 analysis.

# F. Concentration of Water Sample:

Concentration ug/L =  $(\underline{Ax})$  (Is) (Vt) (DF) (GPC) (Ais) (RRF) (Vo) (Vi)

#### Where,

Ax = Area of the characteristic ion for the compound to be measured.

Ais = Area of the characteristic ion for the internal standard.

Is = Amount of internal standard injected in ng.

Vo = Volume of water extracted in mL.

Vi = Volume of extract injected in uL.

Vt = Volume of the concentrated extract in uL

RRF = Mean Relative Response Factor determined from the initial calibration standard.

 $GPC = \underline{Vin} = GPC \text{ factor (If no GPC is performed, GPC=1)}$ Vout

### **G.** Manual Integration Comments:

Please refer to the Manual integration Report included with the Run Logs for information on the manual integrations performed.

I certify that the data package is in compliance with the terms and conditions of the contract, both technically and for completeness, for other than the conditions detailed above. The laboratory manager or his designee, as verified by the following signature has authorized release of the data contained in this hard copy data package.

Signature		
oignature <u>.</u>	 	 