

# Prep Standard - Chemical Standard Summary

Order ID : Q1651

Test : Metals Group3

Prepbatch ID : PB167340,

Sequence ID/Qc Batch ID: LB135215,

Standard ID : MP84041,MP84720,

Chemical ID : M6003,M6012,M6126,M6151,W3112,



# Metals STANDARD PREPARATION LOG

Recipe ID 169	NAME 1:1HNO3	<u>NO.</u> MP84041	Prep Date 01/14/2025		<u>Prepared</u> <u>By</u> Eman Mughal	<u>ScaleID</u> None	<u>PipetteID</u> None	Sarabjit Jaswal
FROM	1250.00000ml of M6126 + 1250.000	00ml of W31	12 = Final Q	uantity: 2500.00	00 ml			
Recipe				Expiration	<u>Prepared</u>			Supervised By

<u>Recipe</u>				Expiration	<u>Prepared</u>			<u>Supervised By</u>
ID	NAME	<u>NO.</u>	Prep Date	<u>Date</u>	<u>By</u>	<u>ScaleID</u>	<u>PipetteID</u>	Sarabjit Jaswal
170	1:1HCL	<u>MP84720</u>	03/03/2025	04/04/2025	Sagar Kanani	None	METALS_PIP	
							ETTE_1 (ICP	03/03/2025
FROM	1000.00000ml of M6151 + 1000.000	00ml of W31	12 = Final Qu	uantity: 2000.0	00 ml		A)	



Т

Iwona

Iwona

# CHEMICAL RECEIPT LOG BOOK

Т

т

Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
Inorganic Ventures	WW-LFS-1 / Laboratory Fortified Stock Solution 1, 125 ml	T2-MEB723367	08/26/2025	02/26/2025 / Eman	05/14/2024 / Jaswal	M6003
Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
Inorganic Ventures	WW-LFS-2 / Laboratory Fortified Stock Solution 2, 125 ml	U2-MEB731108	09/17/2025	03/17/2025 / Eman	05/14/2024 / Jaswal	M6012
Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
Seidler Chemical	BA-9598-34 / Nitric Acid, Instra-Analyzed (cs/4x2.5L)	24D1062002	06/03/2025	12/03/2024 / Janvi	11/12/2024 / Janvi	M6126
Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
Seidler Chemical	BA-9530-33 / Hydrochloric Acid, Instra-Analyzed (cs/6x2.5L)	22G2862015	08/18/2025	02/18/2025 / Sagar	01/15/2025 / Sagar	M6151
Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
Seidler Chemical	DIW / DI Water	Daily Lab-Certified	07/03/2029	07/03/2024 /	07/03/2024 /	W3112

# Certificate of Analysis

Refine your results. Redefine your industry. RD:05/14/2024

**INORGANIC**" V E N T U R E S

300 Technology Drive Christiansburg, VA 24073 USA inorganicventures.com P: 800-669-6799/540-585-3030 F: 540-585-3012 info@inorganicventures.com

# 1.0 ACCREDITATION / REGISTRATION

**INORGANIC VENTURES** is accredited to ISO 17034, "General Requirements for the Competence of Reference Material Producers" and ISO/IEC 17025, "General Requirements for the Competence of Testing and Calibration Laboratories". Inorganic Ventures is also an ISO 9001 registered manufacturer (QSR Certificate Number QSR-1034).



# 2.0 PRODUCT DESCRIPTION

Product Code:	Multi Analyte Custom Grade Solution
Catalog Number:	WW-LFS-1
Lot Number:	T2-MEB723367
Matrix:	5% (v/v) HNO3

	Value / Analyte(s):	1 000 µg/mL ea: Potassium,		
		600 μg/mL ea: Phosphorus,		
		300 µg/mL ea: Sodium,	Iron,	
		200 µg/mŁ ea: Magnesium, Cerium, Thallium,	Aluminum, Selenium,	
		100 µg/mL ea: Lead,	Calcium,	
		80 μg/mL ea: Arsenic,		
		70 μg/mL ea: Mercury,		
		50 μg/mL ea: Nickel,		
		40 µg/mL ea: Chromium,		
		30 µg/mL ea: Copper, Vanadium,	Boron,	
		20 μg/mL ea: Zinc, Barium, Cadmium, Manganese,	Strontium, Beryllium, Cobalt, Lithium,	
3.0	CERTIFIED VALUES	7.5 µg/mL ea: Silver AND UNCERTAINTI	ES	

ANALYTE Aluminum, Al	CERTIFIED VALUE 200.0 ± 0.7 µg/mL	ANALYTE Arsenic, As	CERTIFIED VALUE 80.0 ± 0.7 µg/mL
Barium, Ba	20.00 ± 0.09 µg/mL	Beryllium, Be	20.00 ± 0.13 µg/mL
Boron, B	30.00 ± 0.18 µg/mL	Cadmium, Cd	20.00 ± 0.09 µg/mL
Calcium, Ca	100.0 ± 0.4 μg/mL	Cerium, Ce	200.0 ± 0.8 μg/mL
Chromium, Cr	40.00 ± 0.30 μg/mL	Cobalt, Co	20.00 ± 0.10 µg/mL
Copper, Cu	30.00 ± 0.13 µg/mL	Iron, Fe	300.0 ± 1.3 μg/mL
Lead, Pb	100.0 ± 0.4 µg/mL	Lithium, Li	20.00 ± 0.08 µg/mL
Magneslum, Mg	200.0 ± 0.8 µg/mL	Manganese, Mn	20.00 ± 0.08 µg/mL
Mercury, Hg	70.0 ± 0.3 µg/mL	Nickel, Ni	50.00 ± 0.22 μg/mL
Phosphorus, P	600.0 ± 2.7 μg/mL	Potassium, K	1 000 ± 4 µg/mL
Selenium, Se	200.0 ± 1.3 µg/mL	Silver, Ag	7.50 ± 0.03 μg/mL
Sodium, Na	300.0 ± 1.4 μg/mL	Strontium, Sr	20.01 ± 0.08 µg/mL
Thailium, Ti	200.0 ± 1.4 µg/mL	Vanadium, V	30.00 ± 0.13 μg/mL
Zinc, Zn	20.00 ± 0.09 µg/mL		

Density:

1.034 g/mL (measured at 20  $\pm$  4 °C)

Assay Information:

ANALYTE Ag	METHOD ICP Assay	NIST SRM# 3151	SRM LOT# 160729
Ag	Volhard	999c	999c
Ag	Calculated		See Sec. 4.2
A	ICP Assay	3101a	140903
Al	EDTA	928	928
As	ICP Assay	3103a	100818
В	ICP Assay	3107	190605
Ba	ICP Assay	3104a	140909
Ва	Gravimetric		See Sec. 4.2
Be	ICP Assay	3105a	090514
Са	ICP Assay	3109a	130213
Ca	EDTA	928	928
Cd	ICP Assay	3108	130116
Cd	EDTA	928	928
Се	ICP Assay	3110	090504
Ce	EDTA	928	928
Co	ICP Assay	3113	190630
Со	EDTA	928	928
Cr	ICP Assay	3112a	170630
Cu	ICP Assay	3114	121207
Cu	EDTA	928	928
Fe	ICP Assay	3126a	140812
Fe	EDTA	928	928
Hg	ICP Assay	3133	160921
Hg	EDTA	928	928
к	ICP Assay	3141a	140813
к	Gravimetric		See Sec. 4.2
Li	ICP Assay	3129a	100714
Li	Gravimetric		See Sec. 4.2
Mg	ICP Assay	3131a	140110
Mg	EDTA	928	928
Mn	ICP Assay	3132	050429
Mn	EDTA	928	928
Na	ICP Assay	Traceable to 3152A	S2-NA700842
Na	Gravimetric	0400	See Sec. 4.2
Ni Ni	ICP Assay	3136	120619
P	EDTA	928 3139a	928
P	ICP Assay Acidimetric		060717
F Pb	ICP Assay	84L 3128	84L
Pb	EDTA	928	101026 928
Se	ICP Assay	3149	920 100901
Sr	EDTA	928	928
Sr	ICP Assay	Traceable to 3153a	920 K2-SR650985
TI	ICP Assay	3158	151215
V	IC Assay	3165	160906
v	EDTA	928	928
Zn	ICP Assay	3168a	120629
Zn	EDTA	928	928
	Eco 4		

Page 4 of 6

The following equations are used in the calculation of the certified value and the uncertainty. Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of k = 2.

Characterization of CRM/RM by Two or More Methods	Characterization of CRM/RM by One Method
Certified Value, X <sub>CRMRM</sub> , where two or more methods of characterization are used is the weighted mean of the results:	Certified Value, X <sub>CRM/RM</sub> , where one method of characterization is used is the mean of individual results:
$\begin{split} & X_{CRM/RM} \equiv \Sigma(w_i) \; (X_i) \\ & X_i = \text{mean of Assay Method i with standard uncertainty } u_{char, i} \\ & w_i = \text{the weighting factors for each method calculated using the inverse square of the variance:} \\ & w_i = (1/u_{char, i})^2 / (\Sigma(1/(u_{char, i})^2)) \end{split}$	$X_{CRM/RM} = (X_a) (u_{char a})$ $X_a = mean of Assay Method A withu_{char a} = the standard uncertainty of characterization Method A$
CRM/RM Expanded Uncertainty (±) = U <sub>CRM/RM</sub> = k $(u^2_{char} + u^2_{bb} + u^2_{lts} + u^2_{ts})^{V_2}$ k = coverage factor = 2 $u_{char} = [\Sigma[(w_i)^2 (u_{char}_i)^2])^{V_2}$ where $u_{char}$ is the errors from each characterization method $u_{bb}$ = bottle to bottle homogeneity standard uncertainty $u_{lts} = long term stability standard uncertainty (storage) u_{te} = transport stability standard uncertainty$	CRM/RM Expanded Uncertainty (±) = U <sub>CRM/RM</sub> = k ( $u^2_{chara} + u^2_{bb} + u^2_{tts} + u^2_{ts}$ ) <sup>1/k</sup> k = coverage factor = 2 u <sub>chara</sub> = the errors from characterization u <sub>bb</sub> = bottle to bottle homogeneity standard uncertainty u <sub>Its</sub> = long term stability standard uncertainty (storage) u <sub>uts</sub> = transport stability standard uncertainty

- This product is traceable to NIST via an unbroken chain of comparisons. The uncertainties for each certified value are reported, taking into account the SRM/RM uncertainty error and the measurement, weighing and volume dilution errors. In rare cases where no NIST SRM/RM are available, the term 'in-house std.' is specified.

# 4.1 Thermometer Calibration

- All thermometers are NIST traceable through thermometers that are calibrated by an accredited calibration laboratory.

### 4.2 Balance Calibration

- All analytical balances are calibrated by an accredited calibration laboratory and procedure. The weights used for testing are annually compared to master weights and are traceable to NIST.

# 4.3 Glassware Calibration

- An in-house procedure is used to calibrate all Class A glassware used in the manufacturing and quality control of CRM/RMs.

# 5.0 TRACE METALLIC IMPURITIES (TMI ) DETERMINED BY ICP-MS AND ICP-OES (µg/mL)

### 6.0 INTENDED USE

4.0

- For the calibration of analytical instruments and validation of analytical methods as appropriate.

# 7.0 INSTRUCTIONS FOR THE CORRECT USE OF THIS REFERENCE MATERIAL

# 7.1 Storage and Handling Recommendations

- Store between approximately 4° - 30° C while in sealed TCT bag.

- While stored in the sealed TCT bag, transpiration of this CRM/RM is negligible. After opening the sealed TCT bag transpiration of the CRM/RM will occur, resulting in a gradual increase in the analyte concentration(s). It is the responsibility of the user to account for this effect. When the bottle is weighed both before and after being placed in storage, the mass difference observed will be a measure of transpiration mass loss.

- After opening the sealed TCT bag, keep cap tightly sealed when not in use and store between  $4^{\circ}$  -  $24^{\circ}$  C to minimize the effects of transpiration. Use at  $20^{\circ} \pm 4^{\circ}$  C to minimize volumetric dilution error when using the reported density. Do not pipette from the container. Do not return removed aliquots to container.

- For more information, visit www.inorganicventures.com/TCT

Low Silver Note: This solution contains "LOW" levels of Silver. Please store this entire bottle inside a sealed glass jar.

#### 8.0 **HAZARDOUS INFORMATION**

Please refer to the Safety Data Sheet for information regarding this CRM/RM.

#### 9.0 HOMOGENEITY

- This solution was mixed according to an in-house procedure and is guaranteed to be homogeneous. Homogeneity data indicate that the end user should take a minimum sample size of 0.2 mL to assure homogeneity.

#### 10.0 **QUALITY STANDARD DOCUMENTATION**

# 10.1 ISO 9001 Quality Management System Registration

- QSR Certificate Number QSR-1034

10.2 ISO/IEC 17025 "General Requirements for the Competence of Testing and Calibration Laboratories"

- Chemical Testing - Accredited / A2LA Certificate Number 883.01

# 10.3 ISO 17034 "General Requirements for the Competence of Reference Material Producers"

- Reference Material Producer - Accredited / A2LA Certificate Number 883.02

Inorganic Ventures, 300 Technology Drive, Christiansburg, Va. 24073, USA; Telephone: 800.669.6799; 540.585.3030, Fax: 540.585.3012; inorganicventures.com; info@inorganicventures.com

#### 11.0 CERTIFICATION, LOT EXPIRATION AND PERIOD OF VALIDITY

# **11.1 Certification Issue Date**

August 30, 2022

- The certification is valid within the measurement uncertainty specified provided the CRM/RM is stored and handled in accordance with instructions given in Sec 7.1. This certification is nullified if instructions in Sec 7.1 are not followed or if the CRM/RM is damaged, contaminated, or otherwise modified.

# 11.2 Lot Expiration Date

# - August 30, 2026

- The date after which this CRM/RM should not be used.

- The lot expiration date reflects the period of time that the stability of a CRM/RM can be supported by long term stability studies conducted on properly stored and handled CRM/RMs. Lot expiration is limited primarily by transpiration (loss of water from the solution) and infrequently by chemical stability.

# **11.3 Period of Validity**

- Sealed TCT Bag Open Date:

- This CRM/RM should not be used longer than one year (or six months in the case of a 30 mL bottle) from the date of opening the aluminized bag or after the date given in Sec. 11.2, whichever comes first. This is contingent upon the CRM/RM being stored and handled in accordance with the instructions given in Sec. 7.1.

#### 12.0 NAMES AND SIGNATURES OF CERTIFYING OFFICERS

# **Certificate Approved By:**

Thomas Kozikowski Manager, Quality Control

SD9781.

Certifying Officer:

**Paul Gaines** Chairman / Senior Technical Director

Page 6 of 6

# **Certificate of Analysis**

Refine your results. Redefine your industry. RD:05/14/2024

300 Technology Drive Christiansburg, VA 24073 USA inorganicventures.com P: 800-669-6799/540-585-3030 F: 540-585-3012 info@inorganicventures.com

# 1.0 ACCREDITATION / REGISTRATION

ÍNORGANÍ

VENTURES

**INORGANIC VENTURES** is accredited to ISO 17034, "General Requirements for the Competence of Reference Material Producers" and ISO/IEC 17025, "General Requirements for the Competence of Testing and Calibration Laboratories". Inorganic Ventures is also an ISO 9001 registered manufacturer (QSR Certificate Number QSR-1034).



# 2.0 PRODUCT DESCRIPTION

Product Code:	Multi Analyte Custom Grade Solution
Catalog Number:	WW-LFS-2
Lot Number:	U2-MEB731108
Matrix:	5% (v/v) HNO3 tr. HF
Value / Analyte(s):	200 μg/mL ea: Silica,
	80 μg/mL ea: Antimony,
	70 μg/mL ea: Tin,
	40 μg/mL ea: Molybdenum,
	20 μg/mL ea:
	Titanium

# 3.0 CERTIFIED VALUES AND UNCERTAINTIES

ANALYTE Antimony, Sb	CERTIFIED VALUE 80.1 ± 0.6 µg/mL	ANALYTE Molybdenum, Mo	CERTIFIED VALUE 40.03 ± 0.18 µg/mL
Silica, SIO2	200.2 ± 1.3 μg/mL	Tin, Sn	70.0 ± 0.4 µg/mL
Titanium, Ti	20.01 ± 0.13 μg/mL		

Density:

1.025 g/mL (measured at 20 ± 4 °C)

### **Assay Information:**

ANALYTE Mo	METHOD ICP Assay	NIST SRM# 3134	SRM LOT# 130418
Мо	Calculated		See Sec. 4.2
Sb	ICP Assay	3102a	140911
SiO2	ICP Assay	3150	130912
Sn	ICP Assay	3161a	140917
π	ICP Assay	3162a	130925
ті	Calculated		See Sec. 4.2

The following equations are used in the calculation of the certified value and the uncertainty. Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of k = 2.

# Characterization of CRM/RM by Two or More Methods

Certified Value, X<sub>CRWRM</sub>, where two or more methods of characterization are used is the weighted mean of the results:

 $X_{CRM/RM} = \Sigma(w_i) (X_i)$ 

 $X_i$  = mean of Assay Method i with standard uncertainty u<sub>char</sub> i w<sub>i</sub> = the weighting factors for each method calculated using the inverse square of the variance:

 $w_i = (1/u_{char_i})^2 / (\Sigma(1/(u_{char_i})^2))$ 

CRM/RM Expanded Uncertainty (±) =  $U_{CRM/RM} \simeq k \left\{ u_{char}^2 + u_{bb}^2 + u_{ts}^2 + u_{ts}^2 \right\}^{\frac{1}{2}}$ 

k = coverage factor = 2

 $\begin{array}{l} u_{char} = [\overline{\Sigma}((w_{i})^{2} \, (u_{char})^{2})]^{2} \ \ \, \mbox{ where } u_{char} \ \, _{i} \mbox{ are the errors from each characterization method} \\ u_{bb} = bottle \ \, \mbox{ bottle homogeneity standard uncertainty} \\ u_{hs} = long \ \, \mbox{ term stability standard uncertainty (storage)} \end{array}$ 

uts = transport stability standard uncertainty

# 4.0 TRACEABILITY TO NIST

Characterization of CRM/RM by One Method Certified Value, X<sub>CRM/RM</sub>, where one method of characterization is used is the mean of individual results:

$$\begin{split} X_{CRM/RM} = (X_{a}) (u_{oher \ a}) \\ X_{a} = mean \ of Assay Method A with \\ u_{oher \ a} = the standard uncertainty of characterization Method A \end{split}$$

CRM/RM Expanded Uncertainty (±) =  $U_{CRM/RM} = k (u_{char a}^2 + u_{bb}^2 + u_{its}^2 + u_{ts}^2)^{1/2}$ 

 $\label{eq:coverage factor = 2} \\ u_{char} a = the errors from characterization \\ u_{bb} = bottle to bottle homogeneity standard uncertainty$  $u_{its} = long term stability standard uncertainty (storage)$  $u_{its} = transport stability standard uncertainty$ 

- This product is traceable to NIST via an unbroken chain of comparisons. The uncertainties for each certified value are reported, taking into account the SRM/RM uncertainty error and the measurement, weighing and volume dilution errors. In rare cases where no NIST SRM/RM are available, the term 'in-house std.' is specified.

# 4.1 Thermometer Calibration

- All thermometers are NIST traceable through thermometers that are calibrated by an accredited calibration laboratory.

# 4.2 Balance Calibration

- All analytical balances are calibrated by an accredited calibration laboratory and procedure. The weights used for testing are annually compared to master weights and are traceable to NIST.

# 4.3 Glassware Calibration

- An in-house procedure is used to calibrate all Class A glassware used in the manufacturing and quality control of CRM/RMs.

# 5.0 TRACE METALLIC IMPURITIES (TMI ) DETERMINED BY ICP-MS AND ICP-OES (µg/mL)

N/A

# 6.0 INTENDED USE

**6.1** This standard is intended for the calibration of analytical instruments and validation of analytical methods as appropriate. This CRM may be used in connection with EPA Methods 6010, 6020 (all versions), Standard Methods 3120 B and USP <232> / ICH Q3D.

6.2 For products attaining traceability through Inorganic Ventures' Primary Certified Reference Materials (PCRM™) see the Limited License to Use PCRM™ in the Inorganic Ventures <u>Terms and Conditions of Sale</u>. <u>https://www.inorganicventures.com/terms-and-conditions-sale</u>. The Terms and Conditions contain information on the use of materials traceable to PCRM™ certified reference materials. This Limited License agreement is especially pertinent for laboratories accredited under ISO:17034.

# 7.0 INSTRUCTIONS FOR THE CORRECT USE OF THIS REFERENCE MATERIAL

# 7.1 Storage and Handling Recommendations

- Store between approximately 4° - 30° C while in sealed TCT bag.

- While stored in the sealed TCT bag, transpiration of this CRM/RM is negligible. After opening the sealed TCT bag transpiration of the CRM/RM will occur, resulting in a gradual increase in the analyte concentration(s). It is the responsibility of the user to account for this effect. When the bottle is weighed both before and after being placed in storage, the mass difference observed will be a measure of transpiration mass loss.

- After opening the sealed TCT bag, keep cap tightly sealed when not in use and store between  $4^{\circ}$  -  $24^{\circ}$  C to minimize the effects of transpiration. Use at  $20^{\circ} \pm 4^{\circ}$  C to minimize volumetric dilution error when using the reported density. Do not pipette from the container. Do not return removed aliquots to container.

- For more information, visit www.inorganicventures.com/TCT HF Note: This standard should not be prepared or stored in glass.

# 8.0 HAZARDOUS INFORMATION

- Please refer to the Safety Data Sheet for information regarding this CRM/RM.

# 9.0 HOMOGENEITY

- This solution was mixed according to an in-house procedure and is guaranteed to be homogeneous. Homogeneity data indicate that the end user should take a minimum sample size of 0.2 mL to assure homogeneity.

# 10.0 QUALITY STANDARD DOCUMENTATION

# 10.1 ISO 9001 Quality Management System Registration

- QSR Certificate Number QSR-1034

# 10.2 ISO/IEC 17025 "General Requirements for the Competence of Testing and Calibration Laboratories"

- Chemical Testing - Accredited / A2LA Certificate Number 883.01

# 10.3 ISO 17034 "General Requirements for the Competence of Reference Material Producers"

- Reference Material Producer - Accredited / A2LA Certificate Number 883.02

Inorganic Ventures, 300 Technology Drive, Christiansburg, Va. 24073, USA; Telephone: 800.669.6799; 540.585.3030, Fax: 540.585.3012; Inorganicventures.com; Info@inorganicventures.com

# 11.0 CERTIFICATION, LOT EXPIRATION AND PERIOD OF VALIDITY

### **11.1 Certification Issue Date**

March 17, 2023

- The certification is valid within the measurement uncertainty specified provided the CRM/RM is stored and handled in accordance with instructions given in Sec 7.1. This certification is nullified if instructions in Sec 7.1 are not followed or if the CRM/RM is damaged, contaminated, or otherwise modified.

# 11.2 Lot Expiration Date

## - March 17, 2028

- The date after which this CRM/RM should not be used.

- The lot expiration date reflects the period of time that the stability of a CRM/RM can be supported by long term stability studies conducted on properly stored and handled CRM/RMs. Lot expiration is limited primarily by transpiration (loss of water from the solution) and infrequently by chemical stability.

- Sealed TCT Bag Open Date:

- This CRM/RM should not be used longer than one year (or six months in the case of a 30 mL bottle) from the date of opening the aluminized bag or after the date given in Sec. 11.2, whichever comes first. This is contingent upon the CRM/RM being stored and handled in accordance with the instructions given in Sec. 7.1.

#### NAMES AND SIGNATURES OF CERTIFYING OFFICERS 12.0

**Certificate Approved By:** 

Thomas Kozikowski Manager, Quality Control

3D978 .........

**Certifying Officer:** 

**Paul Gaines** Chairman / Senior Technical Director





R-> 11/12/24 TH6126

Material No.: 9606-03 Batch No.: 24D1062002 Manufactured Date: 2024-03-26 Retest Date: 2029-03-25 **Revision No.: 0** 

# Certificate of Analysis

Test	Specification	Result
Assay (HNO₃)	69.0 – 70.0 %	69.7 %
Appearance	Passes Test	Passes Test
Color (APHA)	≤ 10	5
Residue after Ignition	≤ 2 ppm	1 ppm
Chloride (CI)	≤ 0.08 ppm	< 0.03 ppm
Phosphate (PO4)	≤ 0.10 ppm	< 0.03 ppm
Sulfate (SO4)	≤ 0.2 ppm	< 0.2 ppm
Trace Impurities – Aluminum (Al)	≤ 40.0 ppb	< 1.0 ppb
Arsenic and Antimony (as As)	≤ 5.0 ppb	< 2.0 ppb
Trace Impurities – Barium (Ba)	≤ 10.0 ppb	< 1.0 ppb
Trace Impurities - Beryllium (Be)	≤ 10.0 ppb	< 1.0 ppb
Trace Impurities – Bismuth (Bi)	≤ 20.0 ppb	< 10.0 ppb
Trace Impurities - Boron (B)	≤ 10.0 ppb	< 5.0 ppb
Trace Impurities – Cadmium (Cd)	≤ 50 ppb	< 1 ppb
Trace Impurities – Calcium (Ca)	≤ 50.0 ppb	2.3 ppb
Trace Impurities - Chromium (Cr)	≤ 30.0 ppb	< 1.0 ppb
Trace Impurities – Cobalt (Co)	≤ 10.0 ppb	< 1.0 ppb
Trace Impurities – Copper (Cu)	≤ 10.0 ppb	< 1.0 ppb
Trace Impurities – Gallium (Ga)	≤ 10.0 ppb	< 1.0 ppb
Trace Impurities – Germanium (Ge)	≤ 20 ppb	< 10 ppb
Trace Impurities – Gold (Au)	≤ 20 ppb	< 5 ppb
Heavy Metals (as Pb)	≤ 100 ppb	100 ppb
Trace Impurities – Iron (Fe)	≤ 40.0 ppb	< 1.0 ppb
Trace Impurities - Lead (Pb)	≤ 20.0 ppb	< 10.0 ppb
Trace Impurities – Lithium (Li)	≤ 10.0 ppb	< 1.0 ppb
Trace Impurities – Magnesium (Mg)	≤ 20 ppb	< 1 ppb
Trace Impurities – Manganese (Mn)	≤ 10.0 ppb	< 1.0 ppb
Trace Impurities – Nickel (Ni)	≤ 20.0 ppb	< 5.0 ppb

>>> Continued on page 2 >>>

Nitric Acid 69% CMOS





# Material No.: 9606-03 Batch No.: 24D1062002

Test	Specification	Result	

For Microelectronic Use

Country of Origin: USA Packaging Site: Phillipsburg Mfg Ctr & DC



Hydrochloric Acid, 36.5–38.0% BAKER INSTRA-ANALYZED® Reagent For Trace Metal Analysis





M6151

R-> 1/15/25

Material No.: 9530-33 Batch No.: 22G2862015 Manufactured Date: 2022-06-15 Retest Date: 2027-06-14 Revision No.: 0

# Certificate of Analysis

Test	Specification	Decult
ACS - Assay (as HCI) (by acid-base titrn)		Result
ACS - Color (APHA)	36.5 - 38.0 %	37.9 %
ACS - Residue after Ignition	≤ 10	5
ACS - Specific Gravity at 60°/60°F	≤ 3 ppm	< 1 ppm
ACS – Bromide (Br)	1.185 - 1.192	1.191
ACS - Extractable Organic Substances	≤ 0.005 %	< 0.005 %
ACS – Free Chlorine (as Cl <sub>2</sub> )	≤ 5 ppm	< 1 ppm
Phosphate (PO4)	≤ 0.5 ppm	< 0.5 ppm
Sulfate (SO4)	≤ 0.05 ppm	< 0.03 ppm
Sulfite (SO <sub>3</sub> )	≤ 0.5 ppm	< 0.3 ppm
Ammonium (NH4)	≤ 0.8 ppm	0.3 ppm
Trace Impurities - Arsenic (As)	≤ 3 ppm	< 1 ppm
Trace Impurities – Aluminum (AI)	≤ 0.010 ppm	< 0.003 ppm
Arsenic and Antimony (as As)	≤ 10.0 ppb	1.3 ppb
Trace Impurities – Barium (Ba)	≤ 5.0 ppb	< 3.0 ppb
Trace Impurities – Beryllium (Be)	≤ 1.0 ppb	0.2 ppb
Trace Impurities – Bismuth (Bi)	≤ 1.0 ppb	< 0.2 ppb
Trace Impurities – Bismuth (BI) Trace Impurities – Boron (B)	≤ 10.0 ppb	< 1.0 ppb
	≤ 20.0 ppb	< 5.0 ppb
Trace Impurities - Cadmium (Cd)	≤ 1.0 ppb	< 0.3 ppb
Trace Impurities - Calcium (Ca)	≤ 50.0 ppb	163.0 ppb
Trace Impurities – Chromium (Cr)	≤ 1.0 ppb	0.7 ppb
Trace Impurities - Cobalt (Co)	≤ 1.0 ppb	< 0.3 ppb
Trace Impurities - Copper (Cu)	≤ 1.0 ppb	< 0.1 ppb
Trace Impurities - Gallium (Ga)	≤ 1.0 ppb	< 0.2 ppb
Trace Impurities - Germanium (Ge)	≤ 3.0 ppb	< 2.0 ppb
Trace Impurities – Gold (Au)	≤ 4.0 ppb	0.6 ppb
Heavy Metals (as Pb)	≤ 100 ppb	< 50 ppb
Trace Impurities – Iron (Fe)	≤ 15 ppb	6 ppb
		~ hhn

>>> Continued on page 2 >>>

Hydrochloric Acid, 36.5-38.0% BAKER INSTRA-ANALYZED® Reagent For Trace Metal Analysis





# Material No.: 9530-33 Batch No.: 22G2862015

Test	Specification	Result
Trace Impurities - Lead (Pb)	≤ 1.0 ppb	< 0.5 ppb
Trace Impurities – Lithium (Li)	≤ 1.0 ppb	< 0.2 ppb
Trace Impurities – Magnesium (Mg)	≤ 10.0 ppb	2.9 ppb
Trace Impurities – Manganese (Mn)	≤ 1.0 ppb	< 0.4 ppb
Trace Impurities – Mercury (Hg)	≤ 0.5 ppb	0.1 ppb
Trace Impurities – Molybdenum (Mo)	≤ 10.0 ppb	< 3.0 ppb
Trace Impurities – Nickel (Ni)	≤ 4.0 ppb	< 0.3 ppb
Trace Impurities – Niobium (Nb)	≤ 1.0 ppb	0.8 ppb
Trace Impurities – Potassium (K)	≤ 9.0 ppb	< 2.0 ppb
Trace Impurities – Selenium (Se), For Information Only		< 1.0 ppb
Trace Impurities - Silicon (Si)	≤ 100.0 ppb	< 10.0 ppb
Trace Impurities - Silver (Ag)	≤ 1.0 ppb	0.5 ppb
Trace Impurities – Sodium (Na)	≤ 100.0 ppb	2.3 ppb
Trace Impurities – Strontium (Sr)	≤ 1.0 ppb	< 0.2 ppb
Trace Impurities – Tantalum (Ta)	≤ 1.0 ppb	1.6 ppb
Trace Impurities – Thallium (TI)	≤ 5.0 ppb	< 2.0 ppb
Trace Impurities – Tin (Sn)	≤ 5.0 ppb	4.0 ppb
Trace Impurities – Titanium (Ti)	≤ 1.0 ppb	1.5 ppb
Trace Impurities – Vanadium (V)	≤ 1.0 ppb	< 0.2 ppb
Trace Impurities – Zinc (Zn)	≤ 5.0 ppb	0.8 ppb
Trace Impurities – Zirconium (Zr)	≤ 1.0 ppb	0.3 ppb
		- FFF

Hydrochloric Acid, 36.5-38.0% BAKER INSTRA-ANALYZED® Reagent For Trace Metal Analysis






Material No.: 9530-33 Batch No.: 22G2862015

Test		
Test	Specification	Result

For Laboratory,Research,or Manufacturing Use Product Information (not specifications): Appearance (clear, fuming liquid) Meets ACS Specifications Storage Condition: Store below 25 °C.

Country of Origin: USA Packaging Site: Phillipsburg Mfg Ctr & DC



Vice President Global Quality