

284 Sheffield Street, Mountainside, New Jersey 07092, Phone: 908 789

8900, Fax: 908 789 8922

#### **Prep Standard - Chemical Standard Summary**

Order ID :	Q1666

Test: Anions Group2,BOD5,Flash Point,pH,TSS

Prepbatch ID:

Sequence ID/Qc Batch ID: LB135226,LB135227,LB135236,LB135277,LB135351,
Standard ID: WP110259,WP110386,WP111323,WP112435,WP112436,WP112437,WP112438,WP112439,WP112440,WP112441,WP 112442,WP112443,WP112444,WP112538,WP112539,WP112540,WP112541,WP112542,
Chemical ID: M5673,M6041,W2647,W2653,W2654,W3058,W3059,W3063,W3071,W3072,W3093,W3103,W3105,W3109,W3112,W3113,W3144,W3149,W3161,W3178,W3180,W3191,W3193,



Alliance TECHNICAL GROUP

Fax: 908 789 8922

#### Wet Chemistry STANDARD PREPARATION LOG

Recipe ID	NAME_	NO.	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipetteID</u>	Supervised By  Jignesh Parikh		
4035	IC ELUENT CONCENTRATE FOR IC-1	WP110259	10/16/2024	04/16/2025	lwona Zarych	WETCHEM_S CALE_5 (WC	None	10/17/2024		
	SC-5)									

**FROM** 2.10000gram of W2647 + 84.75000gram of W3058 + 913.15000ml of W3112 = Final Quantity: 1000.000 ml

Recipe				Expiration	Prepared			Supervised By
<u>ID</u>	<u>NAME</u>	<u>NO.</u>	Prep Date	<u>Date</u>	<u>By</u>	<u>ScaleID</u>	<u>PipetteID</u>	lwona Zarych
1841	Sulfuric Acid, 1N	WP110386	10/24/2024	04/24/2025	Rubina Mughal	None	WETCHEM_F	•
							IPETTE_3	10/24/2024

**FROM** 2.80000ml of M5673 + 97.20000ml of W3112 = Final Quantity: 100.000 ml





Fax: 908 789 8922

#### Wet Chemistry STANDARD PREPARATION LOG

Recipe ID	NAME	NO.	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipetteID</u>	Supervised By Iwona Zarych
1571	Sodium hydroxide, 1N	<u>WP111323</u>	01/09/2025	07/09/2025	Rubina Mughal	WETCHEM_S CALE 8 (WC	None	01/09/2025
	4 00000		F: 10			SC-7)		01/09/2023

**FROM** 4.00000gram of W3113 + 96.00000ml of W3112 = Final Quantity: 100.000 ml

Recipe ID	<u>NAME</u>	<u>NO.</u>	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipetteID</u>	Supervised By Iwona Zarych
2487	Anions 300/9056 calibration standard 1	<u>WP112435</u>	03/21/2025	03/22/2025	Niha Farheen Shaik	None	None	03/24/2025

**FROM** 10.00000ml of W3112 = Final Quantity: 10.000 ml



Alliance TECHNICAL GROUP

Fax: 908 789 8922

#### Wet Chemistry STANDARD PREPARATION LOG

Recipe ID	NAME	NO.	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipetteID</u>	Supervised By Iwona Zarych
24	Anions 300/9056 calibration standard 2	<u>WP112436</u>	03/21/2025	03/22/2025	Niha Farheen Shaik	None	WETCHEM_F IPETTE_3	03/24/2025
	0.00000   51410400   0.00000   5	140440 =		10.000			(VVC)	

<u>FROM</u>	0.20000ml of W3180 + 9.80000ml of W3112 = Final Quantity: 10.000 ml	

Recipe ID	<u>NAME</u>	NO.	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipetteID</u>	Supervised By Iwona Zarych
25	Anions 300/9056 calibration standard 3	WP112437	03/21/2025	03/22/2025	Niha Farheen Shaik	None	WETCHEM_F IPETTE_3 (WC)	03/24/2025

**FROM** 0.40000ml of W3180 + 9.60000ml of W3112 = Final Quantity: 10.000 ml



Alliance

Fax: 908 789 8922

#### Wet Chemistry STANDARD PREPARATION LOG

Recipe ID	NAME	NO.	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipetteID</u>	Supervised By Iwona Zarych
26	Anions 300/9056 calibration standard 4	WP112438	03/21/2025	03/22/2025	Niha Farheen Shaik	None	WETCHEM_F IPETTE_3	03/24/2025
	0.50000   5.0000   0.50000   5	140440 =		10.000			(VVC)	

<b>FROM</b>	0.50000ml of W3180 + 9.50000ml of W3112 = Final Quantity: 10.000 ml
-------------	---

Recipe ID	NAME	<u>NO.</u>	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipetteID</u>	Supervised By Iwona Zarych
3680	Anions 300/9056 calibration standard 5-CCV	<u>WP112439</u>	03/21/2025	03/22/2025	Niha Farheen Shaik	None	Glass Pipette-A	03/24/2025

**FROM** 45.00000ml of W3112 + 5.00000ml of W3180 = Final Quantity: 50.000 ml



Aliance

Fax: 908 789 8922

#### Wet Chemistry STANDARD PREPARATION LOG

Recipe ID	NAME.	<u>NO.</u>	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipettelD</u>	Supervised By Iwona Zarych
3679	Anions 300/9056 calibration standard 6	<u>WP112440</u>	03/21/2025	03/22/2025	Niha Farheen Shaik	None	Glass Pipette-A	03/24/2025

<u>FROM</u>	2.00000ml of W3180 + 8.00000ml of W3112 = Final Quantity: 10.000 ml
-------------	---

Recipe ID	NAME	<u>NO.</u>	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipetteID</u>	Supervised By Iwona Zarych
3681	Anions 300/9056 calibration standard 7	<u>WP112441</u>	03/21/2025	03/22/2025	Niha Farheen Shaik	None	Glass Pipette-A	03/24/2025

**FROM** 2.50000ml of W3180 + 7.50000ml of W3112 = Final Quantity: 10.000 ml





Fax: 908 789 8922

#### Wet Chemistry STANDARD PREPARATION LOG

Recipe ID	<u>NAME</u>	NO.	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipettelD</u>	Supervised By Iwona Zarych
3233	Anions 300/9056 ICV-LCS std	<u>WP112442</u>	03/21/2025	03/22/2025	Niha Farheen Shaik	None	Glass Pipette-A	03/24/2025

<b>FROM</b> 45.0000ml of W3112 + 5.0000ml of W3063 = Final Quantity: 50.000 ml
--

Recipe				Expiration	<u>Prepared</u>			Supervised By
<u>ID</u>	<u>NAME</u>	NO.	Prep Date	<u>Date</u>	<u>By</u>	<u>ScaleID</u>	<u>PipetteID</u>	Iwona Zarych
4036	IC ELUENT FOR IC-1	WP112443	03/21/2025	04/16/2025	Niha Farheen	None	None	·
					Shaik			03/24/2025

**FROM** 1980.00000ml of W3112 + 20.00000ml of WP110259 = Final Quantity: 2000.000 ml



Alliance

Fax: 908 789 8922

#### Wet Chemistry STANDARD PREPARATION LOG

	=	d By
ID   NAME   NO.   Prep Date   Date	By ScaleID PipetteID Iwona Zary	/ch
4037 IC H2SO4 FOR IC-1 WP112444 03/21/2025 04/21/2025 Nih	Niha Farheen None Glass	
	Shaik Pipette-A 03/24/202	25

<b>FROM</b>	5.60000ml of M6041 + 994.40000ml of W3112 = Final Quantity: 1000.000 ml
-------------	---

Recipe				<b>Expiration</b>	<u>Prepared</u>			Supervised By
<u>ID</u>	<u>NAME</u>	NO.	Prep Date	<u>Date</u>	<u>By</u>	<u>ScaleID</u>	<u>PipetteID</u>	Iwona Zarych
127	BOD Dilution fluid	WP112538	03/28/2025	03/29/2025	Rubina Mughal	None	None	,
								03/28/2025

FROM 18.00000L of W3112 + 3.00000PILLOW of W3144 = Final Quantity: 18.000 L



Fax: 908 789 8922

#### Wet Chemistry STANDARD PREPARATION LOG

Recipe ID	NAME_	NO.	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipetteID</u>	Supervised By Iwona Zarych
129	Glutamic acid-glucose mix for BOD	WP112539	03/28/2025	03/29/2025	Rubina Mughal	CALE_7 (WC	None	03/28/2025
FROM	0.15000gram of W2653 + 0.15000gra	am of W265	4 + 1000.000	00ml of W3112	= Final Quanti	<del>SC-6)</del> ty: 1000.000 ml		

ROM	0.15000gram of W2653	+ 0.15000gram of W2654 +	1000.00000ml of W3112	= Final Quantity: 1000.000 ml
-----	----------------------	--------------------------	-----------------------	-------------------------------

Recipe				Expiration	Prepared			Supervised By
<u>ID</u>	<u>NAME</u>	<u>NO.</u>	Prep Date	<u>Date</u>	<u>By</u>	<u>ScaleID</u>	<u>PipetteID</u>	Iwona Zarych
128	polyseed seed control	WP112540	03/28/2025	03/29/2025	Rubina Mughal	None	None	·
								03/28/2025

 $1.00000PILLOW ext{ of } W3059 + 300.00000ml ext{ of } WP112538 ext{ = Final Quantity: } 300.000 ext{ ml}$ **FROM** 



Alliance

Fax: 908 789 8922

#### Wet Chemistry STANDARD PREPARATION LOG

ID N	IAME	<u>NO.</u>	Prep Date	Expiration Date	<u>Prepared</u> <u>By</u>	<u>ScaleID</u>	<u>PipetteID</u>	Supervised By Iwona Zarych
	nions 300/9056 calibration tandard 5-CCV	WP112541	03/28/2025	03/29/2025	Niha Farheen Shaik	None	Glass Pipette-A	04/01/2025

<b>FROM</b> 45.00000	oml of W3112 + 5.00000ml	of W3180 = Final Quantity: 50.00	0 ml
----------------------	--------------------------	----------------------------------	------

Recipe				Expiration	Prepared			Supervised By
<u>ID</u>	NAME	<u>NO.</u>	Prep Date	<u>Date</u>	<u>By</u>	<u>ScaleID</u>	<u>PipetteID</u>	Iwona Zarych
3233	Anions 300/9056 ICV-LCS std	WP112542	03/28/2025	03/29/2025	Niha Farheen	None	Glass	
					Shaik		Pipette-A	04/01/2025

**FROM** 45.00000ml of W3112 + 5.00000ml of W3063 = Final Quantity: 50.000 ml



Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
Seidler Chemical	BA-9673-33 / Sulfuric Acid, Instra-Analyzed (cs/6c2.5L)	23D2462010	03/20/2028	09/21/2023 / mohan	09/05/2023 / mohan	M5673
Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
Seidler Chemical	BA-9673-33 / Sulfuric Acid, Instra-Analyzed (cs/6c2.5L)	23D2462010	03/20/2028	08/16/2024 / mohan	08/16/2024 / mohan	M6041
Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
PCI Scientific Supply, Inc.	J3506-5 / SODIUM BICARBONATE, PWD, ACS, 2.5KG	0000240594	06/03/2026	02/24/2020 / AMANDEEP	01/20/2020 / apatel	W2647
Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
PCI Scientific Supply, Inc.	AC156212500 / GLUTAMIC ACID BIOCHEM REG, 250G	A0405990	01/24/2030	01/24/2020 / apatel	01/24/2020 / apatel	W2653
Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date /	Chemtech Lot #
PCI Scientific Supply, Inc.	D16-500 / DEXTROSE ANHYDROUS ACS REAGENT, 500G(New)	186122A	01/24/2030	01/24/2020 / apatel	01/24/2020 / apatel	W2654
Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
PCI Scientific Supply, Inc.	EM-SX0395-3 / SODIUM CARBONATE ANHYDR 2.5KG	2023012653	10/19/2028	09/03/2024 / jignesh	10/19/2023 / lwona	W3058



Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
PCI Scientific Supply, Inc.	136742-80 / POLYSEED	152305	05/30/2025	02/15/2024 / Rubina	10/18/2023 / Iwona	W3059
Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
Inorganic Ventures	300-CAL-A-500ML / 300.0 Calibration Standard, 500 ml	U2-MEB735684	04/09/2025	04/09/2024 / Iwona	11/16/2023 / Iwona	W3063
Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
PCI Scientific Supply, Inc.	AL14455-3 / buffer solution pH 7 yellow	4308H30	07/31/2025	01/02/2024 / JIGNESH	12/06/2023 / Iwona	W3071
Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date /	Chemtech Lot #
PCI Scientific Supply, Inc.	AL14940-1 / Buffer Solution, PH12 (500ml)	2310P21	04/30/2025	01/02/2024 / JIGNESH	12/07/2023 / Iwona	W3072
Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date /	Chemtech Lot #
PCI Scientific Supply, Inc.	566002 / BUFFER PH 7.00 GREEN 1PINT PK6	44001f99	12/31/2025	04/03/2024 / jignesh	04/02/2024 / jignesh	W3093
Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date /	Chemtech Lot #
PCI Scientific Supply, Inc.	4620-32 / MANGANOUS SULFATE SOLUTION-364	2403J02	03/31/2026	04/22/2024 / Iwona	04/22/2024 / Iwona	W3103



Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
PCI Scientific Supply, Inc.	AL69870-8 / SODIUM THIOSULFATE,0.025N,4LIT RE	4403S13	09/30/2025	04/22/2024 / Iwona	04/22/2024 / Iwona	W3105
Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
PCI Scientific Supply, Inc.	AL04100-4 / Alkaline lodide Azide, 1 L	1405D67	04/30/2026	05/23/2024 / Iwona	05/23/2024 / Iwona	W3109
Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
Seidler Chemical	DIW / DI Water	Daily Lab-Certified	07/03/2029	07/03/2024 / Iwona	07/03/2024 / Iwona	W3112
Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
PCI Scientific Supply, Inc.	PC19510-7 / Sodium Hydroxide Pellets 12 Kg	23B1556310	12/31/2025	07/08/2024 / Iwona	07/08/2024 / Iwona	W3113
Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
HACH	1486266 / BOD Nutrient Buffer Pillows, 6 mL concentrate to make 6 L, 50/pk	A4169	06/30/2029	11/20/2024 / rubina	10/01/2024 / Iwona	W3144
	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
Supplier						



Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
PCI Scientific Supply, Inc.	AL13850-1 / Buffer Solution, PH2 (500ml)	2411E26	10/31/2026	12/09/2024 / Iwona	12/09/2024 / Iwona	W3161
Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
PCI Scientific Supply, Inc.	AL14055-3 / PH 4 BUFFER SOLUTION	2411A93	10/30/2026	04/01/2025 / JIGNESH	01/27/2025 / jignesh	W3178
Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
Inorganic Ventures	300-CAL-A-500ML / 300.0 Calibration Standard, 500 ml	V2-MEB742616	02/19/2026	02/19/2025 / Iwona	01/27/2025 / Iwona	W3180
Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date /	Chemtech Lot #
PCI Scientific Supply, Inc.	1601-1 / PH 10.01 BUFFER,COLOR CD 475ML	2410F80	03/31/2026	04/01/2025 / JIGNESH	03/13/2025 / jignesh	W3191
Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
PCI Scientific Supply, Inc.	TCX0014-500ML / p-xylene	C6PEN	03/19/2029	03/21/2025 / rubina	03/19/2025 / lwona	W3193

Sodium Bicarbonate, Powder BAKER ANALYZED® A.C.S. Reagent

(sodium hydrogen carbonate)



Material No.: 3506-05 Batch No.: 0000240594

Manufactured Date: 2019/06/05 Retest Date: 2026/06/03

Revision No: 1

## Certificate of Analysis

Meets ACS Reagent Chemical Requirements,


Test	Specification	Result	
Assay (NaHCO3) (dried basis)	99.7 - 100.3 %	100.1	
Insoluble Matter	<= 0.015 %	< 0.002	
Chloride (Cl)	<= 0.003 %	0.003	
Phosphate (PO4)	<= 0.001 %	0.001	
Sulfur Compounds (as SO4)	<= 0.003 %	0.003	
Calcium (Ca)	<= 0.02 %	0.02	
Frace Impurities – Iron (Fe)	<= 0.001 %	0.001	
Magnesium (Mg)	<= 0.005 %	0.005	
Potassium (K)	<= 0.005 %	0.005	
Ammonium (NH4)	<= 5 ppm	5	
Trace Impurities – ACS – Heavy Metals (as Pb)	<= 5 ppm	5	

For Laboratory, Research or Manufacturing Use Meets Reagent Specifications for testing USP/NF monographs

Country of Origin: US

Packaging Site: Paris Mfg Ctr & DC





## Certificate of Analysis

This is to certify that units of the lot number below were tested and found to comply with the specifications of the grade listed. Certain data have been supplied by third parties. Acros Organics expressly disclaims all warranties, expressed or implied, including the implied warranties of merchantability and fitness for a particular purpose. Products are for research use or further manufacturing. Not for direct administration to human or animals. It is the responsibility of the purchaser, formulator or those performing further manufacturing to determine suitability based upon the intended use of the end product. Products are tested to meet the analytical requirements of the noted grade. The following information is the actual analytical results obtained.

Catalog Number	15621	Quality Test / Release Date	13 March 2019			
Lot Number	A0405990	Suggested Retest Date	March 2022			
Description	L(+)-Glutamic acid,99%					
Country of Origin	CHINA					
Declaration of Origin	plant					

Origin Comment	The product is made by fermentation of sugar molasses	
----------------	---	--

Result Name	Specifications	Test Value
Appearance (Color)	White	White
Appearance (Form)	Powder	Powder
Infrared spectrum	Conforms	Conforms
Titration with NaOH	98.5 to 100.5 % (On dried substance)	99.32 % (On dried substance)
Loss on drying	=<0.5 % (105°C, 3 hrs)	0.002 % (105°C, 3 hrs)
Heavy metals (as Pb)	=<10 ppm	=<10 ppm
Sulfated ash	=<0.1 %	0.08 %
Other amino acids	not detectable	not detectable
Specific optical rotation	+30.5° to +32.5° (20°C, 589 nm) (on dried substance)	+32° (20°C, 589 nm) (on dried substance)
Specific optical rotation	(c=10, 2N HCI)	(c=10, 2N HCI)
Chloride (CI)	=<200 ppm	=<200 ppm
Iron (Fe)	=<30 ppm	=<10 ppm
Sulfate (SO4)	=<300 ppm	=<200 ppm
Ammonium (NH4)	=<200 ppm	=<200 ppm
Arsenic oxide (As2O3)	=<1 ppm	=<1 ppm





L. Van den Broek, QA Manager

Acros Organics ENA23, zone 1, nr 1350, Janssen Pharmaceuticalaan 3a, B-2440 Geel, Belgium Tel +32 14/57.52.11 - Fax +32 14/59.34.34 Internet: <a href="http://www.acros.com">http://www.acros.com</a> 1 Reagent Lane, Fair Lawn, NJ 07410,USA Fax 201-796-1329

Issued: 24 January 2020



# RICCA CHEMICAL COMPANY®

O.

1490 Lammers Pike Batesville, IN 47006 http://www.riccachemical.com

1-888-GO-RICCA customerservice@riccachemical.com

# Certificate of Analysis

Buffer, Reference Standard, pH  $7.00 \pm 0.01$  at 25°C (Color Coded Yellow)

Lot Number: 4308H30

Product Number: 1551

Manufacture Date: AUG 09, 2023

Expiration Date: JUL 2025

The certified value for this product is confirmed in independent testing by a second qualified chemist.

The NIST traceable pH value is certified to  $\pm 0.01$  at 25 °C only. All other pH values at their corresponding temperatures are accurate to  $\pm 0.05$ .

5 10 15 20 25 35 40 45 Hq 7.12 7.09 7.06 7.04 7.027.00 6.99 6.98 6.98 6.97 6.97

Name	CAS#	Grade		
Water	7732-18-5	ACS/ASTM/USP/EP		
Sodium Phosphate Dibasic	7558-79-4	ACS		
Potassium Dihydrogen Phosphate	7778-77-0	ACS		
Preservative	Proprietary			
Yellow Dye	Proprietary	coccottiti S. Tues and et e e e		
Sodium Hydroxide	1310-73-2	Reagent		

Test	Specification	Result		
Appearance	Yellow liquid	Passed	*Not a certified value	
Test	Certified Value	Uncertainty	NIST SRM#	
pH at 25°C (Method: SQCP027, SQCP033)	7.002	0.02	186-I-g, 186-II-g, 191d	

Specification	Reference
Commercial Buffer Solutions	ASTM (D 1293 B)
Buffer A	ASTM (D 5464)
Buffer A	ASTM (D 5128)

pH measurements were performed in our Batesville, IN laboratory under ISO/IEC 17025 accreditation (ANAB Certificate L2387.02) and are certified traceable to National Institute of Standards and Technology (NIST) Standard Reference Material as indicated above via an unbroken chain of comparisons. The uncertainty is calculated from the uncertainty of the measurement variation from sample to sample, the uncertainty in the NIST Standard Reference Material, and the uncertainty of the measurement process. The uncertainty is multiplied by k=2, corresponding to 95% coverage in a normal distribution. Volumetric glassware complies with Class A tolerance requirements of ASTM E 288 and NIST Circular 434; it is calibrated before first use and recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated regularly with a thermometer traceable to NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batch records document raw material traceability and production and testing history for each lot manufactured.

Part Number	Size / Package Type	Shelf Life (Unopened Container)
1551-2.5	10 L Cubitainer®	24 months
1551-5	20 L Cubitainer®	24 months
Possesses de d'Otens en 1500 ou	· · · · · · · · · · · · · · · · · · ·	24 months

Recommended Storage: 15°C - 30°C (59°F - 86°F)

Youl Drandon

Paul Brandon (08/09/2023)

**Production Manager** 

This document is designed to comply with ISO Guide 31 "Reference Materials -- Contents of Certificates and Labels."

## This product was tested in an ISO 17025 Accredited Laboratory

This test report shall not be reproduced, except in full, without the written approval of Ricca Chemical Company.

Version: 1.3 Lot Number: 4308H30 Product Number: 1551 Page 2 of 2

# Certificate Of Analysis




Date of Release: 1/27/2023

Name: Sodium Carbonate, Anhydrous

Powder, ACS

Item No: SX0395 All Sizes Lot / Batch No: 2023012653 Country of Origin: India



ltem	Specifications	Analysis
Assay (calculated on dried substance)	99.5% min.	100.2%
Calcium (Ca)	0.03% max.	0.004%
Chloride (CI)	0.001% max.	<0.001%
Color	White	Passes Test
Form	Powder	Passes Test
Heavy metals (by ICP-OES)	5 ppm max.	<5 ppm
Insoluble Matter	0.01% max.	0.003%
Iron (Fe)	5 ppm max.	<5 ppm
Loss on heating at 285C	1.0% max.	0.1%
Magnesium (Mg)	0.005% max.	0.0008%
Phosphate (PO4)	0.001% max.	<0.001%
Potassium (K)	0.005% max.	0.003%
Silica (SiO2)	0.005% max.	<0.005%
Sulfur compounds (as SO4)	0.003% max.	<0.003%

Joe Schoellkopff

Quality Control Manager

This document has been produced electronically and is valid without a signature.

EMD Millipore is a division of Merck KGaA, Darmstadt, Germany

**EMD Millipore Corporation** 

400 Summit Drive Burlington, MA 01803 U.S.A.

Form number: 00005624CA, Rev. 2.0





#### **CERTIFICATE OF ANALYSIS**

PO BOX 130549 Spring, TX 77393 Phone: (281) 298-9410 Fax: (281) 298-9411

#### FINISHED PRODUCT, LOT NUMBER, MFG. /EXP DATE:

PolySeed® • Part No. P-110 • Lot 152305 • Mfg. Date: 05/2023 • Exp. Date: 05/2025

#### FORMULATION:

The formulation for this product contains a range of naturally occurring microorganisms, which are known to be non-pathogenic to man or animals.

#### **VIABLE COUNT, FINAL TEST RESULT:**

The product has been fully tested in accordance with Finished Product Specifications and contains a minimum viable count of 4.00 x10<sup>9</sup> cfu/a.

#### GLUCOSE/GLUTAMIC-ACID RESULTS:

Tested results within acceptable range 198 +/- 30.5 mg/L (167.5 - 228.5 mg/L). GGA Lot# L257-09 – Average Test Result: 203.4

See www.polyseed.com for details.

#### SEED CONTROL FACTOR:

Tested results within acceptable range 0.6 – 1.0 see www.polyseed.com for details

#### SALMONELLA TEST RESULT:

The product has been shown to be Salmonella negative using procedures recommended in the Microbiology Laboratory Guidebook, published by the USDA Food Safety and Inspection Service.

The purpose of this document is to assure that the Finished Product conforms to the above specification.

Signature:

Date: 05/15/2023

**Quality Control Department** 

POLYSEED.Ref.1.19

Revised Jan 23







## Certificate of Analysis

300 Technology Drive Christiansburg, VA 24073 USA inorganicventures.com

W3063 rec. 11/16/23 12 P: 800-669-6799/540-585-3030 F: 540-585-3012 info@inorganicventures.com

#### 1.0 ACCREDITATION / REGISTRATION

**INORGANIC VENTURES** is accredited to ISO 17034, "General Requirements for the Competence of Reference Material Producers" and ISO/IEC 17025, "General Requirements for the Competence of Testing and Calibration Laboratories". Inorganic Ventures is also an ISO 9001 registered manufacturer (QSR Certificate Number QSR-1034).



#### 2.0 PRODUCT DESCRIPTION

Product Code:

Multi Analyte Ion Chromatography Solution

Catalog Number:

300-CAL-A

Lot Number:

U2-MEB735684

Matrix:

H20

Value / Analyte(s):

150 µg/mL ea:

Sulfate,

100 μg/mL ea: Bromide, 50 μg/mL ea: o-Phosphate as P.

30 µg/mL ea:

Chloride,

Nitrite as N,

25 μg/mL ea: Nitrate as N, 20 μg/mL ea:

Fluoride

#### 3.0 CERTIFIED VALUES AND UNCERTAINTIES

**ANALYTE** 

**CERTIFIED VALUE** 

ANALYTE

**CERTIFIED VALUE** 

Bromide, Br

100.0 ± 0.5 μg/mL

Chloride, CI

30.00 ± 0.14 µg/mL

Fluoride, F-

20.00 ± 0.06 µg/mL

Nitrate as N, NNO3-

25.00 ± 0.09 µg/mL

Nitrite as N, NNO2-

30.00 ± 0.15 µg/mL

o-Phosphate as P. PPO4

50.00 ± 0.18 µg/mL

Sulfate, SO4

 $150.0 \pm 0.8 \, \mu g/mL$ 

Density:

0.999 g/mL (measured at 20 ± 4 °C)

**Assay Information:** 

<b>ANALYTE</b> Br	METHOD IC Assay	NIST SRM# 3184	<b>SRM LOT#</b> 151130
Br	Fajans	999c	999c
CI	IC Assay	3182	190830
CI	Fajans	999c	999c
F-	IC Assay	3183	140203
NNO3-	IC Assay	3185	170309
NNO2-	IC Assay		traceable to 40h
PPO4	IC Assay	3186	170606
SO4	IC Assay	3181	080603

- The Calculated Value is a value calculated from the weight of a starting material that has been certified directly vs. a National Institute of Standards and Technology (NIST) SRM/RM. See Sec 4.2 for balance traceability.

The following equations are used in the calculation of the certified value and the uncertainty. Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of k = 2.

#### Characterization of CRM/RM by Two or More Methods

Certified Value, X<sub>CRM/RM</sub>, where two or more methods of characterization are used is the weighted mean of the results:

 $X_{CRM/RM} = \Sigma(w_i) \{X_i\}$ 

X<sub>i</sub> = mean of Assay Method i with standard uncertainty u<sub>char i</sub>

w<sub>i</sub> = the weighting factors for each method calculated using the inverse square of the variance;

 $w_i = (1/u_{char i})^2 / (\Sigma (1/(u_{char i})^2)$ 

CRM/RM Expanded Uncertainty (t) =  $U_{CRM/RM} = k (u^2_{Cher} + u^2_{bb} + u^2_{lts} + u^2_{ts})^{\frac{1}{2}}$ 

k = coverage factor = 2

 $u_{char} = [\Sigma((w_i)^2 (u_{char})^2)]^{\frac{1}{2}}$  where  $u_{char}$  are the errors from each characterization method

ubb = bottle to bottle homogeneity standard uncertainty

uits = long term stability standard uncertainty (storage)

uts = transport stability standard uncertainty

#### Characterization of CRM/RM by One Method

Certified Value,  $X_{CRN/RM}$ , where one method of characterization is used is the mean of individual results:

X<sub>CRM/RM</sub> = (X<sub>a</sub>) (u<sub>char a</sub>)

X<sub>a</sub> = mean of Assay Method A with

uchar a = the standard uncertainty of characterization Method A

CRM/RM Expanded Uncertainty (±) =  $U_{CRM/RM} = k (u^2_{char} + u^2_{bb} + u^2_{lts} + u^2_{bb})^{1/2}$ 

k = coverage factor = 2

uchar a = the errors from characterization

u<sub>bb</sub> = bottle to bottle homogeneity standard uncertainty

u<sub>lts</sub> = long term stability standard uncertainty (storage) u<sub>ts</sub> = transport stability standard uncertainty

#### 4.0 TRACEABILITY TO NIST

- This product is traceable to NIST via an unbroken chain of comparisons. The uncertainties for each certified value are reported, taking into account the SRM/RM uncertainty error and the measurement, weighing and volume dilution errors. In rare cases where no NIST SRM/RM are available, the term 'in-house std.' is specified.

#### 4.1 Thermometer Calibration

- All thermometers are NIST traceable through thermometers that are calibrated by an accredited calibration laboratory.

#### 4.2 Balance Calibration

 All analytical balances are calibrated by an accredited calibration laboratory and procedure. The weights used for testing are annually compared to master weights and are traceable to NIST.

#### 4.3 Glassware Calibration

- An in-house procedure is used to calibrate all Class A glassware used in the manufacturing and quality control of CRM/RMs.

#### 5.0 CHROMATOGRAM

N/A

#### 6.0 INTENDED USE

**6.1** This standard is intended for the calibration of analytical instruments and validation of analytical methods as appropriate. This CRM may be used in connection with EPA Methods 6010, 6020 (all versions), Standard Methods 3120 B and USP <232> / ICH Q3D,

**6.2** For products attaining traceability through Inorganic Ventures' Primary Certified Reference Materials (PCRM™) see the Limited License to Use PCRM™ in the Inorganic Ventures <u>Terms and Conditions of Sale</u>. <a href="https://www.inorganicventures.com/terms-and-conditions-sale">https://www.inorganicventures.com/terms-and-conditions-sale</a>. The Terms and Conditions contain information on the use of materials traceable to PCRM™ certified reference materials. This Limited License agreement is especially pertinent for laboratories accredited under ISO:17034.

## 7.0 INSTRUCTIONS FOR THE CORRECT USE OF THIS REFERENCE MATERIAL

#### 7.1 Storage and Handling Recommendations

- Store between approximately 4° 30° C while in sealed TCT bag.
- While stored in the sealed TCT bag, transpiration of this CRM/RM is negligible. After opening the sealed TCT bag transpiration of the CRM/RM will occur, resulting in a gradual increase in the analyte concentration(s). It is the responsibility of the user to account for this effect. When the bottle is weighed both before and after being placed in storage, the mass difference observed will be a measure of transpiration mass loss.
- After opening the sealed TCT bag, keep cap tightly sealed when not in use and store between  $4^{\circ}$   $24^{\circ}$  C to minimize the effects of transpiration. Use at  $20^{\circ} \pm 4^{\circ}$  C to minimize volumetric dilution error when using the reported density. Do not pipette from the container. Do not return removed aliquots to container.
- For more information, visit

www.inorganicventures.com/TCT

#### 8.0 HAZARDOUS INFORMATION

- Please refer to the Safety Data Sheet for information regarding this CRM/RM.

#### 9.0 HOMOGENEITY

- This solution was mixed according to an in-house procedure and is guaranteed to be homogeneous. Homogeneity data indicate that the end user should take a minimum sample size of 0.2 mL to assure homogeneity.

#### 10.0 QUALITY STANDARD DOCUMENTATION

#### 10.1 ISO 9001 Quality Management System Registration

- QSR Certificate Number QSR-1034

## 10.2 ISO/IEC 17025 "General Requirements for the Competence of Testing and Calibration Laboratories"

- Chemical Testing - Accredited / A2LA Certificate Number 883.01

## 10.3 ISO 17034 "General Requirements for the Competence of Reference Material Producers"

- Reference Material Producer - Accredited / A2LA Certificate Number 883.02

Inorganic Ventures, 300 Technology Drive, Christiansburg, Va. 24073, USA; Telephone: 800.669.6799; 540.585.3030, Fax: 540.585.3012; inorganicventures.com; info@inorganicventures.com

#### 11.0 CERTIFICATION, LOT EXPIRATION AND PERIOD OF VALIDITY

#### 11.1 Certification Issue Date

August 10, 2023

- The certification is valid within the measurement uncertainty specified provided the CRM/RM is stored and handled in accordance with instructions given in Sec 7.1. This certification is nullified if instructions in Sec 7.1 are not followed or if the CRM/RM is damaged, contaminated, or otherwise modified.

#### 11.2 Lot Expiration Date

- August 10, 2028
- The date after which this CRM/RM should not be used.
- The lot expiration date reflects the period of time that the stability of a CRM/RM can be supported by long term stability studies conducted on properly stored and handled CRM/RMs. Lot expiration is limited primarily by transpiration (loss of water from the solution) and infrequently by chemical stability.

#### 11.3 Period of Validity

- Sealed TCT Bag Open Date: \_\_\_\_\_
- This CRM/RM should not be used longer than one year (or six months in the case of a 30 mL bottle) from the date of opening the aluminized bag or after the date given in Sec. 11.2, whichever comes first. This is contingent upon the CRM/RM being stored and handled in accordance with the instructions given in Sec. 7.1.

## 12.0 NAMES AND SIGNATURES OF CERTIFYING OFFICERS Certificate Prepared By:

Justin Dirico Stock Processing Supervisor

Certificate Approved By:

Nicholas Plymale Custom VSM Coordinator

**Certifying Officer:** 

Paul Gaines Chairman / Senior Technical Director PORS



RICCA CHEMICAL COMPANY®

W 3072

MC. (2/01/23)

Certificate of Analysis

1841 Broad Street Pocomoke City, MD 21851 http://www.riccachemical.com 1-888-GO-RICCA customerservice@riccachemical.com

Buffer, Reference Standard, pH  $12.00 \pm 0.01$  at 25°C

Lot Number: 2310P21

Product Number: 1615

Manufacture Date: OCT 24, 2023

Expiration Date: APR 2025

The certified value for this product is confirmed in independent testing by a second qualified chemist.

°C 15 35 40 12.35 12.17 11.99 11.78 11.62 Нg

Name	CAS#	Grade
Water	7732-18-5	ACS/ASTM/USP/EP
Potassium Chloride	7447-40-7	ACS
Sodium Hydroxide	1310-73-2	Reagent

Test	Specification	Result	
Appearance	Colorless liquid	Passed	*Not a certified value.

Test	Certified Value	Uncertainty	NIST SRM#
pH at 25°C (Method: SQCP027, SQCP033)	12.005	0.02	186-I-g, 186-II-g, 191d

pH measurements were performed in our Pocomoke City, MD laboratory under ISO/IEC 17025 accreditation (ANAB Certificate L2387.01) and are certified traceable to National Institute of Standards and Technology (NIST) Standard Reference Material as indicated above via an unbroken chain of comparisons. The uncertainty is calculated from the uncertainty of the measurement variation from sample to sample, the uncertainty in the NIST Standard Reference Material, and the uncertainty of the measurement process. The uncertainty is multiplied by k=2, corresponding to 95% coverage in a normal distribution. Volumetric glassware complies with Class A tolerance requirements of ASTM E 288 and NIST Circular 434; it is calibrated before first use and recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated regularly with a thermometer traceable to NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batch records document raw material traceability and production and testing history for each lot manufactured.

Part Number	Size / Package Type	Shelf Life (Unopened Container)
1615-1	4 L natural poly	18 months
1615-16	500 mL clear PET-G	18 months
1615-32	1 L natural poly	18 months
1615-5	20 L Cubitainer®	18 months

Recommended Storage: 15°C - 30°C (59°F - 86°F)

Storen Travers.

Sharon Travers (10/24/2023)

**Operations Manager** 

This document is designed to comply with ISO Guide 31 "Reference Materials -- Contents of Certificates and Labels."

## This product was tested in an ISO 17025 Accredited Laboratory

This test report shall not be reproduced, except in full, without the written approval of Ricca Chemical Company.

Version: 1.3 Lot Number: 2310P21 Product Number: 1615 Page 2 of 2

Certificate of Analysis Page 1 of 1



## Certificate of Analysis

1 Reagent Lane Fair Lawn, NJ 07410 201.796.7100 tel 201.796.1329 fax

Thermo Fisher Scientific's Quality System has been found to conform to Quality Management System Standard ISO9001:2015 by SAI Global Certificate Number CERT – 0120632

This is to certify that units of the lot number below were tested and found to comply with the specifications of the grade listed. Certain data have been supplied by third parties. Thermo Fisher Scientific expressly disclaims all warranties, expressed or implied, including the implied warranties of merchantability and fitness for a particular purpose. Products are for research use or further manufacturing. Not for direct administration to humans or animals. It is the responsibility of the final formulator and end user to determine suitability based upon the intended use of the end product. Products are tested to meet the analytical requirements of the noted grade. The following information is the actual analytical results obtained.

Catalog Number	D16	Quality Test / Release Date	03/19/2019
Lot Number	186122A		
Description	DEXTROSE, ANHYDROUS, A.C.S.		
Country of Origin	United States	Suggested Retest Date	Mar/2022
Chemical Origin	Organic - Plant		
BSE/TSE Comment	No animal products are used as starting processing aids, or any other material that	•	
Chemical Comment			

N/A			
Result Name	Units	Specifications	Test Value
APPEARANCE		REPORT	White, granular powder
TITRATABLE ACID	MEQ/G	<= 0.002	<0.002
STARCH		= PASS TEST	pass test
SPECIFIC ROTATION @ 25 C	DEGREES (+ OR -)	Inclusive Between +52.5 - +53.0	53.0
SULFATE & SULFITE	%	<= 0.005	<0.005
IRON (Fe)	ppm	<= 5	<5
CHLORIDE	%	<= 0.01	<0.01
IGNITION RESIDUE	%	<= 0.02	<0.02
IDENTIFICATION	PASS/FAIL	= PASS TEST	pass test
HEAVY METALS (as Pb)	ppm	<= 5	<5
LOSS ON DRYING @ 105 C	%	<= 0.2	<0.2
INSOLUBLE MATTER	%	<= 0.005	0.002

Derisa Bailey- Wyche


Quality Assurance Specialist - Certificate of Analysis Fair Lawn

Sulfuric Acid BAKER INSTRA-ANALYZED® Reagent

For Trace Metal Analysis

Low Selenium









Material No.: 9673-33 Batch No.: 23D2462010

Manufactured Date: 2023-03-22

Retest Date: 2028-03-20 Revision No.: 0

## Certificate of Analysis

Test	Specification	Result	_
ACS – Assay (H <sub>2</sub> SO <sub>4</sub> )	95.0 - 98.0 %	96.1 %	_
Appearance	Passes Test	Passes Test	
ACS – Color (APHA)	≤ 10	5	
ACS – Residue after Ignition	≤ 3 ppm	< 1 ppm	
ACS - Substances Reducing Permanganate (as SO2)	≤ 2 ppm	< 2 ppm	
Ammonium (NH <sub>4</sub> )	≤ 1 ppm	1 ppm	
Chloride (Cl)	≤ 0.1 ppm	< 0.1 ppm	
Nitrate (NO <sub>3</sub> )	≤ 0.2 ppm	< 0.1 ppm	
Phosphate (PO <sub>4</sub> )	≤ 0.5 ppm	< 0.1 ppm	
Trace Impurities - Aluminum (AI)	≤ 30.0 ppb	< 5.0 ppb	
Arsenic and Antimony (as As)	≤ 4.0 ppb	< 2.0 ppb	
Trace Impurities - Boron (B)	≤ 10.0 ppb	8.5 ppb	
Trace Impurities – Cadmium (Cd)	≤ 2.0 ppb	< 0.3 ppb	
Trace Impurities – Chromium (Cr)	≤ 6.0 ppb	< 0.4 ppb	
Trace Impurities - Cobalt (Co)	≤ 0.5 ppb	< 0.3 ppb	
Trace Impurities – Copper (Cu)	≤ 1.0 ppb	< 0.1 ppb	
Trace Impurities – Gold (Au)	≤ 10.0 ppb	0.5 ppb	
Heavy Metals (as Pb)	≤ 500.0 ppb	< 100.0 ppb	
Trace Impurities - Iron (Fe)	≤ 50.0 ppb	1.3 ppb	
Trace Impurities - Lead (Pb)	≤ 0.5 ppb	< 0.5 ppb	
Trace Impurities – Magnesium (Mg)	≤ 7.0 ppb	0.8 ppb	
Trace Impurities – Manganese (Mn)	≤ 1.0 ppb	< 0.4 ppb	
Trace Impurities - Mercury (Hg)	≤ 0.5 ppb	< 0.1 ppb	
Trace Impurities - Nickel (Ni)	≤ 2.0 ppb	0.3 ppb	
Trace Impurities – Potassium (K)	≤ 500.0 ppb	< 2.0 ppb	
Trace Impurities - Selenium (Se)	≤ 50.0 ppb	< 0.1 ppb	
Trace Impurities - Silicon (Si)	≤ 100.0 ppb	31.5 ppb	
Trace Impurities – Silver (Ag)	≤ 1.0 ppb	< 0.3 ppb	

>>> Continued on page 2 >>>

Sulfuric Acid BAKER INSTRA-ANALYZED® Reagent For Trace Metal Analysis Low Selenium





Material No.: 9673-33 Batch No.: 23D2462010

Test	Specification	Result
Trace Impurities – Sodium (Na)	≤ 500.0 ppb	5.4 ppb
Trace Impurities - Strontium (Sr)	≤ 5.0 ppb	< 0.2 ppb
Trace Impurities – Tin (Sn)	≤ 5.0 ppb	< 0.8 ppb
Trace Impurities - Zinc (Zn)	≤ 5.0 ppb	0.4 ppb

For Laboratory, Research, or Manufacturing Use

Country of Origin: USA Packaging Site: Phillipsburg Mfg Ctr & DC



Sulfuric Acid
BAKER INSTRA-ANALYZED® Reagent
For Trace Metal Analysis
Low Selenium





Material No.: 9673-33

Batch No.: 23D2462010 Manufactured Date: 2023-03-22

Retest Date: 2028-03-20

Revision No.: 0

## Certificate of Analysis

Test	Specification	Result
ACS - Assay (H2SO4)	95.0 - 98.0 %	96,1 %
Appearance	Passes Test	Passes Test
ACS - Color (APHA)	≤ 10	5
ACS – Residue after Ignition	≤ 3 ppm	< 1 ppm
ACS - Substances Reducing Permanganate (as SO2)	≤ 2 ppm	< 2 ppm
Ammonium (NH <sub>4</sub> )	≤ 1 ppm	1 ppm
Chloride (CI)	≤ 0.1 ppm	< 0.1 ppm
Nitrate (NO <sub>3</sub> )	≤ 0.2 ppm	< 0.1 ppm
Phosphate (PO <sub>4</sub> )	≤ 0.5 ppm	< 0.1 ppm
Trace Impurities – Aluminum (AI)	≤ 30.0 ppb	< 5.0 ppb
Arsenic and Antimony (as As)	≤ 4.0 ppb	< 2.0 ppb
Trace Impurities - Boron (B)	≤ 10.0 ppb	8.5 ppb
Trace Impurities – Cadmium (Cd)	≤ 2.0 ppb	< 0.3 ppb
Trace Impurities - Chromium (Cr)	≤ 6.0 ppb	< 0.4 ppb
Trace Impurities - Cobalt (Co)	≤ 0.5 ppb	< 0.3 ppb
Trace Impurities - Copper (Cu)	≤ 1.0 ppb	< 0.1 ppb
Trace Impurities - Gold (Au)	≤ 10.0 ppb	0.5 ppb
Heavy Metals (as Pb)	≤ 500.0 ppb	< 100.0 ppb
Trace Impurities - Iron (Fe)	≤ 50.0 ppb	1.3 ppb
Trace Impurities - Lead (Pb)	≤ 0.5 ppb	< 0.5 ppb
Trace Impurities - Magnesium (Mg)	≤ 7.0 ppb	0.8 ppb
Trace Impurities – Manganese (Mn)	≤ 1.0 ppb	< 0.4 ppb
Trace Impurities – Mercury (Hg)	≤ 0.5 ppb	< 0.1 ppb
Trace Impurities - Nickel (Ni)	≤ 2.0 ppb	0.3 ppb
Trace Impurities – Potassium (K)	≤ 500.0 ppb	< 2.0 ppb
Trace Impurities – Selenium (Se)	≤ 50.0 ppb	< 0.1 ppb
Trace Impurities – Silicon (Si)	≤ 100.0 ppb	31.5 ppb
Trace Impurities – Silver (Ag)	≤ 1.0 ppb	< 0.3 ppb

>>> Continued on page 2 >>>

Sulfuric Acid
BAKER INSTRA-ANALYZED® Reagent
For Trace Metal Analysis
Low Selenium





Material No.: 9673-33 Batch No.: 23D2462010

Test	Specification	Result
Trace Impurities - Sodium (Na)	≤ 500.0 ppb	5.4 ppb
Trace Impurities – Strontium (Sr)	≤ 5.0 ppb	< 0.2 ppb
Trace Impurities – Tin (Sn)	≤ 5.0 ppb	< 0.8 ppb
Trace Impurities – Zinc (Zn)	≤ 5.0 ppb	0.4 ppb

For Laboratory, Research, or Manufacturing Use

Country of Origin: USA

Packaging Site: Phillipsburg Mfg Ctr & DC





## RICCA CHEMICAL COMPANY

1490 Lammers Pike Batesville, IN 47006 http://www.riccachemical.com 1-888-GO-RICCA

customerservice@riccachemical.com

Certificate of Analysis Onlong Concession Co

Buffer, Reference Standard, pH  $7.00 \pm 0.01$  at 25°C (Color Coded Yellow)

Lot Number: 4401F99

Product Number: 1551

Manufacture Date: JAN 08, 2024

Expiration Date: DEC 2025

The certified value for this product is confirmed in independent testing by a second qualified chemist.

The NIST traceable pH value is certified to  $\pm 0.01$  at 25 °C only. All other pH values at their corresponding temperatures are accurate to  $\pm 0.05$ .

5 10 15 20 25 30 35 40 45 50 pН 7.12 7.09 7.06 7.04 7.02 7.00 6.99 6.98 6.98 6.97 6.97

Name	CAS#	Grade	115
Water	7732-18-5	ACS/ASTM/USP/EP	
Sodium Phosphate Dibasic	7558-79-4	ACS	
Potassium Dihydrogen Phosphate	7778-77-0	ACS	
Preservative	Proprietary	11 11 7 4	
Yellow Dye	Proprietary		
Sodium Hydroxide	1310-73-2		

Test	Specification	Result	
Appearance	Yellow liquid	Passed	*Not a certified value
Test	Certified Value	Uncertainty	NIST SRM#
pH at 25°C (Method: SQCP027, SQCP033)	7.004	0.02	186-I-g, 186-II-g, 191d

Specification	Reference	
Commercial Buffer Solutions	ASTM (D 1293 B)	
Buffer A	ASTM (D 5464)	
Buffer A	ASTM (D 5128)	

pH measurements were performed in our Batesville, IN laboratory under ISO/IEC 17025 accreditation (ANAB Certificate L2387.02) and are certified traceable to National Institute of Standards and Technology (NIST) Standard Reference Material as indicated above via an unbroken chain of comparisons. The uncertainty is calculated from the uncertainty of the measurement variation from sample to sample, the uncertainty in the NIST Standard Reference Material, and the uncertainty of the measurement process. The uncertainty is multiplied by k=2, corresponding to 95% coverage in a normal distribution. Volumetric glassware complies with Class A tolerance requirements of ASTM E 288 and NIST Circular 434; it is calibrated before first use and recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated regularly with a thermometer traceable to NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batch records document raw material traceability and production and testing history for each lot manufactured.

Part Number	Size / Package Type	Shelf Life (Unopened Container)
1551-1	4 L natural poly	24 months
1551-1CT	4 L Cubitainer®	24 months
1551-2.5	10 L Cubitainer®	24 months
1551-5	20 L Cubitainer®	24 months
		V /V   1.11   1.

Recommended Storage: 15°C - 30°C (59°F - 86°F)

faul Drandon

Paul Brandon (01/08/2024)

**Production Manager** 

This document is designed to comply with ISO Guide 31 "Reference Materials -- Contents of Certificates and Labels."

## This product was tested in an ISO 17025 Accredited Laboratory

This test report shall not be reproduced, except in full, without the written approval of Ricca Chemical Company.

Version: 1.3 Lot Number: 4401F99 Product Number: 1551 Page 2 of 2

1841 Broad Street Pocomoke City, MD 21851 http://www.riccachemical.com 1-888-GO-RICCA

customerservice@riccachemical.com

## Certificate of Analysis

Manganous Sulfate Solution, 364 g/L

Lot Number: 2403J02 Product Number: 4620

Manufacture Date: MAR 15, 2024

Expiration Date: MAR 2026

Name	CAS#	Grade
Water	7732-18-5	ACS/ASTM/USP/EP
Manganous Sulfate Monohydrate	10034-96-5	Reagent
Sulfuric Acid	7664-93-9	ACS

Test	Specification	Result	
Appearance	Pink liquid	Passed	
Assay (by Refractive Index)	360-368 g/L	367 g/L	

Specification	Reference
Manganous Sulfate Solution	ASTM (D 888 A)
Manganous Sulfate Solution	ASTM (D 888 A)
Manganous Sulfate Solution	APHA (4500-O E)
Manganous Sulfate Solution	APHA (4500-O F)
Manganous Sulfate Solution	APHA (4500-O D)
Manganous Sulfate Solution	АРНА (4500-О Е)
Manganous Sulfate Solution	APHA (4500-O F)
Manganous Sulfate Solution	APHA (4500-O D)
Manganous Sulfate Solution	АРНА (4500-О С)
Manganous Sulfate Solution	APHA (4500-O C)
Manganous Sulfate Solution	EPA (360.2)
Manganous Sulfate Solution	EPA (360.2)

Volumetric glassware complies with Class A tolerance requirements of ASTM E 288 and NIST Circular 434; it is calibrated before first use and recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated regularly with a thermometer traceable to NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batch records document raw material traceability and production and testing history for each lot manufactured.

Part Number	Size / Package Type	Shelf Life (Unopened Container)
4620-32	1 L natural poly	24 months

Recommended Storage: 15°C - 30°C (59°F - 86°F)

Version: 1.3 Lot Number: 2403J02 Product Number: 4620 Page 1 of 2



Jose Pena (03/15/2024)

Operations Manager

This document is designed to comply with ISO Guide 31 "Reference Materials -- Contents of Certificates and Labels."

This test report shall not be reproduced, except in full, without the written approval of Ricca Chemical Company.

Version: 1.3 Lot Number: 2403J02 Product Number: 4620 Page 2 of 2

1490 Lammers Pike Batesville, IN 47006 http://www.riccachemical.com 1-888-GO-RICCA

customerservice@riccachemical.com

# Certificate of Analysis

Sodium Thiosulfate, 0.0250 Normal (N/40)

Lot Number: 4403S13 Product Number: 7900

Manufacture Date: MAR 29, 2024

Expiration Date: SEP 2025

This product is specially formulated to increase its stability. A preservative is added to prevent bacterial contamination. However, all Sodium Thiosulfate solutions are subject to slow chemical deterioration and should be restandardized periodically.

Name	CAS#	Grade
Water	7732-18-5	ACS/ASTM/USP/EP
Sodium Thiosulfate Pentahydrate	10102-17-7	ACS
Organic Preservative	Proprietary	
Sodium Carbonate	497-19-8	ACS

Test	Specification	Result	NIST SRM#
Appearance	Colorless liquid	Passed	
Assay (vs. Potassium Iodate/Starch)	$0.02499 \text{-} 0.02501 \text{ N} \text{ at } 20^{\circ}\text{C}$	0.02501 N at 20°C	136


Specification	Reference	
Standard Sodium Thiosulfate Solution, 0.0250 N	APHA (4500-S2- F)	
Standard Sodium Thiosulfate Titrant	APHA (4500-O D)	
Standard Sodium Thiosulfate Titrant	APHA (4500-O E)	
Standard Sodium Thiosulfate Titrant	APHA (4500-O F)	
Standard Sodium Thiosulfate Titrant, 0.025 N	APHA (4500-Cl B)	
Standard Sodium Thiosulfate Titrant	APHA (4500-O C)	
Standard Sodium Thiosulfate Titrant, 0.025 M	АРНА (5530 С)	
Standard Sodium Thiosulfate Solution (0.025 N)	EPA (SW-846) (9031)	
Standard Sodium Thiosulfate solution (0.025 N)	EPA (SW-846) (9034)	

Volumetric glassware complies with Class A tolerance requirements of ASTM E 288 and NIST Circular 434; it is calibrated before first use and recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated regularly with a thermometer traceable to NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batch records document raw material traceability and production and testing history for each lot manufactured.

Part Number	Size / Package Type	Shelf Life (Unopened Container)
7900-1	4 L natural poly	18 months
7900-16	500 mL natural poly	18 months
7900-1CT	4 L Cubitainer®	18 months
7900-32	1 L natural poly	18 months

Recommended Storage: 15°C - 30°C (59°F - 86°F)

Version: 1.3 Lot Number: 4403S13 Product Number: 7900 Page 1 of 2



**Production Manager** 

This document is designed to comply with ISO Guide 31 "Reference Materials  $^{\rm --}$  Contents of Certificates and Labels."

This test report shall not be reproduced, except in full, without the written approval of Ricca Chemical Company.

Version: 1.3 Lot Number: 4403S13 Product Number: 7900 Page 2 of 2

448 West Fork Dr Arlington, TX 76012 http://www.riccachemical.com 1-888-GO-RICCA

customerservice@riccachemical.com

# Certificate of Analysis

Alkaline-Iodide-Azide, Pomeroy Formulation for Dissolved Oxygen (DO) Analysis

Lot Number: 1405D67 Product Number: 535

Manufacture Date: APR 05, 2024

Expiration Date: APR 2026

This solution is intended for use with samples with high Dissolved Oxygen content (above 15 mg/L) and for samples with high concentrations of organic material.

Name	CAS#	Grade	
Water	7732-18-5	ACS/ASTM/USP/EP	
Sodium Iodide	7681-82-5	ACS	
Sodium Hydroxide	1310-73-2	ACS	
Sodium Azide	26628-22-8	Reagent	

Test	Specification	Result
Appearance	Colorless liquid	Passed
Free Iodine	To Pass Test	Passed

Specification	Reference

Alkaline Iodide-Sodium Azide Solution II

ASTM (D 888 A)

Volumetric glassware complies with Class A tolerance requirements of ASTM E 288 and NIST Circular 434; it is calibrated before first use and recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated regularly with a thermometer traceable to NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batch records document raw material traceability and production and testing history for each lot manufactured.

Part Number	Size / Package Type	Shelf Life (Unopened Container)
535-32	1 L natural poly	24 months

Recommended Storage: 15°C - 30°C (59°F - 86°F)

Heidi J Green (04/05/2024) Operations Manager

This test report shall not be reproduced, except in full, without the written approval of Ricca Chemical Company.

Version: 1.3 Lot Number: 1405D67 Product Number: 535 Page 1 of 1



12/14/2022

12/31/2025

### **Sodium Hydroxide (Pellets)**

Material: 0583

Grade: ACS GRADE Batch Number: 23B1556310

Chemical Formula: NaOH
Molecular Weight: 40

CAS #: 1310-73-2

Appearance: Storage: Room Temperature

Pellets

TEST	SPECIFICATION	ANALYSIS	DISPOSITION
Calcium	<= 0.005 %	<0.005 %	PASS
Chloride	<= 0.005 %	0.002 %	PASS
Heavy Metals	<= 0.002 %	<0.002 %	PASS
Iron	<= 0.001 %	<0.001 %	PASS
Magnesium	<= 0.002 %	<0.002 %	PASS
Mercury	<= 0.1 ppm	<0.1 ppm	PASS
Nickel	<= 0.001 %	<0.001 %	PASS
Nitrogen Compounds	<= 0.001 %	<0.001 %	PASS
Phosphate	<= 0.001 %	<0.001 %	PASS
Potassium	<= 0.02 %	<0.02 %	PASS
Purity	>= 97.0 %	99.2 %	PASS
Sodium Carbonate	<= 1.0 %	0.5 %	PASS
Sulfate	<= 0.003 %	<0.003 %	PASS

Manufacture Date:

**Expiration Date:** 

Internal ID #: 710

#### Signature Additional Information

We certify that this batch conforms to the specifications listed.

This document has been electronically produced and is valid without a signature.

Leona Edwardson, Quality Control Sr. Manager - Solon VWR Chemicals, LLC.

28600 Fountain Parkway, Solon OH 44139 USA

Analysis may have been rounded to significant digits in specification limits.

Product meets analytical specifications of the grades listed.



12/14/2022

12/31/2025

Room Temperature

Manufacture Date:

**Expiration Date:** 

Storage:

### **Sodium Hydroxide (Pellets)**

Material: 0583

Grade: ACS GRADE Batch Number: 23B1556310

Chemical Formula: NaOH Molecular Weight: 40

CAS #: 1310-73-2

Appearance:

**Pellets** 

Spec Set: 0583ACS

Internal ID #: 710

Signature Additional Information

We certify that this batch conforms to the specifications listed.

This document has been electronically produced and is valid without a signature.

Leona Edwardson, Quality Control Sr. Manager - Solon VWR Chemicals, LLC. 28600 Fountain Parkway, Solon OH 44139 USA Analysis may have been rounded to significant digits in specification limits.

Product meets analytical specifications of the grades listed.



#### An ISO 9001 Certified Company

### Certificate of Analysis

### This is a Component of 1486266 / LOT A4169

**PRODUCT:** BOD Nutrient Buffer Pillows

PRODUCT NUMBER: 1486227 LOT NUMBER: A4169

**MANUFACTURE DATE:** 06/24/2024 **DATE OF ANALYSIS:** 07/03/2024

TEST	SPECIFICATIONS	RESULTS
Calcium Concentration of a diluted pillow	0.93 to 1.29 ppm	0.960 ppm
Magnesium Concentration of a diluted pillow	0.35 to 0.48 ppm	0.390 ppm
pH in a 6 L of DI water	7.1 to 7.6	7.37
Ammonia Concentration of a diluted pillow	0.57 to 0.79 ppm	0.593 ppm
Iron Concentration of a diluted pillow	0.27 to 0.36 ppm	0.311 ppm
Sterility	To Pass	Passed
Phosphorus Concentration of a diluted pillow	7.6 to 10.3 ppm	8.32 ppm
Five Day Change in Dissolved Oxygen Concentration	-0.2 to 0.2 ppm	0.03 ppm

The expiration date is Jun 2029

Certified by: Scottals

1490 Lammers Pike Batesville, IN 47006 http://www.riccachemical.com 1-888-GO-RICCA

customerservice@riccachemical.com

# Certificate of Analysis

Starch Indicator, 0.5% (w/v), Mercury Free, for Iodometric Titrations

Lot Number: 4408P62 Product Number: 8000 Manufacture Date: AUG 28, 2024

Expiration Date: AUG 2026

This product is Mercury-free.

Name	CAS#	Grade	
Water	7732-18-5	ACS/ASTM/USP/EP	
Starch, soluble	9005-84-9	ACS	
Salicylic Acid	69-72-7	ACS	

Test	Specification	Result
Appearance	White translucent liquid	Passed
Suitability for Use	Colorless (Iodine absent) - Blue	Passed
	(Iodine present)	


Specification	Reference
Starch Solution	APHA (4500-S2- F)
Starch Indicator Solution	APHA (4500-Cl B)
Starch Indicator	APHA (4500-SO32- B)
Starch indicator solution	APHA (2350 B)
Starch indicator solution	APHA (2350 E)
Starch Solution	APHA (510 B)
Starch Solution	APHA (5530 C)
Starch Indicator	APHA (4500-C1 C)
Starch Indicator	EPA (345.1)

Volumetric glassware complies with Class A tolerance requirements of ASTM E 288 and NIST Circular 434; it is calibrated before first use and recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated regularly with a thermometer traceable to NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batch records document raw material traceability and production and testing history for each lot manufactured.

Part Number	Size / Package Type	Shelf Life (Unopened Container)
8000-1	4 L natural poly	24 months
8000-16	500 mL natural poly	24 months
8000-32	1 L natural poly	24 months

Recommended Storage: 15°C - 30°C (59°F - 86°F)

Version: 1.3 Lot Number: 4408P62 Product Number: 8000 Page 1 of 2



This test report shall not be reproduced, except in full, without the written approval of Ricca Chemical Company.

Version: 1.3 Lot Number: 4408P62 Product Number: 8000 Page 2 of 2

1841 Broad Street Pocomoke City, MD 21851 http://www.riccachemical.com 1-888-GO-RICCA

customerservice@riccachemical.com

## Certificate of Analysis

Buffer, Reference Standard, pH  $2.00 \pm 0.01$  at 25°C

Lot Number: 2411E26 Product Number: 1493

Manufacture Date: NOV 11, 2024

Expiration Date: OCT 2026

The certified value for this product is confirmed in independent testing by a second qualified chemist.

The NIST traceable pH value is certified to ±0.01 at 25 °C only. All other pH values at their corresponding temperatures are accurate to ±0.05.

25 30 35 40 45 50 1.93 1.98 1.98 2.00 2.01 2.03 2.03 2.04 2.04 pН

Name	CAS#	Grade
Water	7732-18-5	ACS/ASTM/USP/EP
Potassium Chloride	7447-40-7	ACS
Hydrochloric Acid	7647-01-0	ACS

	<u> </u>		
Appearance	Colorless liquid	Passed	*Not a certified value.
Test	Certified Value	Uncertainty	NIST SRM#
pH at 25°C (Method: SQCP027, SQCP033)	1.994	0.02	185i, 186-I-g, 186-II-g

Specification


Result

pH measurements were performed in our Pocomoke City, MD laboratory under ISO/IEC 17025 accreditation (ANAB Certificate L2387.01) and are certified traceable to National Institute of Standards and Technology (NIST) Standard Reference Material as indicated above via an unbroken chain of comparisons. The uncertainty is calculated from the uncertainty of the measurement variation from sample to sample, the uncertainty in the NIST Standard Reference Material, and the uncertainty of the measurement process. The uncertainty is multiplied by k=2, corresponding to 95% coverage in a normal distribution. Volumetric glassware complies with Class A tolerance requirements of ASTM E 288 and NIST Circular 434; it is calibrated before first use and recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated regularly with a thermometer traceable to NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batch records document raw material traceability and production and testing history for each lot manufactured.

Part Number	Size / Package Type	Shelf Life (Unopened Container)
1493-1	4 L natural poly	24 months
1493-16	500 mL natural poly	24 months
1493-1CT	4 L Cubitainer®	24 months
1493-2.5	10 L Cubitainer®	24 months
1493-32	1 L natural poly	24 months

Recommended Storage: 15°C - 30°C (59°F - 86°F)


Version: 1.3 Lot Number: 2411E26 Product Number: 1493 Page 1 of 2



### This product was tested in an ISO 17025 Accredited Laboratory

This test report shall not be reproduced, except in full, without the written approval of Ricca Chemical Company.

Version: 1.3 Lot Number: 2411E26 Product Number: 1493 Page 2 of 2



1841 Broad Street Pocomoke City, MD 21851 http://www.riccachemical.com 1-888-GO-RICCA

customerservice@riccachemical.com

# Certificate of Analysis

Buffer, Reference Standard, pH  $4.00 \pm 0.01$  at 25°C (Color Coded Red)

Lot Number: 2411A93

Name

Product Number: 1501

Manufacture Date: NOV 04, 2024

Expiration Date: OCT 2026

The certified value for this product is confirmed in independent testing by a second qualified chemist.

The NIST Traceable pH value is certified to  $\pm 0.01$  at 25 °C only. All other pH values at their corresponding temperatures are accurate to  $\pm 0.05$ .

5 10 15 20 25 30 35 45 pH 50 4.00 4.00 4.00 4.00 4.004.00 4.01 4.02 4.03 4.04 4.06

	CAS#	Grade	是 (1) E 第二
Water	7732-18-5	ACS/ASTM/USP/I	PD
Potassium Acid Phthalate	877-24-7	Buffer	
Preservative Red Dye	Proprietary	Commercial	
ned Dye	Proprietary	Purified	
Test	Specification	Result	
Appearance	Red liquid	Passed	
Test			*Not a certified val
pH at 25°C (Method: SQCP027, SQCP033)	Certified Value	Uncertainty	NIST SRM#
	4.008	0.02	185i, 186-I-g, 186-II-g
Specification	STATE OF THE PARTY		

Specification	10 Table 2000
Commonist D. co. G.	Reference
D., CC D	ASTM (D 1293 B) ASTM (D 5464)
Buffer B	ASTM (D 5464) ASTM (D 5128)
DH measurements were and	ASTM (D 5128)

pH measurements were performed in our Pocomoke City, MD laboratory under ISO/IEC 17025 accreditation (ANAB Certificate L2387.01) and are certified traceable to National Institute of Standards and Technology (NIST) Standard Reference Material as indicated above via an unbroken chain of comparisons. The uncertainty is calculated from the uncertainty of the measurement variation from sample to sample, the uncertainty in the NIST Standard Reference Material, and the uncertainty of the measurement process. The uncertainty is multiplied by k=2, corresponding to 95% coverage in a normal distribution. Volumetric glassware complies with Class A tolerance requirements of ASTM E 288 and NIST Circular 434; it is calibrated before first use and recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated regularly with a thermometer traceable to NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batcl: records document raw material traceability and production and testing

Part Number	Size / Package Type	Shelf Life (Unopened Container)
1501-16 1501-2.5	500 mL natural poly 10 L Cubitainer®	24 months
1501-5 Recommended Storage: 15°C - 30	20 L Cubitainer®	24 months 24 months



300 Technology Drive Christiansburg, VA 24073 USA inorganicventures.com

P: 800-669-6799/540-585-3030 F: 540-585-3012 info@inorganicventures.com

#### 1.0 **ACCREDITATION / REGISTRATION**

INORGANIC VENTURES is accredited to ISO 17034, "General Requirements for the Competence of Reference Material Producers" and ISO/IEC 17025, "General Requirements for the Competence of Testing and Calibration Laboratories". Inorganic Ventures is also an ISO 9001 registered manufacturer (QSR Certificate Number QSR-1034).



#### 2.0 PRODUCT DESCRIPTION

Product Code: Multi Analyte Ion Chromatography Solution

Catalog Number: 300-CAL-A

Lot Number: V2-MEB742616

Matrix: H2O

Value / Analyte(s): 150 µg/mL ea:

Sulfate,

100 µg/mL ea: Bromide. 50 µg/mL ea:

o-Phosphate as P, 30 µg/mL ea:

Chloride, Nitrite as N,

25 µg/mL ea: Nitrate as N, 20 µg/mL ea: Fluoride

#### 3.0 **CERTIFIED VALUES AND UNCERTAINTIES**

**ANALYTE CERTIFIED VALUE CERTIFIED VALUE ANALYTE** 100.0 ± 0.5 μg/mL 30.01 ± 0.13 µg/mL Bromide, Br

Chloride, Cl

20.00 ± 0.07 µg/mL 25.00 ± 0.10 µg/mL Fluoride, F-Nitrate as N, NNO3-

30.00 ± 0.10 μg/mL 50.00 ± 0.18 μg/mL Nitrite as N, NNO2o-Phosphate as P, PPO4

Sulfate, SO4 150.0 ± 0.8 µg/mL

0.999 g/mL (measured at 20 ± 4 °C) Density:

**Assay Information:** 

METHOD	NIST SRM#	SRM LOT#
IC Assay	3184	151130
Fajans	999c	999c
IC Assay	3182	190830
Fajans	999c	999c
IC Assay	3183	140203
IC Assay	3185	170309
IC Assay	Traceable to 40H	08228TH-H2
Calculated	40h	40h
IC Assay	3186	170606
IC Assay	3181	080603
	IC Assay Fajans IC Assay Fajans IC Assay IC Assay IC Assay IC Assay Calculated IC Assay	IC Assay     3184       Fajans     999c       IC Assay     3182       Fajans     999c       IC Assay     3183       IC Assay     3185       IC Assay     Traceable to 40H       Calculated     40h       IC Assay     3186

- The Calculated Value is a value calculated from the weight of a starting material that has been certified directly vs. a National Institute of Standards and Technology (NIST) SRM/RM. See Sec 4.2 for balance traceability.

The following equations are used in the calculation of the certified value and the uncertainty. Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of k = 2.

Characterization of CRM/RM by Two or More Methods	Characterization of CRM/RM by One Method
Certified Value, $\mathbf{X}_{\text{CRM/RM}}$ , where two or more methods of characterization are used is the weighted mean of the results:	Certified Value, X <sub>CRM/RM</sub> , where one method of characterization is used is the mean of individual results:
$X_{CRM/RM} = \Sigma(w_i) (X_i)$	$X_{CRM/RM} = (X_a) (u_{char} a)$
X <sub>i</sub> = mean of Assay Method i with standard uncertainty u <sub>char i</sub>	X <sub>a</sub> = mean of Assay Method A with
$\mathbf{w_i}$ = the weighting factors for each method calculated using the inverse square of the variance:	uchar a = the standard uncertainty of characterization Method A
$\mathbf{w_i} = (1/u_{\text{char }i})^2 / (\Sigma(1/(u_{\text{char }i})^2)$	
CRM/RM Expanded Uncertainty (±) = $U_{CRM/RM} = k (u^2_{char} + u^2_{bb} + u^2_{lts} + u^2_{ts})^{1/2}$	CRM/RM Expanded Uncertainty (±) = $U_{CRM/RM}$ = k ( $u_{char}^2$ a + $u_{bb}^2$ + $u_{lts}^2$ + $u_{ts}^2$ ) $v_{ts}^2$
k = coverage factor = 2	k = coverage factor = 2
$u_{char} = [\Sigma((w_i)^2 (u_{char})^2)]^{1/2}$ where $u_{char}$ are the errors from each characterization method	u <sub>char a</sub> = the errors from characterization
u <sub>bb</sub> = bottle to bottle homogeneity standard uncertainty	u <sub>bb</sub> = bottle to bottle homogeneity standard uncertainty
u <sub>lts</sub> = long term stability standard uncertainty (storage)	u <sub>lts</sub> = long term stability standard uncertainty (storage)
u <sub>ts</sub> = transport stability standard uncertainty	u <sub>ts</sub> = transport stability standard uncertainty

#### 4.0 TRACEABILITY TO NIST

- This product is traceable to NIST via an unbroken chain of comparisons. The uncertainties for each certified value are reported, taking into account the SRM/RM uncertainty error and the measurement, weighing and volume dilution errors. In rare cases where no NIST SRM/RM are available, the term 'in-house std.' is specified.

#### 4.1 Thermometer Calibration

- All thermometers are NIST traceable through thermometers that are calibrated by an accredited calibration laboratory.

#### 4.2 Balance Calibration

- All analytical balances are calibrated by an accredited calibration laboratory and procedure. The weights used for testing are annually compared to master weights and are traceable to NIST.

#### 4.3 Glassware Calibration

- An in-house procedure is used to calibrate all Class A glassware used in the manufacturing and quality control of CRM/RMs.

#### 5.0 CHROMATOGRAM

N/A

#### 6.0 INTENDED USE

**6.1** This standard is intended for the calibration of analytical instruments and validation of analytical methods as appropriate. This CRM may be used in connection with EPA Methods 6010, 6020 (all versions), Standard Methods 3120 B and USP <232> / ICH Q3D.

**6.2** For products attaining traceability through Inorganic Ventures' Primary Certified Reference Materials (PCRM™) see the Limited License to Use PCRM™ in the Inorganic Ventures <u>Terms and Conditions of Sale</u>, <a href="https://www.inorganicventures.com/terms-and-conditions-sale">https://www.inorganicventures.com/terms-and-conditions-sale</a>. The Terms and Conditions contain information on the use of materials traceable to PCRM™ certified reference materials. This Limited License agreement is especially pertinent for laboratories accredited under ISO:17034.

#### 7.0 INSTRUCTIONS FOR THE CORRECT USE OF THIS REFERENCE MATERIAL

#### 7.1 Storage and Handling Recommendations

- Store between approximately 4° 30° C while in sealed TCT bag.
- While stored in the sealed TCT bag, transpiration of this CRM/RM is negligible. After opening the sealed TCT bag transpiration of the CRM/RM will occur, resulting in a gradual increase in the analyte concentration(s). It is the responsibility of the user to account for this effect. When the bottle is weighed both before and after being placed in storage, the mass difference observed will be a measure of transpiration mass loss.
- After opening the sealed TCT bag, keep cap tightly sealed when not in use and store between  $4^{\circ}$   $24^{\circ}$  C to minimize the effects of transpiration. Use at  $20^{\circ} \pm 4^{\circ}$  C to minimize volumetric dilution error when using the reported density. Do not pipette from the container. Do not return removed aliquots to container.
- For more information, visit <a href="https://www.inorganicventures.com/TCT">www.inorganicventures.com/TCT</a>

#### 8.0 HAZARDOUS INFORMATION

- Please refer to the Safety Data Sheet for information regarding this CRM/RM.

#### 9.0 HOMOGENEITY

- This solution was mixed according to an in-house procedure and is guaranteed to be homogeneous. Homogeneity data indicate that the end user should take a minimum sample size of 0.2 mL to assure homogeneity.

#### 10.0 QUALITY STANDARD DOCUMENTATION

#### 10.1 ISO 9001 Quality Management System Registration

- QSR Certificate Number QSR-1034

#### 10.2 ISO/IEC 17025 "General Requirements for the Competence of Testing and Calibration Laboratories"

- Chemical Testing - Accredited / A2LA Certificate Number 883.01

#### 10.3 ISO 17034 "General Requirements for the Competence of Reference Material Producers"

- Reference Material Producer - Accredited / A2LA Certificate Number 883.02

Inorganic Ventures, 300 Technology Drive, Christiansburg, Va. 24073, USA; Telephone: 800.669.6799; 540.585.3030, Fax: 540.585.3012; inorganicventures.com; info@inorganicventures.com

#### 11.0 CERTIFICATION, LOT EXPIRATION AND PERIOD OF VALIDITY

#### 11.1 Certification Issue Date

April 02, 2024

- The certification is valid within the measurement uncertainty specified provided the CRM/RM is stored and handled in accordance with instructions given in Sec 7.1. This certification is nullified if instructions in Sec 7.1 are not followed or if the CRM/RM is damaged, contaminated, or otherwise modified.

#### 11.2 Lot Expiration Date

- April 02, 2029
- The date after which this CRM/RM should not be used.
- The lot expiration date reflects the period of time that the stability of a CRM/RM can be supported by long term stability studies conducted on properly stored and handled CRM/RMs. Lot expiration is limited primarily by transpiration (loss of water from the solution) and infrequently by chemical stability.

#### 11.3 Period of Validity

- Sealed TCT Bag Open Date: \_\_
- This CRM/RM should not be used longer than one year (or six months in the case of a 30 mL bottle) from the date of opening the aluminized bag or after the date given in Sec. 11.2, whichever comes first. This is contingent upon the CRM/RM being stored and handled in accordance with the instructions given in Sec. 7.1.

#### 12.0 NAMES AND SIGNATURES OF CERTIFYING OFFICERS Certificate Prepared By:

**Uyen Truong Custom Processing Supervisor** 

#### Certificate Approved By:

Thomas Kozikowski Stock VS Manager

Paul R Laine

#### **Certifying Officer:**

Paul Gaines Chairman / Senior Technical Director



# RICCA CHEMICAL COMPANY 33191

1841 Broad Street Pocomoke City, MD 21851 http://www.riccachemical.com

1-888-GO-RICCA customerservice@riccachemical.com

Certificate of Analysis

Buffer, Reference Standard, pH  $10.00 \pm 0.01$  at 25°C (Color Coded Blue)

Lot Number: 2410F80

Product Number: 1601

Manufacture Date: OCT 09, 2024

Expiration Date: MAR 2026

The certified value for this product is confirmed in independent testing by a second qualified chemist.

The NIST traceable pH value is certified to  $\pm 0.01$  at 25 °C only. All other pH values at their corresponding temperatures are accurate to  $\pm 0.05$ .

20 25 30 pН 35 10.31 10.23 40 50 10.1710.11 10.05 10.00 9.95 9.91 9.87 9.81

Name	CAS#		
Water		Grade	
Sodium Carbonate	7732-18-5	ACS/ASTM/USP/EP	
Sodium Ricarhamat	497-19-8	ACS	
Sodium Hydroxide	144-55-8	ACS	
Preservative	1310-73-2	Reagent	
Blue Dyo	Proprietary		
Cest	Proprietary	11-12-2 11 AT 1-11-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1	Service and a service
Γest			El Mariano de

Appearance	Specification	Result	
Test	Blue liquid	Passed	*Not a certified value
	Certified Value	Uncertainty	
pH at 25°C (Method: SQCP027, SQCP033)  Specification	10.009	0.00	186-I-g, 186-II-g, 191d

Specification	186-I-g, 186-II-g, 191d	
Commorain D. Co. C. J.	Reference	
Buffer C	ASTM (D 1293 B)	
Buffer C	ASTM (D 54CA)	0 × 20 1 0 30 010 1000
pH measurements were performed in our Pocomoke City, MD laboratory us		
cortified the delivered in our Pocomoke City, MD laboratory us	adou ICO TEO	**************************************


pH measurements were performed in our Pocomoke City, MD laboratory under ISO/IEC 17025 accreditation (ANAB Certificate L2387.01) and are certified traceable to National Institute of Standards and Technology (NIST) Standard Reference Material as indicated above via an unbroken chain of comparisons. The uncertainty is calculated from the uncertainty of the measurement variation from sample to sample, the uncertainty in the NIST Standard Reference Material, and the uncertainty of the measurement process. The uncertainty is multiplied by k=2, corresponding to 95% coverage in a normal distribution. Volumetric glassware complies with Class A tolerance requirements of ASTM E 288 and NIST Circular 434; it is calibrated before first use and recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated regularly with a thermometer traceable to NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batch records document raw material traceability and production and testing

Part Number		and production and testing	
1601-1	Size / Package Type	Shalf Life (II.	
1601-16	4 L natural poly 500 mL natural poly	Shelf Life (Unopened Container) 18 months	
1601-16 1601-1CT	500 mL natural poly 4 L Cubitainer®	18 months	
2.0	4 L Cubitainer® 10 L Cubitainer®	18 months	
	1 L natural poly	18 months	
	1 L natural poly 20 L Cubitainer®	18 months	
ersion: 1.3	Lot Number: 2410F80	18 months	

Lot Number: 2410F80

Product Number: 1601

Page 1 of 2





03/19/2025(JST)

TOKYO CHEMICAL INDUSTRY CO.,LTD.
T-PLUS Nihonbashi-Kodemmacho
16-12 Nihonbashi-kodemmacho, Chuo-ku, Tokyo 103-0001, Japan

Chemical Name: p-Xylene				
Product Number: X0014 CAS RN: 106-42-3	Lot: C6PEN			

Tests	Results	Specifications
Appearance	Colorless clear liquid	Colorless to Almost colorless clear liquid
Purity(GC)	99.7 %	min. 99.0 %

TCI Lot numbers are 4-5 characters in length. Characters listed after the first 4-5 characters are control numbers for internal purpose only.

The contents of the specifications are subject to change without advance notice. The specification values displayed here are the most up to date values. There may be cases where the product labels display a different specification, however, the product quality still meets the latest specification.

#### **Customer Service:**

TCI AMERICA

Tel: +1-800-423-8616 / +1-503-283-1681 Fax: +1-888-520-1075 / +1-503-283-1987 E-mail: Sales-US@TCIchemicals.com

Takuya Nishioka

Quality Assurance Department Manager

Tahun Mikich