

284 Sheffield Street, Mountainside, New Jersey 07092, Phone: 908 789

8900, Fax: 908 789 8922

# **Prep Standard - Chemical Standard Summary**

Order ID: Q2264	

Test: Mercury, Metals Group3

Prepbatch ID: PB168402,PB168444,

Sequence ID/Qc Batch ID: LB136099,LB136187,LB136187,

Standard ID: MP85156,MP85935,MP85936,MP85937,MP85938,MP85940,MP85941,MP85943,MP85944,MP85945,MI	
47,MP85948,MP85949,MP85950,MP85952,	-00940,IVIP009
Observiced ID	
Chemical ID: M5062,M5882,M6007,M6016,M6151,M6158,M6161,M6162,W3112,	





Fax: 908 789 8922

# Metals STANDARD PREPARATION LOG

Recipe ID	<u>NAME</u>	<u>NO.</u>	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipetteID</u>	Supervised By Sarabjit Jaswal
170	1:1HCL	MP85156	04/07/2025	08/18/2025	Kareem Khairalla	None	None	04/07/2025

Recipe ID	NAME_	NO.	Prep Date	Expiration Date	<u>Prepared</u> <u>By</u>	<u>ScaleID</u>	<u>PipetteID</u>	Supervised By Sarabjit Jaswal
871	MERCURY INTERMEDIATE B 250PPB WORKING STD.	MP85935	06/11/2025	06/12/2025	Mohan Bera		METALS_PIP ETTE_5 (HG	

FROM 1.00000ml of M6162 + 2.50000ml of M5062 + 96.50000ml of W3112 = Final Quantity: 100.000 ml





Fax: 908 789 8922

# **Metals STANDARD PREPARATION LOG**

Recipe ID	NAME_	NO.	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipettelD</u>	Supervised By Sarabjit Jaswal
1340	Hg 0.00 PPB STD	MP85936	06/11/2025	06/12/2025	Mohan Bera		METALS_PIP ETTE_5 (HG	
	0.50000   1.110400   0.47.50000	514/0440			•		A)	

**FROM** 2.50000ml of M6162 + 247.50000ml of W3112 = Final Quantity: 250.000 ml

Recipe ID	NAME	<u>NO.</u>	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipettelD</u>	Supervised By Sarabjit Jaswal
2750	Нд 0.05ррb	MP85937	06/11/2025	06/12/2025	Mohan Bera		METALS_PIP ETTE_5 (HG	•

FROM 2.50000ml of M6162 + 247.45000ml of W3112 + 0.05000ml of MP85935 = Final Quantity: 250.000 ml





# **Metals STANDARD PREPARATION LOG**

Recipe ID	NAME	NO.	Prep Date	Expiration Date	Prepared By	ScaleID	PipetteID	Supervised By		
1341	Hg 0.2 PPB STD		06/11/2025	06/12/2025	Mohan Bera	None	METALS_PIP ETTE_5 (HG			
EPOM 2 50000ml of M6162 + 247 30000ml of W3112 + 0 20000ml of MP85935 = Final Quantity: 250 000 ml										

<u>FROM</u>	2.50000ml of M6162 + $247.30000$ ml of W3112 + $0.20000$ ml of MP85935	= Final Quantity: 250.000	mI
-------------	--	---------------------------	----

Recipe				Expiration	Prepared			Supervised By
<u>ID</u>	<u>NAME</u>	<u>NO.</u>	Prep Date	<u>Date</u>	<u>By</u>	<u>ScaleID</u>	<u>PipetteID</u>	Sarabjit Jaswal
1342	Hg 2.5 PPB STD	MP85940	06/11/2025	06/12/2025	Mohan Bera		METALS_PIP	
							ETTE_5 (HG	06/14/2025

FROM 2.50000ml of M6162 + 245.0000ml of W3112 + 2.50000ml of MP85935 = Final Quantity: 250.000 ml





Fax: 908 789 8922

# **Metals STANDARD PREPARATION LOG**

Recipe ID	<u>NAME</u>	NO.	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipetteID</u>	Supervised By Sarabjit Jaswal			
1343	Hg 5.0 PPB STD	MP85941	06/11/2025	06/12/2025	Mohan Bera	None	METALS_PIP ETTE_5 (HG				
	A)										

**FROM** 2.50000ml of M6162 + 242.50000ml of W3112 + 5.00000ml of MP85935 = Final Quantity: 250.000 ml

Recipe ID	<u>NAME</u>	NO.	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipetteID</u>	Supervised By Sarabjit Jaswal
1344	Hg 7.5 PPB STD	MP85943	06/11/2025	06/12/2025	Mohan Bera		METALS_PIP ETTE_5 (HG	,

**FROM** 2.50000ml of M6162 + 240.00000ml of W3112 + 7.50000ml of MP85935 = Final Quantity: 250.000 ml



284 Sheffield Street, Mountainside, New Jersey 07092, Phone: 908 789 8900,

Fax: 908 789 8922

# **Metals STANDARD PREPARATION LOG**

Recipe ID	NAME_	NO.	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipetteID</u>	Supervised By Sarabjit Jaswal
1345	Hg 10.0 PPB STD	MP85944	06/11/2025	06/12/2025	Mohan Bera		METALS_PIP ETTE_5 (HG	
							A)	

Recipe				Expiration	Prepared			Supervised By
<u>ID</u>	<u>NAME</u>	<u>NO.</u>	Prep Date	<u>Date</u>	<u>By</u>	<u>ScaleID</u>	<u>PipetteID</u>	Sarabjit Jaswal
1346	Hg ICV SOLUTION	MP85945	06/11/2025	06/12/2025	Mohan Bera		METALS_PIP	
							ETTE_5 (HG	06/14/2025

FROM 2.50000ml of M6161 + 2.50000ml of M6162 + 245.00000ml of W3112 = Final Quantity: 250.000 ml



 $284 \; Sheffield \; Street, \; Mountainside, \; New \; Jersey \; 07092, \; Phone: \; 908 \; 789 \; 8900, \\$ 

Fax: 908 789 8922

# **Metals STANDARD PREPARATION LOG**

1351 ICB (Hg 0.00 PPB SOLUTION) MP85946 06/11/2025 06/12/2025 Mohan Bera None METALS_PIP ETTE_5 (HG 06/14/2025	Recipo ID	NAME	NO.	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipettelD</u>	Supervised By Sarabjit Jaswal
	1351	ICB (Hg 0.00 PPB SOLUTION)	MP85946	06/11/2025	06/12/2025	Mohan Bera	None	_	,

**FROM** 2.50000ml of M6162 + 247.50000ml of W3112 = Final Quantity: 250.000 ml

Recipe ID	NAME	NO.	Prep Date	Expiration Date	Prepared By	ScaleID	<u>PipetteID</u>	Supervised By
1358	CCV (Hg 5.0 PPB SOLUTION)		06/11/2025	06/12/2025	Mohan Bera		METALS_PIP ETTE_5 (HG	

FROM 485.00000ml of W3112 + 5.00000ml of M6162 + 10.00000ml of MP85935 = Final Quantity: 500.000 ml



284 Sheffield Street, Mountainside, New Jersey 07092, Phone: 908 789 8900,

Fax: 908 789 8922

# **Metals STANDARD PREPARATION LOG**

Recipe ID	NAME	NO.	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipetteID</u>	Supervised By Sarabjit Jaswal
1352	CCB (Hg 0.00 PPB SOLUTION)	MP85948	06/11/2025	06/12/2025	Mohan Bera		METALS_PIP ETTE_5 (HG	
							A)	

**FROM** 495.00000ml of W3112 + 5.00000ml of M6162 = Final Quantity: 500.000 ml

Recipe ID	<u>NAME</u>	NO.	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipettelD</u>	Supervised By Sarabjit Jaswal
1349	CRA/CRI (Hg 0.2 PPB SOLUTION)	MP85949	06/11/2025	06/12/2025	Mohan Bera		METALS_PIP ETTE_5 (HG	

**FROM** 2.50000ml of M6162 + 247.30000ml of W3112 + 0.20000ml of MP85935 = Final Quantity: 250.000 ml



284 Sheffield Street, Mountainside, New Jersey 07092, Phone: 908 789 8900,

Fax: 908 789 8922

# **Metals STANDARD PREPARATION LOG**

Recipe ID	NAME_	NO.	Prep Date	Expiration Date	Prepared By	<u>ScaleID</u>	<u>PipetteID</u>	Supervised By Sarabjit Jaswal
1350	CHK STD (Hg 7.0 PPB SOLUTION)	MP85950	06/11/2025	06/12/2025	Mohan Bera		METALS_PIP ETTE_5 (HG	
							A)	

**FROM** 2.50000ml of M6162 + 240.50000ml of W3112 + 7.00000ml of MP85935 = Final Quantity: 250.000 ml

Recipe ID	NAME	NO.	Prep Date	Expiration Date	<u>Prepared</u> <u>By</u>	<u>ScaleID</u>	<u>PipetteID</u>	Supervised By Sarabjit Jaswal
68	STANNOUS CHLORIDE SOLUTION	MP85952	06/11/2025	06/12/2025		METALS_SCA LE_3 (M SC-3)		06/14/2025

FROM 450.00000ml of W3112 + 50.00000gram of M5882 + 50.00000ml of M6151 = Final Quantity: 500.000 ml



# **CHEMICAL RECEIPT LOG BOOK**

Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
Inorganic Ventures	MSHG-10PPM / MERCURY HCI 125mL 10ug/mL	S2-HG709270	09/22/2026	05/28/2022 / mohan	01/27/2022 / mohan	M5062
Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
Seidler Chemical	BA-3980-01 / Stannous Chloride (cs/4x500g)	232820	08/31/2028	04/30/2024 / mohan	04/25/2024 / mohan	M5882
Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
Inorganic Ventures	WW-LFS-1 / Laboratory Fortified Stock Solution 1, 125 ml	T2-MEB723367	05/27/2026	05/27/2025 / Janvi	05/14/2024 / Jaswal	M6007
Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
Inorgania	MANALEC 2 / Laboratory	U2-MEB731108	40/00/0005	0.4/0.0/0.05	05/14/2024 /	
Inorganic Ventures	WW-LFS-2 / Laboratory Fortified Stock Solution 2, 125 ml	02-MED/31100	10/30/2025	04/30/2025 / mohan	Jaswal	M6016
_	Fortified Stock Solution 2,	Lot #	Expiration Date			M6016  Chemtech Lot #
Ventures	Fortified Stock Solution 2, 125 ml		Expiration	mohan  Date Opened /	Jaswal  Received Date /	Chemtech
Ventures  Supplier	Fortified Stock Solution 2, 125 ml  ItemCode / ItemName  BA-9530-33 / Hydrochloric Acid, Instra-Analyzed	Lot #	Expiration Date	Date Opened / Opened By	Jaswal  Received Date / Received By  01/15/2025 /	Chemtech Lot #



Fax: 908 789 8922


# **CHEMICAL RECEIPT LOG BOOK**

Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
EPA	ICV-5 / ICV (HG)STOCK SOLN	ICV 5 0415	07/31/2025	05/01/2025 / mohan	03/30/2024 / mohan	M6161

Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
Seidler Chemical	BA-9598-34 / Nitric Acid, Instra-Analyzed (cs/4x2.5L)	24H0162012	11/27/2025	05/27/2025 / Sagar	04/27/2025 / Sagar	M6162

Supplier	ItemCode / ItemName	Lot #	Expiration Date	Date Opened / Opened By	Received Date / Received By	Chemtech Lot #
Seidler Chemical	DIW / DI Water	Daily Lab-Certified	07/03/2029	07/03/2024 / lwona	07/03/2024 / Iwona	W3112





1 Reagent Lane Fair Lawn, NJ 07410 201,796,7100 tel

Thermo Fisher Scientific's Quality System has been found to conform to Quality Management System

Standard ISO9001:2015 by SAI Global Certificate Number CERT - 0120633 201,796,1329 fax

This is to certify that units of the lot number below were tested and found to comply with the specifications of the grade listed. Certain data have been supplied by third parties. Thermo Fisher Scientific expressly disclaims all warranties, expressed or implied, including the implied warranties of merchantability and fitness for a particular purpose. Products are for research use or further manufacturing. Not for direct administration to humans or animals. It is the responsibility of the final formulator and end user to determine suitability based upon the intended use of the end product. Products are tested to meet the analytical requirements of the noted grade. The following information is the actual analytical results obtained.

Catalog Number	T142	Quality Test / Release Date	08/17/2023
Lot Number	232820		
Description	STANNOUS CHLORIDE, DIHYDR	ATE CERTIFIED ACS (Suitable for Me	rcury Determination)
Country of Origin	United States	Suggested Retest Date	Aug/2028
Chemical Origin	Inorganic-non animal		
BSE/TSE Comment	No animal products are used as starting raw material ingredients, or used in processing, including lubricants, processing aids, or any other material that might migrate to the finished product.		

N/A				
Result Name	Units	Specifications	Test Value	
APPEARANCE		REPORT	Clear crystals	
ASSAY	%	Inclusive Between 98 - 103	100.65	
CALCIUM	%	<= 0.005	0.0017	
IDENTIFICATION	PASS/FAIL	= PASS TEST	PASS TEST	
IRON (Fe)	%	<= 0.003	0.0011	
LEAD (Pb)	%	<= 0.01	0.0006	
MERCURY (Hg)	ppm	<= 0.05	<0.05	
POTASSIUM (K)	%	<= 0.005	0.0001	
SODIUM (Na)	%	<= 0.01	<0.01	
SOLUBILITY IN HCL	PASS/FAIL	= PASS TEST	PASS TEST	
SULFATE (SO4)	PASS/FAIL	= P.T. (ABOUT 0.003%)	P.T. (ABOUT 0.003%)	

Harout Sahagian - Quality Control Supervisor - Fair Lawn

## M6000,M6001,M6002,M6003,M6004,M6005,M6006,M6007,M6008



# **Certificate of Analysis**

Refine your results. Redefine your industry. RD:05/14/2024

300 Technology Drive Christiansburg, VA 24073 USA inorganicventures.com P: 800-669-6799/540-585-3030 F: 540-585-3012 info@inorganicventures.com

#### 1.0 ACCREDITATION / REGISTRATION

**INORGANIC VENTURES** is accredited to ISO 17034, "General Requirements for the Competence of Reference Material Producers" and ISO/IEC 17025, "General Requirements for the Competence of Testing and Calibration Laboratories". Inorganic Ventures is also an ISO 9001 registered manufacturer (QSR Certificate Number QSR-1034).



### 2.0 PRODUCT DESCRIPTION

**Product Code:** 

Multi Analyte Custom Grade Solution

Catalog Number:

WW-LFS-1

Lot Number:

T2-MEB723367

Matrix:

5% (v/v) HNO3

Value / Analyte(s):

1 000 μg/mL ea: Potassium, 600 μg/mL ea: Phosphorus, 300 μg/mL ea:

Iron,

200 μg/mL ea:

Sodium,

Magnesium, Aluminum, Cerium, Selenium,

Thallium,

100 μg/mL ea:

Lead, Calcium,

80 µg/mL ea: Arsenic, 70 µg/mL ea: Mercury, 50 µg/mL ea: Nickel,

40 μg/mL ea: Chromium,

30 μg/mL ea:

Copper, Boron,

Vanadium,

20 μg/mL ea:

Zinc, Strontium,
Barium, Beryllium,
Cadmium, Cobalt,
Manganese, Lithium,

7.5 µg/mL ea: Silver

## 3.0 CERTIFIED VALUES AND UNCERTAINTIES

ANALYTE Aluminum, Al	CERTIFIED VALUE 200.0 ± 0.7 µg/mL	ANALYTE Arsenic, As	CERTIFIED VALUE 80.0 ± 0.7 µg/mL
Barium, Ba	20.00 ± 0.09 μg/mL	Beryllium, Be	20.00 ± 0.13 μg/mL
Boron, B	30.00 ± 0.18 μg/mL	Cadmlum, Cd	20.00 ± 0.09 μg/mL
Calcium, Ca	100.0 ± 0.4 μg/mL	Cerium, Ce	200.0 ± 0.8 µg/mL
Chromium, Cr	40.00 ± 0.30 μg/mL	Cobalt, Co	20.00 ± 0.10 μg/mL
Copper, Cu	30.00 ± 0.13 μg/mL	Iron, Fe	300.0 ± 1.3 μg/mL
Lead, Pb	100.0 ± 0.4 μg/mL	Lithium, Li	20.00 ± 0.08 µg/mL
Magneslum, Mg	200.0 ± 0.8 μg/mL	Manganese, Mn	20.00 ± 0.08 µg/mL
Mercury, Hg	70.0 ± 0.3 µg/mL	Nickel, Ni	50.00 ± 0.22 μg/mL
Phosphorus, P	600.0 ± 2.7 μg/mL	Potassium, K	1 000 ± 4 µg/mL
Selenium, Se	200.0 ± 1.3 μg/mL	Silver, Ag	7.50 ± 0.03 µg/mL
Sodium, Na	300.0 ± 1.4 μg/mL	Strontium, Sr	20.01 ± 0.08 μg/mL
Thailium, Ti	200.0 ± 1.4 μg/mL	Vanadium, V	30.00 ± 0.13 μg/mL
Zinc, Zn	20.00 ± 0.09 μg/mL		

1.034 g/mL (measured at 20  $\pm$  4 °C) Density:

**Assay Information:** 

ANALYTE	METHOD	NIST SRM#	SRM LOT#
Ag	ICP Assay	3151	160729
Ag	Volhard	999c	999c
Ag	Calculated		See Sec. 4.2
Al	ICP Assay	3101a	140903
Al	EDTA	928	928
As	ICP Assay	3103a	100818
В	ICP Assay	3107	190605
Ва	ICP Assay	3104a	140909
Ва	Gravimetric		See Sec. 4.2
Ве	ICP Assay	3105a	090514
Ca	ICP Assay	3109a	130213
Ca	EDTA	928	928
Cd	ICP Assay	3108	130116
Cd	EDTA	928	928
Се	ICP Assay	3110	090504
Ce	EDTA	928	928
Co	ICP Assay	3113	190630
Со	EDTA	928	928
Cr	ICP Assay	3112a	170630
Cu	ICP Assay	3114	121207
Cu	EDTA	928	928
Fe	ICP Assay	3126a	140812
Fe	EDTA	928	928
Hg	ICP Assay	3133	160921
Hg	EDTA	928	928
K	ICP Assay	3141a	140813
K	Gravimetric		See Sec. 4.2
Li	ICP Assay	3129a	100714
Li	Gravimetric		See Sec. 4.2
Mg	ICP Assay	3131a	140110
Mg	EDTA	928	928
Mn	ICP Assay	3132	050429
Mn	EDTA	928	928
Na	ICP Assay	Traceable to 3152A	S2-NA700842
Na	Gravimetric		See Sec. 4.2
Ni	ICP Assay	3136	120619
Ni	EDTA	928	928
P	ICP Assay	3139a	060717
P	Acidimetric	84L	84L
Pb	ICP Assay	3128	101026
Pb	EDTA	928	928
Se	ICP Assay	3149	100901
Sr	EDTA	928	928
Sr	ICP Assay	Traceable to 3153a	K2-SR650985
TI	ICP Assay	3158	151215
V	IC Assay	3165	160906
V	EDTA	928	928
Zn	ICP Assay	3168a	120629
Zn	EDTA	928	928

Page 4 of 6

The following equations are used in the calculation of the certified value and the uncertainty. Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of k = 2.

#### Characterization of CRM/RM by Two or More Methods

Certified Value, X<sub>CRM/RM</sub>, where two or more methods of characterization are used is the weighted mean of the results:

 $X_{CRM/RM} = \Sigma(w_i) (X_i)$ 

 $X_i$  = mean of Assay Method i with standard uncertainty  $u_{char\ i}$ 

w<sub>i</sub> = the weighting factors for each method calculated using the inverse square of the variance:

 $w_i = (1/u_{char})^2 / (\Sigma(1/(u_{char})^2))$ 

CRM/RM Expanded Uncertainty (±) =  $U_{CRM/RM} = k \left\{ u^2_{char} + u^2_{bb} + u^2_{lts} + u^2_{ts} \right\}^{1/2}$ 

k = coverage factor = 2

 $u_{char} = [\Sigma((w_i)^2 (u_{char})^2)]^{1/2}$  where  $u_{char}$  is are the errors from each characterization method

ubb = bottle to bottle homogeneity standard uncertainty

ults = long term stability standard uncertainty (storage)

uts = transport stability standard uncertainty

#### Characterization of CRM/RM by One Method

Certified Value, X<sub>CRMRM</sub>, where one method of characterization is used is the mean of individual results:

 $X_{CRM/RM} = (X_a) (u_{char})$ 

X<sub>a</sub> = mean of Assay Method A with

uchar a = the standard uncertainty of characterization Method A

CRM/RM Expanded Uncertainty (±) =  $U_{CRM/RM} = k (u^2_{chara} + u^2_{bb} + u^2_{tts} + u^2_{ts})^{1/2}$ 

k = coverage factor = 2

uchar a = the errors from characterization

u<sub>bb</sub> = bottle to bottle homogeneity standard uncertainty

u<sub>lts</sub> = long term stability standard uncertainty (slorage) u<sub>ts</sub> = transport stability standard uncertainty

#### 4.0 TRACEABILITY TO NIST

- This product is traceable to NIST via an unbroken chain of comparisons. The uncertainties for each certified value are reported, taking into account the SRM/RM uncertainty error and the measurement, weighing and volume dilution errors. In rare cases where no NIST SRM/RM are available, the term 'in-house std.' is specified.

#### 4.1 Thermometer Calibration

- All thermometers are NIST traceable through thermometers that are calibrated by an accredited calibration laboratory.

#### 4.2 Balance Calibration

- All analytical balances are calibrated by an accredited calibration laboratory and procedure. The weights used for testing are annually compared to master weights and are traceable to NIST.

#### 4.3 Glassware Calibration

- An in-house procedure is used to calibrate all Class A glassware used in the manufacturing and quality control of CRM/RMs.

# 5.0 TRACE METALLIC IMPURITIES (TMI ) DETERMINED BY ICP-MS AND ICP-OES (µg/mL)

N/A

#### 6.0 INTENDED USE

- For the calibration of analytical instruments and validation of analytical methods as appropriate.

#### 7.0 INSTRUCTIONS FOR THE CORRECT USE OF THIS REFERENCE MATERIAL

### 7.1 Storage and Handling Recommendations

- Store between approximately 4° 30° C while in sealed TCT bag.
- While stored in the sealed TCT bag, transpiration of this CRM/RM is negligible. After opening the sealed TCT bag transpiration of the CRM/RM will occur, resulting in a gradual increase in the analyte concentration(s). It is the responsibility of the user to account for this effect. When the bottle is weighed both before and after being placed in storage, the mass difference observed will be a measure of transpiration mass loss.
- After opening the sealed TCT bag, keep cap tightly sealed when not in use and store between 4° 24° C to minimize the effects of transpiration. Use at 20° ± 4° C to minimize volumetric dilution error when using the reported density. Do not pipette from the container. Do not return removed aliquots to container.
- For more information, visit www.inorganicventures.com/TCT

Low Silver Note: This solution contains "LOW" levels of Silver. Please store this entire bottle inside a sealed glass jar.

#### 8.0 HAZARDOUS INFORMATION

Please refer to the Safety Data Sheet for information regarding this CRM/RM.

#### 9.0 HOMOGENEITY

- This solution was mixed according to an in-house procedure and is guaranteed to be homogeneous. Homogeneity data indicate that the end user should take a minimum sample size of 0.2 mL to assure homogeneity.

#### 10.0 QUALITY STANDARD DOCUMENTATION

#### 10.1 ISO 9001 Quality Management System Registration

- QSR Certificate Number QSR-1034

## 10.2 ISO/IEC 17025 "General Requirements for the Competence of Testing and Calibration Laboratories"

- Chemical Testing - Accredited / A2LA Certificate Number 883.01

#### 10.3 ISO 17034 "General Requirements for the Competence of Reference Material Producers"

- Reference Material Producer - Accredited / A2LA Certificate Number 883.02

Inorganic Ventures, 300 Technology Drive, Christiansburg, Va. 24073, USA; Telephone: 800.669.6799; 540.585.3030, Fax: 540.585.3012; inorganicventures.com; info@inorganicventures.com

#### 11.0 CERTIFICATION, LOT EXPIRATION AND PERIOD OF VALIDITY

#### 11.1 Certification Issue Date

August 30, 2022

- The certification is valid within the measurement uncertainty specified provided the CRM/RM is stored and handled in accordance with instructions given in Sec 7.1. This certification is nullified if instructions in Sec 7.1 are not followed or if the CRM/RM is damaged, contaminated, or otherwise modified.

#### 11.2 Lot Expiration Date

- August 30, 2026
- The date after which this CRM/RM should not be used.
- The lot expiration date reflects the period of time that the stability of a CRMRM can be supported by long term stability studies conducted on properly stored and handled CRMRMs. Lot expiration is limited primarily by transpiration (loss of water from the solution) and infrequently by chemical stability.

#### 11.3 Period of Validity

<ul> <li>Sealed TCT Bag Open Date</li> </ul>	
--	--

- This CRM/RM should not be used longer than one year (or six months in the case of a 30 mL bottle) from the date of opening the aluminized bag or after the date given in Sec. 11.2, whichever comes first. This is contingent upon the CRM/RM being stored and handled in accordance with the instructions given in Sec. 7.1.

### 12.0 NAMES AND SIGNATURES OF CERTIFYING OFFICERS

#### **Certificate Approved By:**

Thomas Kozikowski Manager, Quality Control

Certifying Officer:

**Paul Gaines** 

Chairman / Senior Technical Director

DD978hi.



# Certificate of Analysis

Refine your results. Redefine your industry. RD:05/14/2024

300 Technology Drive Christiansburg, VA 24073 USA inorganicventures.com

P: 800-669-6799/540-585-3030 F: 540-585-3012 info@inorganicventures.com

#### 1.0 **ACCREDITATION / REGISTRATION**

INORGANIC VENTURES is accredited to ISO 17034, "General Requirements for the Competence of Reference Material Producers" and ISO/IEC 17025, "General Requirements for the Competence of Testing and Calibration Laboratories". Inorganic Ventures is also an ISO 9001 registered manufacturer (QSR Certificate Number QSR-1034).



#### 2.0 PRODUCT DESCRIPTION

**Product Code:** 

Multi Analyte Custom Grade Solution

Catalog Number:

WW-LFS-2

Lot Number:

U2-MEB731108

Matrix:

5% (v/v) HNO3

tr. HF

Value / Analyte(s):

200 µg/mL ea:

Silica,

80 µg/mL ea: Antimony, 70 µg/mL ea:

Tin,

40 µg/mL ea: Molybdenum,

20 µg/mL ea: Titanium

#### 3.0 **CERTIFIED VALUES AND UNCERTAINTIES**

**ANALYTE** Antimony, Sb **CERTIFIED VALUE** 80.1 ± 0.6 µg/mL

**ANALYTE** Molybdenum, Mo **CERTIFIED VALUE** 40.03 ± 0.18 µg/mL

Silica, SIQ2

200.2 ± 1.3 μg/mL

Tin, Sn

 $70.0 \pm 0.4 \, \mu g/mL$ 

Titanium, Ti

20.01 ± 0.13 µg/mL

Density:

1.025 g/mL (measured at 20 ± 4 °C)

#### **Assay Information:**

ANALYTE Mo	METHOD ICP Assav	NIST SRM# 3134	SRM LOT# 130418
Мо	Calculated		See Sec. 4.2
Sb	ICP Assay	3102a	140911
SiO2	ICP Assay	3150	130912
Sn	ICP Assay	3161a	140917
П	ICP Assay	3162a	130925
Ti	Calculated		See Sec. 4.2

The following equations are used in the calculation of the certified value and the uncertainty. Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of k = 2.

#### Characterization of CRM/RM by Two or More Methods

Certified Value, X<sub>CRM/RM</sub>, where two or more methods of characterization are used is the weighted mean of the results:

 $X_{CRM/RM} = \Sigma(w_i) (X_i)$ 

X<sub>i</sub> = mean of Assay Method i with standard uncertainty u<sub>char i</sub>

 $\mathbf{w_i}$  = the weighting factors for each method calculated using the inverse square of the variance:

 $w_i = (1/u_{char i})^2 / (\Sigma (1/(u_{char i})^2))$ 

CRM/RM Expanded Uncertainty (±) =  $U_{CRM/RM} = k \left\{ u^2_{char} + u^2_{bb} + u^2_{lts} + u^2_{ts} \right\}^{\frac{1}{2}}$ 

k = coverage factor = 2

 $u_{char} = [\Sigma((w_i)^2 (u_{char})^2)]^{\frac{1}{2}}$  where  $u_{char}$  are the errors from each characterization method

ubb = bottle to bottle homogeneity standard uncertainty

u<sub>lts</sub> = long term stability standard uncertainty (storage)

uts = transport stability standard uncertainty

#### Characterization of CRM/RM by One Method

Certified Value, X<sub>CRM/RM</sub>, where one method of characterization is used is the mean of Individual results:

 $X_{CRM/RM} = (X_a) (u_{char e})$ 

X<sub>a</sub> = mean of Assay Method A with

u<sub>char a</sub> = the standard uncertainty of characterization Method A

CRM/RM Expanded Uncertainty (±) =  $U_{CRM/RM} = k \left(u^2_{char} + u^2_{bb} + u^2_{bs} + u^2_{ts}\right)^{1/2}$ 

k = coverage factor = 2

uchar a = the errors from characterization

ubb = bottle to bottle homogeneity standard uncertainty

ults = long term stability standard uncertainty (storage)

uts = transport stability standard uncertainty

#### 4.0 TRACEABILITY TO NIST

- This product is traceable to NIST via an unbroken chain of comparisons. The uncertainties for each certified value are reported, taking into account the SRM/RM uncertainty error and the measurement, weighing and volume dilution errors. In rare cases where no NIST SRM/RM are available, the term 'in-house std.' is specified.

#### 4.1 Thermometer Calibration

- All thermometers are NIST traceable through thermometers that are calibrated by an accredited calibration laboratory.

#### 4.2 Balance Calibration

- All analytical balances are calibrated by an accredited calibration laboratory and procedure. The weights used for testing are annually compared to master weights and are traceable to NIST.

#### 4.3 Glassware Calibration

- An in-house procedure is used to calibrate all Class A glassware used in the manufacturing and quality control of CRM/RMs.

#### 5.0 TRACE METALLIC IMPURITIES (TMI ) DETERMINED BY ICP-MS AND ICP-OES (µg/mL)

N/Δ

#### 6.0 INTENDED USE

- **6.1** This standard is intended for the calibration of analytical instruments and validation of analytical methods as appropriate. This CRM may be used in connection with EPA Methods 6010, 6020 (all versions), Standard Methods 3120 B and USP <232> / ICH Q3D.
- **6.2** For products attaining traceability through Inorganic Ventures' Primary Certified Reference Materials (PCRM™) see the Limited License to Use PCRM™ in the Inorganic Ventures <u>Terms and Conditions of Sale.</u> <a href="https://www.inorganicventures.com/terms-and-conditions-sale">https://www.inorganicventures.com/terms-and-conditions-sale</a>. The Terms and Conditions contain information on the use of materials traceable to PCRM™ certified reference materials. This Limited License agreement is especially pertinent for laboratories accredited under ISO:17034.

#### 7.0 INSTRUCTIONS FOR THE CORRECT USE OF THIS REFERENCE MATERIAL

#### 7.1 Storage and Handling Recommendations

- Store between approximately 4° 30° C while in sealed TCT bag.
- While stored in the sealed TCT bag, transpiration of this CRM/RM is negligible. After opening the sealed TCT bag transpiration of the CRM/RM will occur, resulting in a gradual increase in the analyte concentration(s). It is the responsibility of the user to account for this effect. When the bottle is weighed both before and after being placed in storage, the mass difference observed will be a measure of transpiration mass loss.
- After opening the sealed TCT bag, keep cap tightly sealed when not in use and store between  $4^{\circ}$   $24^{\circ}$  C to minimize the effects of transpiration. Use at  $20^{\circ} \pm 4^{\circ}$  C to minimize volumetric dilution error when using the reported density. Do not pipette from the container. Do not return removed aliquots to container.
- For more information, visit www.Inorganicventures.com/TCT HF Note: This standard should not be prepared or stored in glass.

### 8.0 HAZARDOUS INFORMATION

- Please refer to the Safety Data Sheet for information regarding this CRM/RM.

#### 9.0 HOMOGENEITY

This solution was mixed according to an in-house procedure and is guaranteed to be homogeneous.
 Homogeneity data indicate that the end user should take a minimum sample size of 0.2 mL to assure homogeneity.

#### 10.0 QUALITY STANDARD DOCUMENTATION

## 10.1 ISO 9001 Quality Management System Registration

- QSR Certificate Number QSR-1034

# 10.2 ISO/IEC 17025 "General Requirements for the Competence of Testing and Calibration Laboratories"

- Chemical Testing - Accredited / A2LA Certificate Number 883.01

#### 10.3 ISO 17034 "General Requirements for the Competence of Reference Material Producers"

- Reference Material Producer - Accredited / A2LA Certificate Number 883.02

Inorganic Ventures, 300 Technology Drive, Christiansburg, Va. 24073, USA; Telephone: 800.669.6799; 540.585.3030, Fax: 540.585.3012; inorganicventures.com; info@inorganicventures.com

#### 11.0 CERTIFICATION, LOT EXPIRATION AND PERIOD OF VALIDITY

#### 11.1 Certification Issue Date

March 17, 2023

- The certification is valid within the measurement uncertainty specified provided the CRM/RM is stored and handled in accordance with instructions given in Sec 7.1. This certification is nullified if instructions in Sec 7.1 are not followed or if the CRM/RM is damaged, contaminated, or otherwise modified.

#### 11.2 Lot Expiration Date

- March 17, 2028
- The date after which this CRM/RM should not be used.
- The lot expiration date reflects the period of time that the stability of a CRM/RM can be supported by long term stability studies conducted on properly stored and handled CRM/RMs. Lot expiration is limited primarily by transpiration (loss of water from the solution) and infrequently by chemical stability.

#### 11.3 Period of Validity

<ul> <li>Sealed TCT Bag Open Date</li> </ul>	
--	--

- This CRM/RM should not be used longer than one year (or six months in the case of a 30 mL bottle) from the date of opening the aluminized bag or after the date given in Sec. 11.2, whichever comes first. This is contingent upon the CRM/RM being stored and handled in accordance with the instructions given in Sec. 7.1.

### 12.0 NAMES AND SIGNATURES OF CERTIFYING OFFICERS

Certificate Approved By:

Thomas Kozikowski Manager, Quality Control 3D978hi.

**Certifying Officer:** 

Paul Gaines
Chairman / Senior Technical I

Chairman / Senior Technical Director



# Certificate of Analysis

300 Technology Drive Christiansburg, VA 24073 USA inorganicventures.com M5062 M5063

P: 800-669-6799/540-585-3030 F: 540-585-3012 info@inorganicventures.com

#### 1.0 ACCREDITATION / REGISTRATION

**INORGANIC VENTURES** is accredited to ISO 17034, "General Requirements for the Competence of Reference Material Producers" and ISO/IEC 17025, "General Requirements for the Competence of Testing and Calibration Laboratories". Inorganic Ventures is also an ISO 9001 registered manufacturer (QSR Certificate Number QSR-1034).



### 2.0 PRODUCT DESCRIPTION

Product Code:

Single Analyte Mass Spec Solution

Catalog Number:

MSHG-10PPM

Lot Number:

S2-HG709270

Matrix:

10% (v/v) HCI

Value / Analyte(s):

10 μg/mL ea:

Mercury

Starting Material:

Hg metal

Starting Material Lot#:

1959

Starting Material Purity:

99.9994%

#### 3.0 CERTIFIED VALUES AND UNCERTAINTIES

**Certified Value:** 

 $10.001 \pm 0.053 \,\mu g/mL$ 

Density:

1.020 g/mL (measured at 20 ± 4 °C)

#### **Assay Information:**

ANALYTE	METHOD	NIST SRM#	SRM LOT#
Hg	ICP Assay	3133	160921
Hg	EDTA	928	928
Ha	Calculated		See Sec. 4.2

The following equations are used in the calculation of the certified value and the uncertainty. Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of k = 2.

#### Characterization of CRM/RM by Two or More Methods

Certified Value, X<sub>CRM/RM</sub>, where two or more methods of characterization are used is the weighted mean of the results:

 $X_{CRM/RM} = \Sigma(w_i) (X_i)$ 

 $\mathbf{X_i}$  = mean of Assay Method i with standard uncertainty  $\mathbf{u_{char}}$  i

w<sub>i</sub> = the weighting factors for each method calculated using the inverse square of

the variance.

 $\mathbf{w_i} = (1/u_{chari})^2 / (\Sigma (1/(u_{chari})^2)$ 

CRM/RM Expanded Uncertainty (±) =  $U_{CRM/RM} = k (u_{char}^2 + u_{bb}^2 + u_{its}^2 + u_{ts}^2)^{1/2}$ 

k = coverage factor = 2

 $u_{char} = [\Sigma((w_i)^2 (u_{char})^2)]^{\frac{1}{2}}$  where  $u_{char}$  i are the errors from each characterization method

u<sub>bb</sub> = bottle to bottle homogeneity standard uncertainty

ults = long term stability standard uncertainty (storage)

uts = transport stability standard uncertainty

#### Characterization of CRM/RM by One Method

Certified Value,  $X_{CRM/RM}$ , where one method of characterization is used is the mean of individual results:

X<sub>CRM/RM</sub> = (X<sub>a</sub>) (u<sub>char a</sub>)

Xa = mean of Assay Method A with

uchar a = the standard uncertainty of characterization Method A

CRM/RM Expanded Uncertainty (±) = U<sub>CRM/RM</sub> = k (u<sup>2</sup>char a + u<sup>2</sup>bb + u<sup>2</sup>lts + u<sup>2</sup>ts) 1/2

k = coverage factor = 2

u<sub>char a</sub> = the errors from characterization

ubb = bottle to bottle homogeneity standard uncertainty

u<sub>lts</sub> = long term stability standard uncertainty (storage)

uts = transport stability standard uncertainty

### 4.0 TRACEABILITY TO NIST

- This product is traceable to NIST via an unbroken chain of comparisons. The uncertainties for each certified value are reported, taking into account the SRM/RM uncertainty error and the measurement, weighing and volume dilution errors. In rare cases where no NIST SRM/RM are available, the term 'in-house std.' is specified.

#### 4.1 Thermometer Calibration

- All thermometers are NIST traceable through thermometers that are calibrated by an accredited calibration laboratory.

#### 4.2 Balance Calibration

- All analytical balances are calibrated by an accredited calibration laboratory and procedure. The weights used for testing are annually compared to master weights and are traceable to NIST.

#### 4.3 Glassware Calibration

- An in-house procedure is used to calibrate all Class A glassware used in the manufacturing and quality control of CRM/RMs.

### 5.0 TRACE METALLIC IMPURITIES (TMI) DETERMINED BY ICP-MS AND ICP-OES (µg/mL)

CRM/RMs are tested for trace metallic impurities by Axial ICP-OES and ICP-MS. The result from the most sensitive method for each element, is reported below. Solutions tested by ICP-MS were analyzed in an ULPA-Filtered Clean Room. An ULPA-Filter is 99.9985% efficient for the removal of particles down to 0.3 µm.

```
O Ag
          0.000011 M Eu <
                            0.000201 O Na
                                              0.000004 M Se <
                                                               0.015915 O Zn <
                                                                                 0.001510
0
   Al
          0.000001 O Fe
                            0.000001 M Nb <
                                              0.000201 O Si
                                                                0.000005 M Zr <
                                                                                 0.000201
M
   As <
          0.000402 M Ga <
                            0.000201 M Nd <
                                              0.000201 M Sm <
                                                               0.000201
M
   Au <
          0.003631 M Gd <
                            0.000201 M Ni <
                                              0.000402 M
                                                        Sn <
                                                               0.001007
M
   B <
          0.001208 M
                    Ge <
                            0.000201 M Os <
                                              0.000605 M
                                                        Sr <
                                                               0.000201
M Ba <
          0.000201 M Hf <
                            0.000201 O P <
                                              0.032370 M
                                                        Ta <
                                                               0.000201
M
  Be <
          0.000201 s
                                   M Pb <
                    Hq <
                                              0.000201 M Tb <
                                                               0.000201
M Bi <
          0.000201 M
                    Ho <
                            0.000201 M Pd <
                                              0.000403 M
                                                        Te <
                                                               0.002216
0
  Ca
          0.000007 M In <
                            0.000201 M Pr <
                                              0.000201 M Th <
                                                               0.000201
M
  Cd <
          0.000201 M Ir
                            0.000201 M
                                      Pt <
                                              0.000402 M Ti <
                                                               0.000402
                                              0.000201 O TI <
M
  Ce <
          0.000201 O K
                            0.000020 M
                                      Rb <
                                                               0.016508
  Co <
M
          0.000201 M La <
                            0.000201 M
                                      Re <
                                              0.000201 M Tm <
                                                               0.000201
  Cr <
0
          0.003021 O Li <
                            0.000107 M
                                      Rh <
                                              0.000201 M U <
                                                               0.008058
M
  Cs <
          0.001208 M Lu <
                            0.000201 M Ru <
                                              0.000201 M V <
                                                               0.000201
M
  Cu <
          0.000402 O
                    Mg
                            0.000001 O
                                      S <
                                             0.053950 M W <
                                                               0.000604
M Dy <
          0.000201 M Mn <
                            0.000604 M Sb <
                                             0.001208 M Y <
                                                               0.000201
M Er <
          0.000201 M Mo
                           0.000009 M Sc <
                                             0.000201 M Yb <
                                                               0.000201
```

M - Checked by ICP-MS O - Checked by ICP-OES i - Spectral Interference n - Not Checked For s - Solution Standard Element

#### 6.0 INTENDED USE

- For the calibration of analytical instruments and validation of analytical methods as appropriate.

### 7.0 INSTRUCTIONS FOR THE CORRECT USE OF THIS REFERENCE MATERIAL

#### 7.1 Storage and Handling Recommendations

- Store between approximately 4° 30° C while in sealed TCT bag.
- While stored in the sealed TCT bag, transpiration of this CRM/RM is negligible. After opening the sealed TCT bag transpiration of the CRM/RM will occur, resulting in a gradual increase in the analyte concentration(s). It is the responsibility of the user to account for this effect. When the bottle is weighed both before and after being placed in storage, the mass difference observed will be a measure of transpiration mass loss.
- After opening the sealed TCT bag, keep cap tightly sealed when not in use and store between  $4^{\circ}$   $24^{\circ}$  C to minimize the effects of transpiration. Use at  $20^{\circ} \pm 4^{\circ}$  C to minimize volumetric dilution error when using the reported density. Do not pipette from the container. Do not return removed aliquots to container.
- For more information, visit www.inorganicventures.com/TCT

**Atomic Weight; Valence; Coordination Number; Chemical Form in Solution -** 200.59 +2 4 Hg(OH)(aq) 1+ **Chemical Compatibility -** Stable in HNO3. Avoid basic media forming insoluble carbonate. The sulfide, basic carbonate, oxalate, phosphate, arsenite, arsenate and iodide are insoluble in water.

**Stability -** 2-100 ppb levels not stable in 1% HNO3 / LDPE container, stable in 10% HNO3 packaged in borosilicate glass. 1-100 ppm levels stable in 7% HNO3 packaged in borosilicate glass. 1000-10,000 ppm solutions are chemically stable for years in 5-10% HNO3 / LDPE container.

**Hg Containing Samples (Preparation and Solution) -** Metal (soluble in HNO3); Oxide (Soluble in HNO3); Ores and Organic based (The literature has more references to the preparation of Hg containing samples than any other element. Please consult the literature for your specific sample type, since such preparations are prone to error. Or e-mail our technical staff and we will contact you to discuss your particular sample preparation questions in further detail.).

Atomic Spectroscopic Information (ICP-OES D.L.s are given as radial/axial view):

Technique/Line	Estimated D.L.	Order	Interferences (underlined indicates severe)
ICP-MS 202 amu	9 ppt	n/a	186W16O
ICP-OES 184.950 nm	0.03 / 0.005 μg/mL	1	
ICP-OES 194.227 nm	0.03 / 0.005 µg/mL	1	V
ICP-OES 253.652 nm	0.1 / 0.03 µg/mL	1	Ta, Co, Th, Rh, Fe,
			U

#### 8.0 HAZARDOUS INFORMATION

- Please refer to the Safety Data Sheet for information regarding this CRM/RM.

#### 9.0 HOMOGENEITY

- This solution was mixed according to an in-house procedure and is guaranteed to be homogeneous. Homogeneity data indicate that the end user should take a minimum sample size of 0.2 mL to assure homogeneity.

#### 10.0 QUALITY STANDARD DOCUMENTATION

#### 10.1 ISO 9001 Quality Management System Registration

- QSR Certificate Number QSR-1034

### 10.2 ISO/IEC 17025 "General Requirements for the Competence of Testing and Calibration Laboratories"

- Chemical Testing - Accredited / A2LA Certificate Number 883.01

#### 10.3 ISO 17034 "General Requirements for the Competence of Reference Material Producers"

- Reference Material Producer - Accredited / A2LA Certificate Number 883.02

Inorganic Ventures, 300 Technology Drive, Christiansburg, Va. 24073, USA; Telephone: 800.669.6799; 540.585.3030, Fax: 540.585.3012; inorganicventures.com; info@inorganicventures.com

#### 11.0 CERTIFICATION, LOT EXPIRATION AND PERIOD OF VALIDITY

#### 11.1 Certification Issue Date

September 22, 2021

- The certification is valid within the measurement uncertainty specified provided the CRM/RM is stored and handled in accordance with instructions given in Sec 7.1. This certification is nullified if instructions in Sec 7.1 are not followed or if the CRM/RM is damaged, contaminated, or otherwise modified.

### 11.2 Lot Expiration Date

- September 22, 2026
- The date after which this CRM/RM should not be used.
- The lot expiration date reflects the period of time that the stability of a CRM/RM can be supported by long term stability studies conducted on properly stored and handled CRM/RMs. Lot expiration is limited primarily by transpiration (loss of water from the solution) and infrequently by chemical stability.

### 11.3 Period of Validity

Sealed TCT	Bag	Open Date	:		

- This CRM/RM should not be used longer than one year (or six months in the case of a 30 mL bottle) from the date of opening the aluminized bag or after the date given in Sec. 11.2, whichever comes first. This is contingent upon the CRM/RM being stored and handled in accordance with the instructions given in Sec. 7.1.

# 12.0 NAMES AND SIGNATURES OF CERTIFYING OFFICERS Certificate Prepared By:

Uyen Truong
Supervisor, Product Documentation

Mya Truong

#### Certificate Approved By:

Michael Booth Director, Quality Control Michael 2 Booth

#### Certifying Officer:

Paul Gaines Chairman / Senior Technical Director Paul R Laines

Hydrochloric Acid, 36.5-38.0%

BAKER INSTRA-ANALYZED® Reagent
For Trace Metal Analysis





M6151

R-> 1/15/25

Material No.: 9530-33

Batch No.: 22G2862015 Manufactured Date: 2022-06-15

Retest Date: 2027-06-14

Revision No.: 0

# Certificate of Analysis

Test	Specification	Result
ACS - Assay (as HCI) (by acid-base titrn)	36.5 - 38.0 %	
ACS - Color (APHA)	50.5 - 38.0 % ≤ 10	37.9 %
ACS - Residue after Ignition	≤ 3 ppm	5
ACS - Specific Gravity at 60°/60°F		< 1 ppm
ACS – Bromide (Br)	1.185 - 1.192	1.191
ACS - Extractable Organic Substances	≤ 0.005 %	< 0.005 %
ACS - Free Chlorine (as Cl2)	≤ 5 ppm	< 1 ppm
Phosphate (PO <sub>4</sub> )	≤ 0.5 ppm	< 0.5 ppm
Sulfate (SO <sub>4</sub> )	≤ 0.05 ppm	< 0.03 ppm
Sulfite (SO₃)	≤ 0.5 ppm	< 0.3 ppm
Ammonium (NH <sub>4</sub> )	≤ 0.8 ppm	0.3 ppm
Trace Impurities - Arsenic (As)	≤ 3 ppm	< 1 ppm
Trace Impurities – Aluminum (AI)	≤ 0.010 ppm	< 0.003 ppm
Arsenic and Antimony (as As)	≤ 10.0 ppb	1.3 ppb
Trace Impurities - Barium (Ba)	≤ 5.0 ppb	< 3.0 ppb
Trace Impurities – Beryllium (Be)	≤ 1.0 ppb	0.2 ppb
Trace Impurities - Bismuth (Bi)	≤ 1.0 ppb	< 0.2 ppb
Trace Impurities – Boron (B)	≤ 10.0 ppb	< 1.0 ppb
Trace Impurities - Cadmium (Cd)	≤ 20.0 ppb	< 5.0 ppb
Trace Impurities - Calcium (Ca)	≤ 1.0 ppb	< 0.3 ppb
Trace Impurities - Calcium (Ca)  Trace Impurities - Chromium (Cr)	≤ 50.0 ppb	163.0 ppb
Trace Impurities - Cobalt (Co)	≤ 1.0 ppb	0.7 ppb
	≤ 1.0 ppb	< 0.3 ppb
Trace Impurities - Copper (Cu)	≤ 1.0 ppb	< 0.1 ppb
Trace Impurities - Gallium (Ga)	≤ 1.0 ppb	< 0.2 ppb
Frace Impurities – Germanium (Ge)	≤ 3.0 ppb	< 2.0 ppb
Frace Impurities – Gold (Au)	≤ 4.0 ppb	0.6 ppb
Heavy Metals (as Pb)	≤ 100 ppb	< 50 ppb
Frace Impurities – Iron (Fe)	≤ 15 ppb	6 ppb

>>> Continued on page 2 >>>

Hydrochloric Acid, 36.5-38.0% BAKER INSTRA-ANALYZED® Reagent For Trace Metal Analysis





Material No.: 9530-33 Batch No.: 22G2862015

Test	Specification	Result
Trace Impurities – Lead (Pb)	≤ 1.0 ppb	< 0.5 ppb
Trace Impurities - Lithium (Li)	≤ 1.0 ppb	< 0.2 ppb
Trace Impurities – Magnesium (Mg)	≤ 10.0 ppb	2.9 ppb
Trace Impurities - Manganese (Mn)	≤ 1.0 ppb	< 0.4 ppb
Trace Impurities – Mercury (Hg)	≤ 0.5 ppb	0.1 ppb
Trace Impurities – Molybdenum (Mo)	≤ 10.0 ppb	< 3.0 ppb
Trace Impurities - Nickel (Ni)	≤ 4.0 ppb	< 0.3 ppb
Trace Impurities - Niobium (Nb)	≤ 1.0 ppb	0.8 ppb
Trace Impurities - Potassium (K)	≤ 9.0 ppb	< 2.0 ppb
Trace Impurities - Selenium (Se), For Information Only		< 1.0 ppb
Trace Impurities - Silicon (Si)	≤ 100.0 ppb	< 10.0 ppb
Trace Impurities - Silver (Ag)	≤ 1.0 ppb	0.5 ppb
Trace Impurities – Sodium (Na)	≤ 100.0 ppb	2.3 ppb
Trace Impurities – Strontium (Sr)	≤ 1.0 ppb	< 0.2 ppb
Trace Impurities – Tantalum (Ta)	≤ 1.0 ppb	1.6 ppb
Trace Impurities – Thallium (TI)	≤ 5.0 ppb	< 2.0 ppb
Trace Impurities – Tin (Sn)	≤ 5.0 ppb	4.0 ppb
Trace Impurities – Titanium (Ti)	≤ 1.0 ppb	1.5 ppb
Trace Impurities – Vanadium (V)	≤ 1.0 ppb	< 0.2 ppb
Trace Impurities – Zinc (Zn)	≤ 5.0 ppb	0.8 ppb
Frace Impurities – Zirconium (Zr)	≤ 1.0 ppb	0.3 ppb

Hydrochloric Acid, 36.5-38.0% BAKER INSTRA-ANALYZED® Reagent For Trace Metal Analysis





Material No.: 9530-33 Batch No.: 22G2862015

Test

Specification

Result

For Laboratory, Research, or Manufacturing Use Product Information (not specifications): Appearance (clear, fuming liquid) Meets ACS Specifications Storage Condition: Store below 25 °C.

Country of Origin: USA Packaging Site: Phillipsburg Mfg Ctr & DC







R-02/02/2025

M-6158

Material No.: 9606-03 Batch No.: 24D1062002

Manufactured Date: 2024-03-26

Retest Date: 2029-03-25 Revision No.: 0

# Certificate of Analysis

Test	Specification	Result
Assay (HNO3)	69.0 - 70.0 %	
Appearance	Passes Test	69.7 %
Color (APHA)	≤ 10	Passes Test
Residue after Ignition		5
Chloride (CI)	≤ 2 ppm	1 ppm
Phosphate (PO <sub>4</sub> )	≤ 0.08 ppm	< 0.03 ppm
Sulfate (SO <sub>4</sub> )	≤ 0.10 ppm	< 0.03 ppm
Trace Impurities - Aluminum (AI)	≤ 0.2 ppm	< 0.2 ppm
Arsenic and Antimony (as As)	≤ 40.0 ppb	< 1.0 ppb
Trace Impurities - Barium (Ba)	≤ 5.0 ppb	< 2.0 ppb
Trace Impurities – Beryllium (Be)	≤ 10.0 ppb	< 1.0 ppb
Trace Impurities – Bismuth (Bi)	≤ 10.0 ppb	< 1.0 ppb
Trace Impurities - Boron (B)	≤ 20.0 ppb	< 10.0 ppb
Trace Impurities - Cadmium (Cd)	≤ 10.0 ppb	< 5.0 ppb
Trace Impurities - Calcium (Ca)	≤ 50 ppb	< 1 ppb
Trace Impurities - Chromium (Cr)	≤ 50.0 ppb	2.3 ppb
Trace Impurities – Cobalt (Co)	≤ 30.0 ppb	< 1.0 ppb
Trace Impurities - Copper (Cu)	≤ 10.0 ppb	< 1.0 ppb
Trace Impurities – Gallium (Ga)	≤ 10.0 ppb	< 1.0 ppb
Trace Impurities - Germanium (Ge)	≤ 10.0 ppb	< 1.0 ppb
Trace Impurities – Gold (Au)	≤ 20 ppb	< 10 ppb
Heavy Metals (as Pb)	≤ 20 ppb	< 5 ppb
Trace Impurities - Iron (Fe)	≤ 100 ppb	100 ppb
Trace Impurities - Lead (Pb)	≤ 40.0 ppb	< 1.0 ppb
Trace Impurities – Lead (PD)  Trace Impurities – Lithium (Li)	≤ 20.0 ppb	< 10.0 ppb
	≤ 10.0 ppb	< 1.0 ppb
Trace Impurities - Magnesium (Mg)	≤ 20 ppb	< 1 ppb
race Impurities – Manganese (Mn) race Impurities – Nickel (Ni)	≤ 10.0 ppb	< 1.0 ppb
	≤ 20.0 ppb	< 5.0 ppb

>>> Continued on page 2 >>>





Material No.: 9606-03 Batch No.: 24D1062002

Test	Specification	D. I.
Trace Impurities – Niobium (Nb)		Result
Trace Impurities – Potassium (K)	≤ 50.0 ppb	< 1.0 ppb
Trace Impurities – Silicon (Si)	≤ 50 ppb	16 ppb
	≤ 50 ppb	< 10 ppb
Trace Impurities – Silver (Ag)	≤ 20.0 ppb	< 1.0 ppb
Trace Impurities - Sodium (Na)	≤ 150.0 ppb	
Trace Impurities - Strontium (Sr)	≤ 30.0 ppb	< 5.0 ppb
Trace Impurities - Tantalum (Ta)		< 1.0 ppb
Trace Impurities – Thallium (TI)	≤ 10.0 ppb	< 5.0 ppb
Trace Impurities – Tin (Sn)	≤ 10.0 ppb	< 5.0 ppb
	≤ 20.0 ppb	< 10.0 ppb
Trace Impurities – Titanium (Ti)	≤ 10.0 ppb	< 1.0 ppb
Trace Impurities – Vanadium (V)	≤ 10.0 ppb	
Frace Impurities - Zinc (Zn)	≤ 20.0 ppb	< 1.0 ppb
Frace Impurities – Zirconium (Zr)		< 1.0 ppb
Particle Count - 0.5 µm and greater	≤ 10.0 ppb	< 1.0 ppb
Particle Count - 1.0 µm and greater	≤ 60 par/mi	10 par/ml
	≤ 10 par/ml	3 par/ml

Nitric Acid 69% **CMOS** 





Material No.: 9606-03 Batch No.: 24D1062002

Test Specification Result

For Microelectronic Use

Country of Origin: USA Packaging Site: Phillipsburg Mfg Ctr & DC

Jamie Croak Director Quality Operations, Bioscience Production





M-6162

R. Date & 0412712025

Material No.: 9606-03 Batch No.: 24H0162012 Manufactured Date: 2024-06-28

Retest Date: 2029-06-27 Revision No.: 0

# Certificate of Analysis

Assay (HNOs) Appearance Passes Test Passes Test Passes Test Color (APHA)  Residue after Ignition  S 2 ppm  Chloride (Cl) Choride (Cl) Choride (CQ) Phosphate (PO₄) Sulfate (SO₄) Sulfate (SO₄)  Trace Impurities - Aluminum (Al) Arsenic and Antimony (as As)  Trace Impurities - Beryllium (Be)  Trace Impurities - Beryllium (Be)  Trace Impurities - Beryllium (Be)  Trace Impurities - Bismuth (Bi)  Trace Impurities - Bismuth (Bi)  Trace Impurities - Calcium (Cd)  Trace Impurities - Calcium (Cd)  Trace Impurities - Cobait (Co)  Trace Impurities - Cobait (Co)  Trace Impurities - Cobait (Co)  Trace Impurities - Coper (Cu)  Trace Impurities - Gold (Au)  Frace Impurities - Gold (Au)  Frace Impurities - Gold (Au)  Frace Impurities - Iron (Fe)  Trace Impurities - Iron (Fe)  Trace Impurities - Lithium (Li)  Trace Impurities - Manganese (Mn)  ≤ 20.0 ppb  < 10.0 ppb  < 1.0 ppb  Trace Impurities - Lithium (Li)  Trace Impurities - Lithium (Li)  Trace Impurities - Manganese (Mn)  ≤ 20.0 ppb  < 1.0 ppb  < 1.0 ppb  Trace Impurities - Manganese (Mn)  ≤ 20.0 ppb  < 1.0 ppb  < 1.0 ppb	Test	Specification	Result
Appearance Color (APHA)	Assay (HNO3)	69.0 - 70.0 %	69.7 %
Color (APHA)       ≤ 10       5         Residue after Ignition       ≤ 2 ppm       < 1 ppm	Appearance		
Residue after Ignition       ≤ 2 ppm       < 1 ppm	Color (APHA)	≤ 10	
Chloride (CI)       ≤ 0.08 ppm       0.03 ppm         Phosphate (PO4)       ≤ 0.10 ppm       < 0.03 ppm	Residue after Ignition	≤ 2 ppm	
Phosphate (PO₄)         ≤ 0.10 ppm         < 0.03 ppm	Chloride (CI)	≤ 0.08 ppm	
Sulfate (SO <sub>4</sub> )       ≤ 0.2 ppm       < 0.2 ppm	Phosphate (PO <sub>4</sub> )	≤ 0.10 ppm	• •
Trace Impurities - Aluminum (Al)       ≤ 40.0 ppb       < 1.0 ppb	Sulfate (SO <sub>4</sub> )	≤ 0.2 ppm	
Arsenic and Antimony (as As)    Solution   S	Trace Impurities - Aluminum (Al)	≤ 40.0 ppb	• •
Trace Impurities – Barium (Ba)	Arsenic and Antimony (as As)	≤ 5.0 ppb	
Trace Impurities – Beryllium (Be)  Trace Impurities – Bismuth (Bi)  Trace Impurities – Boron (B)  Trace Impurities – Cadmium (Cd)  Trace Impurities – Calcium (Ca)  Trace Impurities – Calcium (Ca)  Trace Impurities – Chromium (Cr)  Trace Impurities – Cobalt (Co)  Trace Impurities – Cobalt (Co)  Trace Impurities – Copper (Cu)  Trace Impurities – Copper (Cu)  Trace Impurities – Gallium (Ga)  Trace Impurities – Gallium (Ga)  Trace Impurities – Gallium (Ga)  Trace Impurities – Germanium (Ge)  Trace Impurities – Gold (Au)  Heavy Metals (as Pb)  Trace Impurities – Iron (Fe)  Trace Impurities – Lead (Pb)  Trace Impurities – Lead (Pb)  Trace Impurities – Magnesium (Mg)  Trace Impurities – Manganese (Mn)  Trace Impurities – Mickel (Ni)  ■ 20 ppb  ■ 21.0 ppb  ▼ 1.0 ppb	Trace Impurities – Barium (Ba)	≤ 10.0 ppb	
Trace Impurities – Bismuth (Bi)    \$\leq 20.0 ppb	Trace Impurities - Beryllium (Be)	≤ 10.0 ppb	• •
Trace Impurities – Boron (B) ≤ 10.0 ppb 0.1 ppb  Trace Impurities – Cadmium (Cd) ≤ 50 ppb < 1 ppb  Trace Impurities – Calcium (Ca) ≤ 50.0 ppb 0.3 ppb  Trace Impurities – Chromium (Cr) ≤ 30.0 ppb 0.1 ppb  Trace Impurities – Cobalt (Co) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities – Copper (Cu) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities – Gallium (Ga) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities – Gallium (Ga) ≤ 20 ppb < 1 ppb  Trace Impurities – Gold (Au) ≤ 20 ppb < 1 ppb  Trace Impurities – Gold (Au) ≤ 20 ppb < 1 ppb  Trace Impurities – Iron (Fe) ≤ 40.0 ppb < 1.0 ppb  Trace Impurities – Lithium (Li) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities – Lithium (Li) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities – Magnaese (Mn) ≤ 20 ppb < 1.0 ppb	Trace Impurities - Bismuth (Bi)	≤ 20.0 ppb	• •
Trace Impurities - Cadmium (Cd) ≤ 50 ppb 0.3 ppb  Trace Impurities - Calcium (Ca) ≤ 50.0 ppb 0.3 ppb  Trace Impurities - Chromium (Cr) ≤ 30.0 ppb 0.1 ppb  Trace Impurities - Cobalt (Co) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Copper (Cu) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Gallium (Ga) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Germanium (Ge) ≤ 20 ppb < 1 ppb  Trace Impurities - Gold (Au) ≤ 20 ppb < 1 ppb  Heavy Metals (as Pb) ≤ 100 ppb < 50 ppb  Trace Impurities - Iron (Fe) ≤ 40.0 ppb < 1.0 ppb  Trace Impurities - Lead (Pb) ≤ 20.0 ppb < 1.0 ppb  Trace Impurities - Lithium (Li) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Magnesium (Mg) ≤ 20 ppb < 1.0 ppb  Trace Impurities - Magnesee (Mn) ≤ 10.0 ppb < 1.0 ppb	Trace Impurities - Boron (B)	≤ 10.0 ppb	
Trace Impurities - Calcium (Ca) ≤ 50.0 ppb 0.3 ppb  Trace Impurities - Chromium (Cr) ≤ 30.0 ppb 0.1 ppb  Trace Impurities - Cobalt (Co) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Copper (Cu) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Gallium (Ga) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Germanium (Ge) ≤ 20 ppb < 1 ppb  Trace Impurities - Gold (Au) ≤ 20 ppb < 1 ppb  Trace Impurities - Gold (Au) ≤ 20 ppb < 50 ppb  Trace Impurities - Iron (Fe) ≤ 40.0 ppb < 1.0 ppb  Trace Impurities - Lead (Pb) ≤ 20.0 ppb < 1.0 ppb  Trace Impurities - Lithium (Li) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Magnesium (Mg) ≤ 20 ppb < 1 ppb  Trace Impurities - Manganese (Mn) ≤ 10.0 ppb < 1.0 ppb	Trace Impurities - Cadmium (Cd)	≤ 50 ppb	
Trace Impurities - Chromium (Cr) ≤ 30.0 ppb 0.1 ppb  Trace Impurities - Cobalt (Co) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Copper (Cu) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Gallium (Ga) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Germanium (Ge) ≤ 20 ppb < 1 ppb  Trace Impurities - Gold (Au) ≤ 20 ppb < 1 ppb  Heavy Metals (as Pb) ≤ 100 ppb < 50 ppb  Trace Impurities - Iron (Fe) ≤ 40.0 ppb < 1.0 ppb  Trace Impurities - Lead (Pb) ≤ 20.0 ppb < 1.0 ppb  Trace Impurities - Lithium (Li) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Magnesium (Mg) ≤ 20 ppb < 1 ppb  Trace Impurities - Magnesium (Mg) ≤ 20 ppb < 1 ppb  Trace Impurities - Magnesium (Mg) ≤ 10.0 ppb < 1.0 ppb	Trace Impurities - Calcium (Ca)		• •
Trace Impurities - Cobalt (Co) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Copper (Cu) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Gallium (Ga) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Germanium (Ge) < 20 ppb < 1 ppb  Trace Impurities - Gold (Au) ≤ 20 ppb < 1 ppb  Heavy Metals (as Pb) ≤ 100 ppb < 50 ppb  Trace Impurities - Iron (Fe) ≤ 40.0 ppb < 1.0 ppb  Trace Impurities - Lead (Pb) < 20.0 ppb < 1.0 ppb  Trace Impurities - Lithium (Li) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Magnesium (Mg) ≤ 20 ppb < 1 ppb  Trace Impurities - Magnesee (Mn) ≤ 10.0 ppb < 1.0 ppb	Trace Impurities - Chromium (Cr)	≤ 30.0 ppb	
Trace Impurities - Copper (Cu) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Gallium (Ga) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Germanium (Ge) ≤ 20 ppb < 1 ppb  Trace Impurities - Gold (Au) ≤ 20 ppb < 1 ppb  Heavy Metals (as Pb) ≤ 100 ppb < 50 ppb  Trace Impurities - Iron (Fe) ≤ 40.0 ppb < 1.0 ppb  Trace Impurities - Lead (Pb) ≤ 20.0 ppb < 1.0 ppb  Trace Impurities - Lithium (Li) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities - Magnesium (Mg) ≤ 20 ppb < 1 ppb  Trace Impurities - Magnesium (Mg) ≤ 20 ppb < 1.0 ppb	Trace Impurities - Cobalt (Co)	≤ 10.0 ppb	
Trace Impurities – Gallium (Ga) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities – Germanium (Ge) ≤ 20 ppb < 1 ppb  Trace Impurities – Gold (Au) ≤ 20 ppb < 1 ppb  Heavy Metals (as Pb) ≤ 100 ppb < 50 ppb  Trace Impurities – Iron (Fe) ≤ 40.0 ppb < 1.0 ppb  Trace Impurities – Lead (Pb) ≤ 20.0 ppb < 1.0 ppb  Trace Impurities – Lithium (Li) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities – Magnesium (Mg) ≤ 20 ppb < 1 ppb  Trace Impurities – Magnesium (Mg) ≤ 20 ppb < 1 ppb  Trace Impurities – Manganese (Mn) ≤ 10.0 ppb < 1.0 ppb	Trace Impurities - Copper (Cu)	≤ 10.0 ppb	• •
Trace Impurities – Germanium (Ge) ≤ 20 ppb < 1 ppb  Trace Impurities – Gold (Au) ≤ 20 ppb < 1 ppb  Heavy Metals (as Pb) ≤ 100 ppb < 50 ppb  Trace Impurities – Iron (Fe) ≤ 40.0 ppb < 1.0 ppb  Trace Impurities – Lead (Pb) ≤ 20.0 ppb < 1.0 ppb  Trace Impurities – Lithium (Li) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities – Magnesium (Mg) ≤ 20 ppb < 1 ppb  Trace Impurities – Magnese (Mn) ≤ 10.0 ppb < 1 ppb	Trace Impurities - Gallium (Ga)	≤ 10.0 ppb	
Trace Impurities - Gold (Au)       ≤ 20 ppb       < 1 ppb	Trace Impurities - Germanium (Ge)	≤ 20 ppb	
Heavy Metals (as Pb) ≤ 100 ppb < 50 ppb  Trace Impurities – Iron (Fe) ≤ 40.0 ppb < 1.0 ppb  Trace Impurities – Lead (Pb) ≤ 20.0 ppb < 1.0 ppb  Trace Impurities – Lithium (Li) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities – Magnesium (Mg) ≤ 20 ppb < 1 ppb  Trace Impurities – Manganese (Mn) ≤ 10.0 ppb < 1.0 ppb	Trace Impurities - Gold (Au)	≤ 20 ppb	• •
Trace Impurities – Iron (Fe)       ≤ 40.0 ppb       < 1.0 ppb	Heavy Metals (as Pb)	≤ 100 ppb	
Trace Impurities – Lead (Pb)       ≤ 20.0 ppb       < 1.0 ppb	Trace Impurities - Iron (Fe)	• •	
Trace Impurities – Lithium (Li)       ≤ 10.0 ppb       < 1.0 ppb	Trace Impurities - Lead (Pb)	≤ 20.0 ppb	• • • • • • • • • • • • • • • • • • • •
Trace Impurities – Magnesium (Mg) ≤ 20 ppb < 1 ppb  Trace Impurities – Manganese (Mn) ≤ 10.0 ppb < 1.0 ppb  Trace Impurities – Mickel (Ni)	Trace Impurities - Lithium (Li)	≤ 10.0 ppb	• •
Trace Impurities - Manganese (Mn) ≤ 10.0 ppb < 1.0 ppb	Trace Impurities – Magnesium (Mg)	≤ 20 ppb	• •
Trace Impurities Mickel (Ni)	Trace Impurities - Manganese (Mn)	• •	
	Trace Impurities – Nickel (Ni)	≤ 20.0 ppb	< 1.0 ppb

>>> Continued on page 2 >>>





Material No.: 9606-03 Batch No.: 24H0162012

Test	Specification	Result
Trace Impurities - Niobium (Nb)	≤ 50.0 ppb	< 1.0 ppb
Trace Impurities – Potassium (K)	≤ 50 ppb	< i ppb
Trace Impurities - Silicon (Si)	≤ 50 ppb	1 ppb
Trace Impurities - Silver (Ag)	≤ 20.0 ppb	< 1.0 ppb
Trace Impurities – Sodium (Na)	≤ 150.0 ppb	< 1.0 ppb
Trace Impurities - Strontium (Sr)	≤ 30.0 ppb	< 1.0 ppb
Trace Impurities – Tantalum (Ta)	≤ 10.0 ppb	< 1.0 ppb
Trace Impurities - Thallium (TI)	≤ 10.0 ppb	< 1.0 ppb
Trace Impurities - Tin (Sn)	≤ 20.0 ppb	< 1.0 ppb
Trace Impurities - Titanium (Ti)	≤ 10.0 ppb	< 1.0 ppb
Trace Impurities - Vanadium (V)	≤ 10.0 ppb	< 1.0 ppb
Trace Impurities - Zinc (Zn)	≤ 20.0 ppb	< 1.0 ppb
Trace Impurities - Zirconium (Zr)	≤ 10.0 ppb	< 1.0 ppb
Particle Count - 0.5 µm and greater	≤ 60 par/ml	13 par/ml
Particle Count - 1.0 µm and greater	≤ 10 par/ml	5 par/ml

Nitric Acid 69% **CMOS** 





Material No.: 9606-03 Batch No.: 24H0162012

Test Specification Result

For Microelectronic Use

Country of Origin: USA Packaging Site: Phillipsburg Mfg Ctr & DC