



PERCENT SOLID

Supervisor: apatel
Analyst: jignesh
Date: 3/14/2019

OVENTEMP IN Celsius(°C): 108
Time IN: 17:00
In Date: 03/13/2019
Weight Check 1.0g: 1.00
Weight Check 10g: 10.00
OvenID: M OVEN-1

OVENTEMP OUT Celsius(°C): 103
Time OUT: 08:05
Out Date: 03/14/2019
Weight Check 1.0g: 1.00
Weight Check 10g: 10.00
BalanceID: M SC-1
Thermometer ID: %SOLIDS-OVEN

QC:LB101359

Lab ID	Client Sample ID	Dish#	Dish Wt(g) (A)	Dish + Sample Wt(g) (B)	Dish + Dry Sample Wt(g) (C)	% Solid
K1711-05	TOC-3	1	1.13	9.98	9.43	93.8
K1823-02	STOCK-PILE-1	2	1.13	9.83	5.11	45.7
K1890-01	B-1	3	1.13	9.63	8.79	90.1
K1890-02	B-2	4	1.16	9.97	8.77	86.4
K1891-01	CHRT-24556-CHRT-25423-7	5	1.17	9.87	9.22	92.5
K1892-01	GARAGE-FLOOR	6	1.00	2.00	2.00	100.0
K1892-02	GARAGE-FLOOR	7	1.00	2.00	2.00	100.0
K1893-01	CONCRETE	8	1.00	2.00	2.00	100.0
K1895-01	OILY-SOIL	9	1.13	9.94	8.42	82.7
K1897-01	TP-1	10	1.15	9.75	8.45	84.9
K1897-02	TP-1-A	11	1.15	9.75	8.45	84.9
K1897-03	TP-1-B	12	1.15	9.75	8.45	84.9
K1897-05	TP-1-2-CONCRETE	13	1.00	2.00	2.00	100.0
K1897-06	TP-2	14	1.12	9.91	8.46	83.5
K1897-07	TP-2-A	15	1.12	9.91	8.46	83.5
K1897-08	TP-2-B	16	1.12	9.91	8.46	83.5
K1902-11	30245	17	1.00	2.00	2.00	100.0

$$\% \text{ Solid} = \frac{(C-A) * 100}{(B-A)}$$