



PERCENT SOLID

Supervisor: apatel
Analyst: jignesh
Date: 12/26/2019

OVENTEMP IN Celsius(°C): 107
Time IN: 16:45
In Date: 12/19/2019
Weight Check 1.0g: 1.00
Weight Check 10g: 10.00
OvenID: M OVEN #1

OVENTEMP OUT Celsius(°C): 102
Time OUT: 08:00
Out Date: 12/20/2019
Weight Check 1.0g: 1.00
Weight Check 10g: 10.00
BalanceID: M SC-4
Thermometer ID: %SOLIDS-OVEN

QC:LB106853

Lab ID	Client SampleID	Dish #	Dish Wt (g) (A)	Dish + Sample Wt (g) (B)	Dish+Dry Sample Wt (g) (C)	% Solid	Comments
K6117-07	TR-04-121919	1	1.14	9.82	9.05	91.1	
K6117-08	TR-04-121919	2	1.16	9.71	8.59	86.9	
K6374-01	203	3	1.14	9.54	9.54	100.0	100% SOLIDS
K6376-01	PCB-121719-01	4	1.00	2.00	2.00	100.0	CAULKING MATERIAL 100% SOLIDS
K6376-02	PCB-121719-02	5	1.00	2.00	2.00	100.0	CAULKING MATERIAL 100% SOLIDS
K6376-03	PCB-121719-03	6	1.00	2.00	2.00	100.0	CAULKING MATERIAL 100% SOLIDS
K6376-04	PCB-121719-04	7	1.00	2.00	2.00	100.0	CAULKING MATERIAL 100% SOLIDS
K6376-05	PCB-121719-05	8	1.00	2.00	2.00	100.0	CAULKING MATERIAL 100% SOLIDS
K6376-06	PCB-121719-06	9	1.00	2.00	2.00	100.0	CAULKING MATERIAL 100% SOLIDS
K6376-07	PCB-121719-07	10	1.00	2.00	2.00	100.0	CAULKING MATERIAL 100% SOLIDS
K6376-08	PCB-121719-08	11	1.00	2.00	2.00	100.0	CAULKING MATERIAL 100% SOLIDS

$$\% \text{ Solid} = \frac{(C-A) * 100}{(B-A)}$$