



PERCENT SOLID

Supervisor: apatel  
Analyst: Daniel  
Date: 1/17/2020

OVENTEMP IN Celsius(°C): 107  
Time IN: 17:10  
In Date: 01/16/2020  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
OvenID: M OVEN #1

OVENTEMP OUT Celsius(°C): 102  
Time OUT: 08:42  
Out Date: 01/17/2020  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
BalanceID: M SC-4  
Thermometer ID: %SOLIDS-OVEN

QC:LB107207

| Lab ID   | Client SampleID | Dish # | Dish Wt (g) (A) | Dish + Sample Wt (g) (B) | Dish+Dry Sample Wt (g) (C) | % Solid | Comments                      |
|----------|-----------------|--------|-----------------|--------------------------|----------------------------|---------|-------------------------------|
| L1008-08 | CL-01-011620    | 30     | 1.14            | 9.9                      | 8.38                       | 82.6    |                               |
| L1008-09 | CL-01-011620    | 31     | 1.16            | 9.86                     | 9.3                        | 93.6    |                               |
| L1008-10 | CL-01-011620-1  | 32     | 1.13            | 9.62                     | 9.11                       | 94.0    |                               |
| L1008-11 | CL-01-011620-2  | 33     | 1.18            | 9.69                     | 8.72                       | 88.6    |                               |
| L1008-12 | CL-01-011620-3  | 34     | 1.16            | 9.76                     | 8.91                       | 90.1    |                               |
| L1008-13 | CL-01-011620-4  | 35     | 1.15            | 9.95                     | 9.47                       | 94.5    |                               |
| L1010-06 | OK-02-011620    | 36     | 1.14            | 9.88                     | 8.72                       | 86.7    |                               |
| L1010-07 | OK-02-011620    | 37     | 1.13            | 9.77                     | 7.31                       | 71.5    |                               |
| L1010-08 | OK-02-011620-1  | 38     | 1.17            | 9.96                     | 8.89                       | 87.8    |                               |
| L1012-01 | EO-02-011620    | 39     | 1.17            | 9.93                     | 9.35                       | 93.4    |                               |
| L1012-02 | EO-02-011620    | 40     | 1.13            | 9.93                     | 8.97                       | 89.1    |                               |
| L1012-03 | EO-02-011620-1  | 41     | 1.18            | 9.72                     | 9.65                       | 99.2    |                               |
| L1012-04 | EO-02-011620-2  | 42     | 1.12            | 9.93                     | 8.68                       | 85.8    |                               |
| L1012-05 | EO-02-011620-3  | 43     | 1.1             | 9.84                     | 9.11                       | 91.6    |                               |
| L1152-01 | 01-A-01-B-01-C  | 1      | 1.00            | 2.00                     | 2.00                       | 100.0   | CAULKING MATERIAL 100% SOLIDS |
| L1152-02 | 02-A-02-B-02-C  | 2      | 1.00            | 2.00                     | 2.00                       | 100.0   | CAULKING MATERIAL 100% SOLIDS |
| L1152-03 | 03-A-03-B-03-C  | 3      | 1.00            | 2.00                     | 2.00                       | 100.0   | CAULKING MATERIAL 100% SOLIDS |
| L1152-04 | 04-A-04-B-04-C  | 4      | 1.00            | 2.00                     | 2.00                       | 100.0   | CAULKING MATERIAL 100% SOLIDS |
| L1152-05 | 05-A-05-B-05-C  | 5      | 1.00            | 2.00                     | 2.00                       | 100.0   | CAULKING MATERIAL 100% SOLIDS |
| L1153-01 | 01-A-01-B-01-C  | 6      | 1.00            | 2.00                     | 2.00                       | 100.0   | CAULKING MATERIAL 100% SOLIDS |
| L1153-02 | 02-A-02-B-02-C  | 7      | 1.00            | 2.00                     | 2.00                       | 100.0   | CAULKING MATERIAL 100% SOLIDS |
| L1153-03 | 03-A-03-B-03-C  | 8      | 1.00            | 2.00                     | 2.00                       | 100.0   | CAULKING MATERIAL 100% SOLIDS |
| L1153-04 | 04-A-04-B-04-C  | 9      | 1.00            | 2.00                     | 2.00                       | 100.0   | CAULKING MATERIAL 100% SOLIDS |
| L1153-05 | 05-A-05-B-05-C  | 10     | 1.00            | 2.00                     | 2.00                       | 100.0   | CAULKING MATERIAL 100% SOLIDS |
| L1153-06 | 06-A-06-B-06-C  | 11     | 1.00            | 2.00                     | 2.00                       | 100.0   | CAULKING MATERIAL 100% SOLIDS |
| L1153-07 | 07-A-07-B-07-C  | 12     | 1.00            | 2.00                     | 2.00                       | 100.0   | CAULKING MATERIAL 100% SOLIDS |
| L1153-08 | 08-A-08-B-08-C  | 13     | 1.00            | 2.00                     | 2.00                       | 100.0   | CAULKING MATERIAL 100% SOLIDS |
| L1153-09 | 09-A-09-B-09-C  | 14     | 1.00            | 2.00                     | 2.00                       | 100.0   | CAULKING MATERIAL 100% SOLIDS |



# PERCENT SOLID

Supervisor: apatel  
Analyst: Daniel  
Date: 1/17/2020

OVENTEMP IN Celsius(°C): 107  
Time IN: 17:10  
In Date: 01/16/2020  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
OvenID: M OVEN #1

OVENTEMP OUT Celsius(°C): 102  
Time OUT: 08:42  
Out Date: 01/17/2020  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
BalanceID: M SC-4  
Thermometer ID: %SOLIDS-OVEN

QC:LB107207

| Lab ID   | Client SampleID | Dish # | Dish Wt(g) (A) | Dish + Sample Wt(g) (B) | Dish+Dry Sample Wt(g) (C) | % Solid | Comments                      |
|----------|-----------------|--------|----------------|-------------------------|---------------------------|---------|-------------------------------|
| L1153-10 | 10-A-10-B-10-C  | 15     | 1.00           | 2.00                    | 2.00                      | 100.0   | CAULKING MATERIAL 100% SOLIDS |
| L1153-11 | 11-A-11-B-11-C  | 16     | 1.00           | 2.00                    | 2.00                      | 100.0   | CAULKING MATERIAL 100% SOLIDS |
| L1153-12 | 12-A-12-B-12-C  | 17     | 1.00           | 2.00                    | 2.00                      | 100.0   | CAULKING MATERIAL 100% SOLIDS |
| L1154-01 | B4-0-15         | 18     | 1.14           | 9.96                    | 8.29                      | 81.1    |                               |
| L1154-02 | B4-0-15         | 19     | 1.14           | 9.96                    | 8.29                      | 81.1    |                               |
| L1154-03 | B4-15-20        | 20     | 1.13           | 9.53                    | 8.36                      | 86.1    |                               |
| L1154-04 | B4-15-20        | 21     | 1.13           | 9.53                    | 8.36                      | 86.1    |                               |
| L1154-05 | B3-0-15         | 22     | 1.16           | 9.9                     | 8.54                      | 84.4    |                               |
| L1154-06 | B3-0-15         | 23     | 1.16           | 9.9                     | 8.54                      | 84.4    |                               |
| L1154-07 | B3-15-20        | 24     | 1.18           | 9.66                    | 8.48                      | 86.1    |                               |
| L1154-08 | B3-15-20        | 25     | 1.18           | 9.66                    | 8.48                      | 86.1    |                               |
| L1155-01 | RBR-200028      | 26     | 1.11           | 9.54                    | 8.65                      | 89.4    |                               |
| L1155-02 | RBR-200028      | 27     | 1.12           | 9.58                    | 8.87                      | 91.6    |                               |
| L1155-04 | RBR-200052      | 28     | 1.14           | 9.97                    | 8.22                      | 80.2    |                               |
| L1155-05 | RBR-200052      | 29     | 1.16           | 9.8                     | 8.27                      | 82.3    |                               |

$$\% \text{ Solid} = \frac{(C-A) * 100}{(B-A)}$$