



PERCENT SOLID

Supervisor: apatel  
Analyst: jignesh  
Date: 2/24/2020

OVENTEMP IN Celsius(°C): 107  
Time IN: 17:00  
In Date: 02/21/2020  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
OvenID: M OVEN-1

OVENTEMP OUT Celsius(°C): 103  
Time OUT: 08:11  
Out Date: 02/22/2020  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
BalanceID: M SC-4  
Thermometer ID: %SOLIDS-OVEN

QC:LB107894

| Lab ID   | Client SampleID      | Dish # | Dish Wt (g) (A) | Dish + Sample Wt (g) (B) | Dish+Dry Sample Wt (g) (C) | % Solid | Comments                      |
|----------|----------------------|--------|-----------------|--------------------------|----------------------------|---------|-------------------------------|
| L1593-02 | STOCKPILE            | 40     | 1.1             | 9.89                     | 6.23                       | 58.4    |                               |
| L1635-01 | DUNR-TS001-01        | 1      | 1.15            | 9.96                     | 9.36                       | 93.2    |                               |
| L1635-02 | L1635-01MS           | 2      | 1.15            | 9.96                     | 9.36                       | 93.2    |                               |
| L1635-03 | L1635-01MSD          | 3      | 1.15            | 9.96                     | 9.36                       | 93.2    |                               |
| L1635-04 | DUNR-TS001-02        | 4      | 1.17            | 9.93                     | 9.17                       | 91.3    |                               |
| L1635-05 | DUNR-TS002-01        | 5      | 1.18            | 9.95                     | 9.61                       | 96.1    |                               |
| L1635-06 | DUNR-TS003-01        | 6      | 1.13            | 9.98                     | 9.12                       | 90.3    |                               |
| L1635-07 | DUNR-TS004-01        | 7      | 1.13            | 9.8                      | 9.11                       | 92.0    |                               |
| L1635-08 | DUNR-TS005-01        | 8      | 1.18            | 9.92                     | 9.05                       | 90.0    |                               |
| L1635-09 | DUNR-TS006-01        | 9      | 1.17            | 9.93                     | 8.51                       | 83.8    |                               |
| L1635-10 | DUNR-TS007-01        | 10     | 1.17            | 9.86                     | 8.3                        | 82.0    |                               |
| L1635-11 | LIED-TS001-01        | 11     | 1.13            | 9.84                     | 8.9                        | 89.2    |                               |
| L1635-12 | L1635-11MS           | 12     | 1.13            | 9.84                     | 8.9                        | 89.2    |                               |
| L1635-13 | L1635-11MSD          | 13     | 1.13            | 9.84                     | 8.9                        | 89.2    |                               |
| L1635-14 | LIED-TS001-02        | 14     | 1.17            | 9.62                     | 8.69                       | 89.0    |                               |
| L1635-15 | LIED-TS002-01        | 15     | 1.18            | 9.96                     | 8.87                       | 87.6    |                               |
| L1635-16 | LIED-TS003-01        | 16     | 1.18            | 9.98                     | 8.64                       | 84.8    |                               |
| L1635-17 | LIED-TS004-01        | 17     | 1.18            | 9.96                     | 8.42                       | 82.5    |                               |
| L1635-18 | LIED-TS005-01        | 18     | 1.12            | 9.83                     | 8.24                       | 81.7    |                               |
| L1635-19 | LIED-TS006-01        | 19     | 1.14            | 9.77                     | 8.32                       | 83.2    |                               |
| L1635-20 | LIED-TS007-01        | 20     | 1.17            | 9.57                     | 8.18                       | 83.5    |                               |
| L1636-01 | JDHS-SOUTH-1B        | 21     | 1.18            | 9.91                     | 8.86                       | 88.0    |                               |
| L1636-02 | JDHS-SOUTH-1A        | 22     | 1.16            | 9.73                     | 8.08                       | 80.7    |                               |
| L1642-01 | 021920HU01-P         | 23     | 1.00            | 2.00                     | 2.00                       | 100.0   | PAINT CHIPS SAMPLE,100%SOLIDS |
| L1645-05 | SVOC-GPC-BLANK       | 24     | 1.00            | 2.00                     | 2.00                       | 100.0   |                               |
| L1645-06 | PEST-GPC-BLANK       | 25     | 1.00            | 2.00                     | 2.00                       | 100.0   |                               |
| L1645-07 | PEST-GPC-BLANK-SPIKE | 26     | 1.00            | 2.00                     | 2.00                       | 100.0   |                               |
| L1645-08 | PCB-GPC-BLANK        | 27     | 1.00            | 2.00                     | 2.00                       | 100.0   |                               |



PERCENT SOLID

Supervisor: apatel  
Analyst: jignesh  
Date: 2/24/2020

OVENTEMP IN Celsius(°C): 107  
Time IN: 17:00  
In Date: 02/21/2020  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
OvenID: M OVEN-1

OVENTEMP OUT Celsius(°C): 103  
Time OUT: 08:11  
Out Date: 02/22/2020  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
BalanceID: M SC-4  
Thermometer ID: %SOLIDS-OVEN

QC:LB107894

| Lab ID   | Client SampleID             | Dish # | Dish Wt (g) (A) | Dish + Sample Wt (g) (B) | Dish+Dry Sample Wt (g) (C) | % Solid | Comments                    |
|----------|-----------------------------|--------|-----------------|--------------------------|----------------------------|---------|-----------------------------|
| L1645-09 | PCB-GPC-BLANK-SPIKE         | 28     | 1.00            | 2.00                     | 2.00                       | 100.0   |                             |
| L1645-10 | SVOC-GPC2-BLANK             | 29     | 1.00            | 2.00                     | 2.00                       | 100.0   |                             |
| L1645-11 | PEST-GPC2-BLANK             | 30     | 1.00            | 2.00                     | 2.00                       | 100.0   |                             |
| L1645-12 | PEST-GPC2-BLANK-SPIKE       | 31     | 1.00            | 2.00                     | 2.00                       | 100.0   |                             |
| L1645-13 | PCB-GPC2-BLANK              | 32     | 1.00            | 2.00                     | 2.00                       | 100.0   |                             |
| L1645-14 | PCB-GPC2-BLANK-SPIKE        | 33     | 1.00            | 2.00                     | 2.00                       | 100.0   |                             |
| L1648-01 | PAX-1A                      | 41     | 1.00            | 2.00                     | 2.00                       | 100.0   | CONCRETE SAMPLE 100% SOLIDS |
| L1648-02 | PAX-1B                      | 42     | 1.00            | 2.00                     | 2.00                       | 100.0   | CONCRETE SAMPLE 100% SOLIDS |
| L1648-03 | PAX-2A                      | 43     | 1.00            | 2.00                     | 2.00                       | 100.0   | CONCRETE SAMPLE 100% SOLIDS |
| L1648-04 | PAX-2B                      | 44     | 1.00            | 2.00                     | 2.00                       | 100.0   | CONCRETE SAMPLE 100% SOLIDS |
| L1649-01 | CONCRETE                    | 45     | 1.00            | 2.00                     | 2.00                       | 100.0   | CONCRETE SAMPLE 100% SOLIDS |
| L1650-01 | EP-1                        | 34     | 1.15            | 9.69                     | 8.72                       | 88.6    |                             |
| L1650-02 | EP-2                        | 35     | 1.13            | 9.92                     | 8.98                       | 89.3    |                             |
| L1650-03 | EP-3                        | 36     | 1.18            | 9.81                     | 8.59                       | 85.9    |                             |
| L1650-04 | EP-4                        | 37     | 1.12            | 9.93                     | 8.25                       | 80.9    |                             |
| L1650-05 | EP-5                        | 38     | 1.17            | 9.7                      | 8.94                       | 91.1    |                             |
| L1650-06 | EP-6                        | 39     | 1.18            | 9.79                     | 8.99                       | 90.7    |                             |
| L1654-01 | FK-BPM-03-012-ABCD          | 46     | 1.13            | 9.85                     | 9.1                        | 91.4    |                             |
| L1654-02 | FK-BPM-03-012-ABCD          | 47     | 1.15            | 9.73                     | 9.19                       | 93.7    |                             |
| L1655-01 | FK-BPM-01-AA1-BB1-AA1A-BB1A | 48     | 1.13            | 9.82                     | 9.38                       | 94.9    |                             |
| L1655-02 | FK-BPM-01-AA1-BB1-AA1A-BB1A | 49     | 1.13            | 9.57                     | 9.11                       | 94.5    |                             |
| L1656-01 | FK-BPM-04-006-ABCD          | 50     | 1.18            | 9.57                     | 9.09                       | 94.3    |                             |
| L1656-02 | FK-BPM-04-006-ABCD          | 51     | 1.17            | 9.92                     | 9.45                       | 94.6    |                             |
| L1657-01 | TP-F-S1                     | 52     | 1.18            | 9.69                     | 8.98                       | 91.7    |                             |
| L1657-02 | TP-F-S2                     | 53     | 1.15            | 9.94                     | 9.7                        | 97.3    |                             |
| L1657-03 | TP-F-S                      | 54     | 1.18            | 9.83                     | 9.26                       | 93.4    |                             |
| L1657-05 | TP-F-D1                     | 55     | 1.1             | 9.88                     | 9.43                       | 94.9    |                             |



PERCENT SOLID

Supervisor: apatel  
Analyst: jignesh  
Date: 2/24/2020

OVENTEMP IN Celsius(°C): 107  
Time IN: 17:00  
In Date: 02/21/2020  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
OvenID: M OVEN-1

OVENTEMP OUT Celsius(°C): 103  
Time OUT: 08:11  
Out Date: 02/22/2020  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
BalanceID: M SC-4  
Thermometer ID: %SOLIDS-OVEN

QC:LB107894

| Lab ID   | Client SampleID | Dish # | Dish Wt (g) (A) | Dish + Sample Wt (g) (B) | Dish+Dry Sample Wt (g) (C) | % Solid | Comments |
|----------|-----------------|--------|-----------------|--------------------------|----------------------------|---------|----------|
| L1657-06 | TP-F-D2         | 56     | 1.17            | 9.9                      | 9.34                       | 93.6    |          |
| L1657-07 | TP-F-D          | 57     | 1.13            | 9.85                     | 9.42                       | 95.1    |          |
| L1659-02 | WH-1-1.5-1.5    | 58     | 1.17            | 9.95                     | 8.56                       | 84.2    |          |
| L1659-03 | WH-1-2.5-3.0    | 59     | 1.18            | 9.93                     | 8.94                       | 88.7    |          |
| L1659-05 | WH-2-1.5-2.0    | 60     | 1.17            | 9.96                     | 9.46                       | 94.3    |          |
| L1659-06 | WH-2-5.0-5.5    | 61     | 1.14            | 9.92                     | 9.38                       | 93.8    |          |

$$\% \text{ Solid} = \frac{(C-A) * 100}{(B-A)}$$