



PERCENT SOLID

Supervisor: apatel
Analyst: jignesh
Date: 2/28/2020

OVENTEMP IN Celsius(°C): 107
Time IN: 17:00
In Date: 02/27/2020
Weight Check 1.0g: 1.00
Weight Check 10g: 10.00
OvenID: M OVEN-1

OVENTEMP OUT Celsius(°C): 103
Time OUT: 08:00
Out Date: 02/28/2020
Weight Check 1.0g: 1.00
Weight Check 10g: 10.00
BalanceID: M SC-4
Thermometer ID: %SOLIDS-OVEN

QC:LB107999

Lab ID	Client SampleID	Dish #	Dish Wt (g) (A)	Dish + Sample Wt (g) (B)	Dish+Dry Sample Wt (g) (C)	% Solid	Comments
L1373-04	TR-06-022720	1	1.12	9.81	8.3	82.6	
L1373-05	TR-06-022720	2	1.14	9.97	9.16	90.8	
L1705-01	FLY-ASH	3	1.13	9.67	7.98	80.2	
L1705-02	BRICK	4	1.00	2.00	2.00	100.0	BRICK SAMPLE,100% SOLIDS
L1705-03	BRICK-MORTAR	5	1.00	2.00	2.00	100.0	BRICK ,100% SOLIDS
L1718-01	72-11976	6	1.15	9.97	6.8	64.1	
L1718-02	72-11976	7	1.18	9.98	8.79	86.5	
L1718-04	72-11986	8	1.13	9.54	8.75	90.6	
L1718-05	72-11986	9	1.16	9.5	8.00	82.0	
L1718-07	VNJ-232	10	1.11	9.62	7.87	79.4	
L1718-08	VNJ-232	11	1.17	9.61	7.47	74.6	
L1718-10	O6	12	1.13	9.59	8.84	91.1	
L1718-11	O6	13	1.13	9.59	8.84	91.1	
L1719-01	MP-1-COMP	14	1.14	9.65	8.45	85.9	
L1719-02	MP-1-VOC	15	1.18	6.98	6.57	92.9	
L1719-03	MP-1-4.0-4.5	16	1.19	9.77	8.95	90.4	
L1719-04	MP-1-9.0-9.5	17	1.12	9.95	9.15	90.9	

$$\% \text{ Solid} = \frac{(C-A) * 100}{(B-A)}$$