



PERCENT SOLID

Supervisor: apatel
Analyst: jignesh
Date: 5/21/2020

OVENTEMP IN Celsius(°C): 107
Time IN: 17:30
In Date: 05/20/2020
Weight Check 1.0g: 1.00
Weight Check 10g: 10.00
OvenID: M OVEN-1

OVENTEMP OUT Celsius(°C): 103
Time OUT: 08:00
Out Date: 05/21/2020
Weight Check 1.0g: 1.00
Weight Check 10g: 10.00
BalanceID: M SC-4
Thermometer ID: %SOLIDS-OVEN

QC:LB109252

Lab ID	Client SampleID	Dish #	Dish Wt (g) (A)	Dish + Sample Wt (g) (B)	Dish+Dry Sample Wt (g) (C)	% Solid	Comments
L2506-14	TR-04-052020	1	1.15	9.78	8.39	83.9	
L2506-15	TR-04-052020	2	1.19	9.82	8.45	84.1	
L2506-16	TR-04-052020-1	3	1.13	9.67	8.88	90.7	
L2716-01	G4-CONCRETE	4	1.00	2.00	2.00	100.0	CONCRETE SAMPLE,100% SOLIDS
L2717-01	DRUM-01-04	5	1.00	2.00	2.00	100.0	PAINT CHIPS SAMPLE,100% SOLIDS
L2718-01	72-12017	6	1.18	9.75	9.19	93.5	
L2718-02	72-12017	7	1.19	9.87	9.14	91.6	
L2719-01	AOC-17	8	1.00	2.00	2.00	100.0	stone sample,100% solids
L2722-01	COMP-1	9	1.14	9.68	8.78	89.5	
L2722-02	COMP-2	10	1.16	9.98	8.98	88.7	
L2722-03	COMP-3	11	1.11	9.7	8.9	90.7	
L2728-01	239994	12	1.14	9.57	8.86	91.6	
L2728-04	239990	13	1.15	9.96	8.93	88.3	
L2728-07	239998	14	1.13	9.94	8.43	82.9	
L2728-10	240000	15	1.11	9.96	9.00	89.2	
L2728-13	240001	16	1.13	9.58	8.46	86.7	

$$\% \text{ Solid} = \frac{(C-A) * 100}{(B-A)}$$