



PERCENT SOLID

Supervisor: apatel
Analyst: JIGNESH
Date: 7/7/2020

OVENTEMP IN Celsius(°C): 107
Time IN: 16:25
In Date: 07/06/2020
Weight Check 1.0g: 1.00
Weight Check 10g: 10.00
OvenID: M OVEN-1

OVENTEMP OUT Celsius(°C): 103
Time OUT: 07:30
Out Date: 07/07/2020
Weight Check 1.0g: 1.00
Weight Check 10g: 10.00
BalanceID: M SC-4
Thermometer ID: %SOLIDS-OVEN

QC:LB109873

Lab ID	Client SampleID	Dish #	Dish Wt (g) (A)	Dish + Sample Wt (g) (B)	Dish+Dry Sample Wt (g) (C)	% Solid	Comments
L3206-12	31078	27	1.15	9.96	9.43	94.0	
L3216-01	LOD-MDL-SOIL-01-QT3-2020	1	1.00	2.00	2.00	100.0	
L3216-02	LOQ-SOIL-02-QT3-2020	2	1.00	2.00	2.00	100.0	
L3216-03	MDL-SOIL-03-QT3-2020	3	1.00	2.00	2.00	100.0	
L3216-04	LOD-MDL-SOIL-04-QT3-2020	4	1.00	2.00	2.00	100.0	
L3216-05	LOQ-SOIL-05-QT3-2020	5	1.00	2.00	2.00	100.0	
L3216-06	MDL-SOIL-06-QT3-2020	6	1.00	2.00	2.00	100.0	
L3217-01	E3-41-DRUM-95	28	1.15	9.88	9.53	96.0	
L3217-02	E3-41-NHS	29	1.16	9.85	7.66	74.8	
L3217-03	E3-41-COMP-1-FLOOR	30	1.13	9.67	7.81	78.2	
L3217-04	E3-41-VAT	31	1.18	9.95	7.14	68.0	
L3217-05	E3-41-BOILER-ROOM	32	1.13	9.78	4.8	42.4	
L3220-01	PCB-062220-01	7	1.00	2.00	2.00	100.0	CAULKING SAMPLE,100% SOLIDS
L3221-01	PCB-062220-SR-02	8	1.00	2.00	2.00	100.0	CAULKING SAMPLE,100% SOLIDS
L3221-02	PCB-062220-SR-03	9	1.00	2.00	2.00	100.0	CAULKING SAMPLE,100% SOLIDS
L3221-03	PCB-062220-SR-04	10	1.00	2.00	2.00	100.0	CAULKING SAMPLE,100% SOLIDS
L3222-01	PCB-070220-SR-01	11	1.00	2.00	2.00	100.0	CAULKING SAMPLE,100% SOLIDS
L3223-01	PCB-062220-SR-08	12	1.00	2.00	2.00	100.0	CAULKING SAMPLE,100% SOLIDS
L3224-01	PCB-062220-SR-07	13	1.00	2.00	2.00	100.0	CAULKING SAMPLE,100% SOLIDS
L3225-01	PCB-062220-SR-06	14	1.00	2.00	2.00	100.0	CAULKING SAMPLE,100% SOLIDS
L3226-01	PCB-070220-SR-02	15	1.00	2.00	2.00	100.0	CAULKING SAMPLE,100% SOLIDS
L3227-01	PCB-062220-SR-09	16	1.00	2.00	2.00	100.0	CAULKING SAMPLE,100% SOLIDS
L3229-05	SVOC-GPC-BLANK	17	1.00	2.00	2.00	100.0	
L3229-06	PEST-GPC-BLANK	18	1.00	2.00	2.00	100.0	
L3229-07	PEST-GPC-BLANK-SPIKE	19	1.00	2.00	2.00	100.0	
L3229-08	PCB-GPC-BLANK	20	1.00	2.00	2.00	100.0	
L3229-09	PCB-GPC-BLANK-SPIKE	21	1.00	2.00	2.00	100.0	



PERCENT SOLID

Supervisor: apatel
Analyst: JIGNESH
Date: 7/7/2020

OVENTEMP IN Celsius(°C): 107
Time IN: 16:25
In Date: 07/06/2020
Weight Check 1.0g: 1.00
Weight Check 10g: 10.00
OvenID: M OVEN-1

OVENTEMP OUT Celsius(°C): 103
Time OUT: 07:30
Out Date: 07/07/2020
Weight Check 1.0g: 1.00
Weight Check 10g: 10.00
BalanceID: M SC-4
Thermometer ID: %SOLIDS-OVEN

QC:LB109873

Lab ID	Client SampleID	Dish #	Dish Wt (g) (A)	Dish + Sample Wt (g) (B)	Dish+Dry Sample Wt (g) (C)	% Solid	Comments
L3229-10	SVOC-GPC2-BLANK	22	1.00	2.00	2.00	100.0	
L3229-11	PEST-GPC2-BLANK	23	1.00	2.00	2.00	100.0	
L3229-12	PEST-GPC2-BLANK-SPIKE	24	1.00	2.00	2.00	100.0	
L3229-13	PCB-GPC2-BLANK	25	1.00	2.00	2.00	100.0	
L3229-14	PCB-GPC2-BLANK-SPIKE	26	1.00	2.00	2.00	100.0	
L3230-01	FK-BPM-01-C4-D4-C4A-D4A	33	1.13	9.96	9.13	90.6	
L3230-02	FK-BPM-01-C4-D4-C4A-D4A	34	1.19	9.74	9.06	92.0	

$$\% \text{ Solid} = \frac{(C-A) * 100}{(B-A)}$$