



PERCENT SOLID

Supervisor: apatel
Analyst: JIGNESH
Date: 9/2/2020

OVENTEMP IN Celsius(°C): 107
Time IN: 17:00
In Date: 09/01/2020
Weight Check 1.0g: 1.00
Weight Check 10g: 10.00
OvenID: M OVEN-1

OVENTEMP OUT Celsius(°C): 103
Time OUT: 08:00
Out Date: 09/02/2020
Weight Check 1.0g: 1.00
Weight Check 10g: 10.00
BalanceID: M SC-4
Thermometer ID: %SOLIDS-OVEN

QC:LB110764

Lab ID	Client SampleID	Dish #	Dish Wt (g) (A)	Dish + Sample Wt (g) (B)	Dish+Dry Sample Wt (g) (C)	% Solid	Comments
L3505-01	PCB-082620-SR-01	34	1.00	2.00	2.00	100.0	CAULKING SAMPLE
L3509-01	PCB-080520-SR-02	35	1.00	2.00	2.00	100.0	CAULKING SAMPLE
L3849-01	16090	1	1.12	9.67	8.12	81.9	
L3849-02	16090	2	1.15	9.56	7.99	81.3	
L3849-04	232	3	1.14	9.89	8.82	87.8	
L3849-05	232	4	1.13	9.68	8.98	91.8	
L3849-07	209	5	1.18	9.6	9.03	93.2	
L3849-08	209	6	1.15	9.92	9.36	93.6	
L3850-01	15203	7	1.14	9.98	7.32	69.9	
L3850-02	15203	8	1.12	9.69	7.11	69.9	
L3850-04	228	9	1.18	9.51	7.81	79.6	
L3850-05	228	10	1.11	9.54	7.91	80.7	
L3851-01	11995	11	1.13	9.84	8.44	83.9	
L3851-02	11995	12	1.16	9.76	8.74	88.1	
L3851-04	238	13	1.18	9.63	9.35	96.7	
L3851-05	238	14	1.1	9.66	9.11	93.6	
L3851-07	20058	15	1.1	9.92	8.75	86.7	
L3851-08	20058	16	1.15	9.95	8.16	79.7	
L3851-10	24743	17	1.14	9.86	7.76	75.9	
L3851-11	24743	18	1.18	9.96	7.91	76.7	
L3851-13	11998	19	1.14	9.96	9.35	93.1	
L3851-14	11998	20	1.12	9.57	9.06	94.0	
L3851-16	RBR-78	21	1.16	9.74	9.06	92.1	
L3851-17	RBR-78	22	1.16	9.72	9.11	92.9	
L3852-01	251378	23	1.15	9.86	9.06	90.8	
L3852-02	251378	24	1.1	9.76	8.95	90.6	
L3852-04	206	25	1.13	9.52	9.26	96.9	
L3852-05	206	26	1.17	9.68	9.44	97.2	



PERCENT SOLID

Supervisor: apatel
Analyst: JIGNESH
Date: 9/2/2020

OVENTEMP IN Celsius(°C): 107
Time IN: 17:00
In Date: 09/01/2020
Weight Check 1.0g: 1.00
Weight Check 10g: 10.00
OvenID: M OVEN-1

OVENTEMP OUT Celsius(°C): 103
Time OUT: 08:00
Out Date: 09/02/2020
Weight Check 1.0g: 1.00
Weight Check 10g: 10.00
BalanceID: M SC-4
Thermometer ID: %SOLIDS-OVEN

QC:LB110764

Lab ID	Client SampleID	Dish #	Dish Wt (g) (A)	Dish + Sample Wt (g) (B)	Dish+Dry Sample Wt (g) (C)	% Solid	Comments
L3852-07	24179	27	1.19	9.77	8.72	87.8	
L3852-08	24179	28	1.13	9.53	8.69	90.0	
L3853-01	208	29	1.16	9.92	9.38	93.8	
L3853-02	208	30	1.1	9.75	9.33	95.1	
L3853-04	11934	31	1.18	9.72	9.47	97.1	
L3853-05	11934	32	1.15	9.58	9.31	96.8	
L3866-01	OK-03-090120	39	1.15	9.96	9.55	95.3	
L3866-02	OK-03-090120	40	1.15	9.63	8.88	91.2	
L3866-03	OK-03-090120-1	41	1.12	9.72	9.27	94.8	
L3866-04	OK-03-090120-2	42	1.18	9.7	9.48	97.4	
L3873-01	DRUM-1-2	38	1.00	2.00	2.00	100.0	CONCRETE SAMPLE
L3875-01	DIELETRIC-FLUID-TOTE-F7	33	1.00	2.00	2.00	100.0	OIL SAMPLE
L3876-01	1500	43	1.00	2.00	2.00	100.0	OILY-DEBRIS
L3876-02	1494	44	1.00	2.00	2.00	100.0	OILY-DEBRIS
L3876-03	1449	45	1.15	9.89	5.67	51.7	
L3876-04	1447	46	1.00	2.00	2.00	100.0	OILY-DEBRIS
L3876-05	1577	47	1.00	2.00	2.00	100.0	OIL SAMPLE
L3876-06	1458-62	48	1.15	9.68	7.2	70.9	
L3876-07	1458-62	49	1.15	9.68	7.2	70.9	
L3876-08	1495-96	50	1.12	9.52	8.5	87.9	
L3876-09	1495-96	51	1.12	9.52	8.5	87.9	
L3876-10	1451-52	52	1.00	2.00	2.00	100.0	OILY DEBRIS
L3876-11	1451-52	53	1.00	2.00	2.00	100.0	OILY-DEBRIS
L3876-12	VNJ-215	54	1.13	9.69	8.66	88.0	
L3876-13	VNJ-215	55	1.13	9.69	8.66	88.0	
L3880-01	PCB-080520-SR-01	36	1.00	2.00	2.00	100.0	CAULKING SAMPLE
L3881-01	PCB-082620-SR-02	37	1.00	2.00	2.00	100.0	CAULKING SAMPLE

$$\% \text{ Solid} = \frac{(C-A) * 100}{(B-A)}$$