



PERCENT SOLID

Supervisor: apatel  
Analyst: jignesh  
Date: 10/5/2020

OVENTEMP IN Celsius(°C): 107  
Time IN: 17:00  
In Date: 10/02/2020  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
OvenID: M OVEN-1

OVENTEMP OUT Celsius(°C): 103  
Time OUT: 08:11  
Out Date: 10/03/2020  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
BalanceID: M SC-4  
Thermometer ID: %SOLIDS-OVEN

QC:LB111273

| Lab ID   | Client SampleID      | Dish # | Dish Wt (g) (A) | Dish + Sample Wt (g) (B) | Dish+Dry Sample Wt (g) (C) | % Solid | Comments              |
|----------|----------------------|--------|-----------------|--------------------------|----------------------------|---------|-----------------------|
| L4242-01 | PAV-B24-100120-0-1   | 1      | 1.15            | 9.96                     | 9.47                       | 94.4    |                       |
| L4242-03 | PAV-B24-100120-0-10  | 2      | 1.13            | 9.86                     | 8.97                       | 89.8    |                       |
| L4242-05 | PAV-B24-100120-10-18 | 3      | 1.15            | 9.94                     | 8.82                       | 87.3    |                       |
| L4242-07 | PAV-B24-100120-17-18 | 4      | 1.17            | 9.97                     | 8.11                       | 78.9    |                       |
| L4242-09 | PAV-B17-100120-0-1   | 5      | 1.16            | 9.79                     | 9.19                       | 93.0    |                       |
| L4242-11 | PAV-B17-100120-0-10  | 6      | 1.13            | 9.95                     | 9.25                       | 92.1    |                       |
| L4242-13 | PAV-B17-100120-10-19 | 7      | 1.14            | 9.78                     | 8.5                        | 85.2    |                       |
| L4242-15 | PAV-B17-100120-18-19 | 8      | 1.14            | 9.94                     | 8.91                       | 88.3    |                       |
| L4242-17 | PAV-B24-100120-DP    | 9      | 1.13            | 9.63                     | 9.06                       | 93.3    |                       |
| L4242-19 | PAV-B24-100120-DP    | 10     | 1.13            | 9.51                     | 8.68                       | 90.1    |                       |
| L4247-01 | B-18 (0-1)           | 11     | 1.16            | 9.96                     | 9.48                       | 94.5    |                       |
| L4247-02 | L4247-01MS           | 12     | 1.16            | 9.96                     | 9.48                       | 94.5    |                       |
| L4247-03 | L4247-01MSD          | 13     | 1.16            | 9.66                     | 9.48                       | 97.9    |                       |
| L4247-04 | B-18 (5-7)           | 14     | 1.16            | 9.9                      | 8.91                       | 88.7    |                       |
| L4247-05 | B-18 (11-13)         | 15     | 1.16            | 9.97                     | 8.81                       | 86.8    |                       |
| L4247-06 | B-19 (4-5)           | 16     | 1.15            | 9.97                     | 9.11                       | 90.2    |                       |
| L4247-07 | DUP-4                | 17     | 1.14            | 9.94                     | 8.95                       | 88.8    |                       |
| L4247-08 | B-19 (5-7)           | 18     | 1.1             | 9.88                     | 9.04                       | 90.4    |                       |
| L4247-09 | B-19 (7-9)           | 19     | 1.13            | 9.82                     | 8.82                       | 88.5    |                       |
| L4247-10 | B-20 (12-14)         | 20     | 1.13            | 9.95                     | 8.65                       | 85.3    |                       |
| L4248-01 | NP-SOIL              | 21     | 1.13            | 9.67                     | 8.41                       | 85.2    |                       |
| L4248-02 | NP-SOIL              | 22     | 1.16            | 9.71                     | 8.33                       | 83.9    |                       |
| L4251-01 | 368                  | 23     | 1.00            | 2.00                     | 2.00                       | 100.0   | ASBESTOS, 100% SOLIDS |
| L4253-05 | SVOC-GPC-BLANK       | 24     | 1.00            | 2.00                     | 2.00                       | 100.0   |                       |
| L4253-06 | PEST-GPC-BLANK       | 25     | 1.00            | 2.00                     | 2.00                       | 100.0   |                       |
| L4253-07 | PEST-GPC-BLANK-SPIKE | 26     | 1.00            | 2.00                     | 2.00                       | 100.0   |                       |
| L4253-08 | PCB-GPC-BLANK        | 27     | 1.00            | 2.00                     | 2.00                       | 100.0   |                       |
| L4253-09 | PCB-GPC-BLANK-SPIKE  | 28     | 1.00            | 2.00                     | 2.00                       | 100.0   |                       |



PERCENT SOLID

Supervisor: apatel  
Analyst: jignesh  
Date: 10/5/2020

OVENTEMP IN Celsius(°C): 107  
Time IN: 17:00  
In Date: 10/02/2020  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
OvenID: M OVEN-1

OVENTEMP OUT Celsius(°C): 103  
Time OUT: 08:11  
Out Date: 10/03/2020  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
BalanceID: M SC-4  
Thermometer ID: %SOLIDS-OVEN

QC:LB111273

| Lab ID   | Client SampleID          | Dish # | Dish Wt (g) (A) | Dish + Sample Wt (g) (B) | Dish+Dry Sample Wt (g) (C) | % Solid | Comments |
|----------|--------------------------|--------|-----------------|--------------------------|----------------------------|---------|----------|
| L4253-10 | SVOC-GCP2-BLANK          | 29     | 1.00            | 2.00                     | 2.00                       | 100.0   |          |
| L4253-11 | PEST-GCP2-BLANK          | 30     | 1.00            | 2.00                     | 2.00                       | 100.0   |          |
| L4253-12 | PEST-GCP2-BLANK-SPIKE    | 31     | 1.00            | 2.00                     | 2.00                       | 100.0   |          |
| L4253-13 | PCB-GCP2-BLANK           | 32     | 1.00            | 2.00                     | 2.00                       | 100.0   |          |
| L4253-14 | PCB-GCP2-BLANK-SPIKE     | 33     | 1.00            | 2.00                     | 2.00                       | 100.0   |          |
| L4260-01 | PAV-B21-100220-0-1       | 34     | 1.12            | 9.74                     | 9.26                       | 94.4    |          |
| L4260-03 | PAV-B21-100220-0-10      | 35     | 1.12            | 9.52                     | 8.71                       | 90.4    |          |
| L4260-05 | PAV-B21-100220-10-18.5   | 36     | 1.16            | 9.97                     | 8.91                       | 88.0    |          |
| L4260-07 | PAV-B21-100220-17.5-18.5 | 37     | 1.13            | 9.93                     | 7.98                       | 77.8    |          |
| L4260-09 | PAV-B23-100220-0-1       | 38     | 1.13            | 9.71                     | 9.12                       | 93.1    |          |
| L4260-11 | PAV-B23-100220-0-10      | 39     | 1.16            | 9.81                     | 9.18                       | 92.7    |          |
| L4260-13 | PAV-B23-100220-10-19     | 40     | 1.16            | 9.82                     | 8.5                        | 84.8    |          |
| L4260-15 | PAV-B23-100220-18-19     | 41     | 1.13            | 9.78                     | 8.39                       | 83.9    |          |
| L4264-01 | BPC-WASTE-DRUM           | 42     | 1.17            | 9.62                     | 8.44                       | 86.0    |          |

$$\% \text{ Solid} = \frac{(C-A) * 100}{(B-A)}$$