



PERCENT SOLID

Supervisor: apatel  
Analyst: JIGNESH  
Date: 3/22/2021

OVENTEMP IN Celsius(°C): 107  
Time IN: 17:00  
In Date: 03/19/2021  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
OvenID: M OVEN-1

OVENTEMP OUT Celsius(°C): 103  
Time OUT: 08:06  
Out Date: 03/20/2021  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
BalanceID: M SC-4  
Thermometer ID: %SOLIDS-OVEN

QC:LB113604

| Lab ID    | Client SampleID | Dish # | Dish Wt (g) (A) | Dish + Sample Wt (g) (B) | Dish+Dry Sample Wt (g) (C) | % Solid | Comments        |
|-----------|-----------------|--------|-----------------|--------------------------|----------------------------|---------|-----------------|
| M1660-03  | X127-1B         | 1      | 1.14            | 9.8                      | 8.00                       | 79.2    |                 |
| M1660-06  | X127-2B         | 2      | 1.12            | 9.79                     | 8.09                       | 80.4    |                 |
| M1660-09  | X127-3B         | 3      | 1.16            | 9.98                     | 8.16                       | 79.4    |                 |
| M1660-12  | X127-4B         | 4      | 1.12            | 9.81                     | 6.71                       | 64.3    |                 |
| M1660-15  | X127-5B         | 5      | 1.13            | 9.92                     | 8.24                       | 80.9    |                 |
| M1660-18  | X127-6B         | 6      | 1.14            | 9.94                     | 8.31                       | 81.5    |                 |
| M1661-02  | X127-7B         | 7      | 1.18            | 9.97                     | 8.03                       | 77.9    |                 |
| M1661-05  | X127-8B         | 8      | 1.19            | 9.75                     | 7.52                       | 73.9    |                 |
| M1661-11  | X127-DUP2       | 9      | 1.13            | 9.82                     | 8.06                       | 79.7    |                 |
| M1663-04  | X127-DUP5       | 10     | 1.12            | 9.77                     | 8.07                       | 80.3    |                 |
| M1745-01  | 01-A-01-B-01-C  | 11     | 1.00            | 2.00                     | 2.00                       | 100.0   | CAULKING SAMPLE |
| M1745-02  | 02-A-02-B-02-C  | 12     | 1.00            | 2.00                     | 2.00                       | 100.0   | CAULKING SAMPLE |
| M1745-03  | 03-A-03-B-03-C  | 13     | 1.00            | 2.00                     | 2.00                       | 100.0   | CAULKING SAMPLE |
| M1746-01  | SB-1-18.5-19.0  | 14     | 1.14            | 9.81                     | 8.2                        | 81.4    |                 |
| M1746-02  | SB-2-18.5-19.0  | 15     | 1.16            | 9.59                     | 8.63                       | 88.6    |                 |
| M1746-03  | SB-3-18.5-19.0  | 16     | 1.16            | 9.66                     | 8.52                       | 86.6    |                 |
| M1746-04  | SB-4-18.5-19.0  | 17     | 1.17            | 9.78                     | 8.54                       | 85.6    |                 |
| M1746-05  | SB-5-18.5-19.0  | 18     | 1.16            | 9.84                     | 9.11                       | 91.6    |                 |
| M1746-06  | SB-6-18.5-19.0  | 19     | 1.16            | 9.76                     | 8.09                       | 80.6    |                 |
| M1746-07  | COMP-1          | 20     | 1.11            | 9.66                     | 8.09                       | 81.6    |                 |
| M1746-08  | COMP-2          | 21     | 1.11            | 9.6                      | 7.96                       | 80.7    |                 |
| M1746-09  | COMP-3          | 22     | 1.14            | 9.94                     | 8.62                       | 85.0    |                 |
| M1746-10  | COMP-4          | 23     | 1.16            | 9.6                      | 8.01                       | 81.2    |                 |
| M1749-01  | FS-SB-15-11-13  | 24     | 1.15            | 9.98                     | 8.66                       | 85.1    |                 |
| M1749-02  | FS-SB-15-21-22  | 25     | 1.19            | 9.74                     | 8.14                       | 81.3    |                 |
| M1750-01  | TRE-1019        | 48     | 1.00            | 2.00                     | 2.00                       | 100.0   | WIPE SAMPLE     |
| M1751-01  | BU-03-031921    | 49     | 1.12            | 9.94                     | 8.56                       | 84.4    |                 |
| M1751-01D | BU-03-031921DUP | 50     | 1.14            | 9.95                     | 8.58                       | 84.4    |                 |



PERCENT SOLID

Supervisor: apatel  
Analyst: JIGNESH  
Date: 3/22/2021

OVENTEMP IN Celsius(°C): 107  
Time IN: 17:00  
In Date: 03/19/2021  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
OvenID: M OVEN-1

OVENTEMP OUT Celsius(°C): 103  
Time OUT: 08:06  
Out Date: 03/20/2021  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
BalanceID: M SC-4  
Thermometer ID: %SOLIDS-OVEN

QC:LB113604

| Lab ID   | Client SampleID       | Dish # | Dish Wt(g) (A) | Dish + Sample Wt(g) (B) | Dish+Dry Sample Wt(g) (C) | % Solid | Comments |
|----------|-----------------------|--------|----------------|-------------------------|---------------------------|---------|----------|
| M1756-01 | HR-03-031921          | 26     | 1.15           | 9.95                    | 9.5                       | 94.9    |          |
| M1756-02 | HR-03-031921-EPH-2    | 27     | 1.16           | 9.96                    | 9.44                      | 94.1    |          |
| M1757-01 | B1A                   | 28     | 1.16           | 9.76                    | 8.71                      | 87.8    |          |
| M1757-02 | B1B                   | 29     | 1.19           | 9.88                    | 9.12                      | 91.3    |          |
| M1757-03 | B2A                   | 30     | 1.14           | 9.97                    | 8.46                      | 82.9    |          |
| M1757-04 | B2B                   | 31     | 1.16           | 9.74                    | 8.95                      | 90.8    |          |
| M1757-05 | B3A                   | 32     | 1.13           | 9.9                     | 8.89                      | 88.5    |          |
| M1757-06 | B3B                   | 33     | 1.11           | 9.66                    | 8.82                      | 90.2    |          |
| M1757-07 | B4A                   | 34     | 1.1            | 9.88                    | 8.46                      | 83.8    |          |
| M1757-11 | B5B                   | 35     | 1.14           | 9.94                    | 8.92                      | 88.4    |          |
| M1757-12 | B5C                   | 36     | 1.15           | 9.97                    | 9.4                       | 93.5    |          |
| M1757-13 | D31921                | 37     | 1.19           | 9.98                    | 8.64                      | 84.8    |          |
| M1758-05 | SVOC-GPC-BLANK        | 38     | 1.00           | 2.00                    | 2.00                      | 100.0   |          |
| M1758-06 | PEST-GPC-BLANK        | 39     | 1.00           | 2.00                    | 2.00                      | 100.0   |          |
| M1758-07 | PEST-GPC-BLANK-SPIKE  | 40     | 1.00           | 2.00                    | 2.00                      | 100.0   |          |
| M1758-08 | PCB-GPC-BLANK         | 41     | 1.00           | 2.00                    | 2.00                      | 100.0   |          |
| M1758-09 | PCB-GPC-BLANK-SPIKE   | 42     | 1.00           | 2.00                    | 2.00                      | 100.0   |          |
| M1758-10 | SVOC-GPC2-BLANK       | 43     | 1.00           | 2.00                    | 2.00                      | 100.0   |          |
| M1758-11 | PEST-GPC2-BLANK       | 44     | 1.00           | 2.00                    | 2.00                      | 100.0   |          |
| M1758-12 | PEST-GPC2-BLANK-SPIKE | 45     | 1.00           | 2.00                    | 2.00                      | 100.0   |          |
| M1758-13 | PCB-GPC2-BLANK        | 46     | 1.00           | 2.00                    | 2.00                      | 100.0   |          |
| M1758-14 | PCB-GPC2-BLANK-SPIKE  | 47     | 1.00           | 2.00                    | 2.00                      | 100.0   |          |

$$\% \text{ Solid} = \frac{(C-A) * 100}{(B-A)}$$