



PERCENT SOLID

Supervisor: apatel
Analyst: Alexander
Date: 4/12/2021

OVENTEMP IN Celsius(°C): 107
Time IN: 16:45
In Date: 04/09/2021
Weight Check 1.0g: 1.00
Weight Check 10g: 10.00
OvenID: M OVEN-1

OVENTEMP OUT Celsius(°C): 105
Time OUT: 08:50
Out Date: 04/12/2021
Weight Check 1.0g: 1.00
Weight Check 10g: 10.00
BalanceID: M SC-4
Thermometer ID: %SOLIDS-OVEN

QC:LB113900

Lab ID	Client SampleID	Dish #	Dish Wt (g) (A)	Dish + Sample Wt (g) (B)	Dish+Dry Sample Wt (g) (C)	% Solid	Comments
M1991-01	JCSY-WC1-1	1	1.18	9.71	9.14	93.3	
M1991-05	JCSY-WC2-1	2	1.16	9.61	9.01	92.9	
M1991-09	JCSY-WC3-1	3	1.16	9.9	9.03	90.0	
M1991-13	JCSY-WC1-A	4	1.19	9.85	9.29	93.5	
M1991-15	JCSY-WC2-A	5	1.14	9.81	9.13	92.2	
M1991-17	JCSY-WC3-A	6	1.15	9.77	9.00	91.1	
M1991-17D	JCSY-WC3-ADUP	7	1.11	9.79	9.07	91.7	
M1992-01	AU-05-040921	38	1.12	9.54	8.93	92.8	
M1993-01	T-1	20	1.00	2.00	2.00	100.0	CONCRETE SAMPLE
M1993-02	T-1	21	1.00	2.00	2.00	100.0	CONCRETE SAMPLE
M1993-03	T-2	22	1.00	2.00	2.00	100.0	CONCRETE SAMPLE
M1993-04	T-2	23	1.00	2.00	2.00	100.0	CONCRETE SAMPLE
M1996-01	26878	39	1.12	9.81	8.4	83.8	
M1996-02	26878	40	1.16	9.54	8.18	83.8	
M1997-01	RBR-58-56	41	1.19	9.76	8.2	81.8	
M1997-02	RBR-58-56	42	1.17	9.77	7.92	78.5	
M1997-03	801-675	43	1.15	9.94	8.94	88.6	
M1997-04	801-675	44	1.18	9.69	8.46	85.5	
M1998-01	SB-3A	8	1.15	9.57	5.77	54.9	
M1998-02	SB-3B	9	1.16	9.62	5.64	53.0	
M1998-03	SB-3C	10	1.11	9.67	6.72	65.5	
M1998-04	SB-3D	11	1.19	9.71	5.65	52.3	
M1998-05	SB-4A	12	1.15	9.96	6.12	56.4	
M1998-06	SB-4B	13	1.15	9.54	5.36	50.2	
M1998-07	SB-4C	14	1.19	9.85	5.45	49.2	
M1998-08	SB-5A	15	1.18	9.61	5.58	52.2	
M1998-09	M1998-08MS	16	1.18	9.61	5.58	52.2	
M1998-10	M1998-08MSD	17	1.18	9.61	5.58	52.2	



PERCENT SOLID

Supervisor: apatel
Analyst: Alexander
Date: 4/12/2021

OVENTEMP IN Celsius(°C): 107
Time IN: 16:45
In Date: 04/09/2021
Weight Check 1.0g: 1.00
Weight Check 10g: 10.00
OvenID: M OVEN-1

OVENTEMP OUT Celsius(°C): 105
Time OUT: 08:50
Out Date: 04/12/2021
Weight Check 1.0g: 1.00
Weight Check 10g: 10.00
BalanceID: M SC-4
Thermometer ID: %SOLIDS-OVEN

QC:LB113900

Lab ID	Client SampleID	Dish #	Dish Wt (g) (A)	Dish + Sample Wt (g) (B)	Dish+Dry Sample Wt (g) (C)	% Solid	Comments
M1998-11	SB-5B	18	1.1	9.61	5.79	55.1	
M1998-12	SB-5C	19	1.17	9.98	8.56	83.9	
M2001-01	HA-02	24	1.00	2.00	2.00	100.0	CAULKING SAMPLE
M2001-02	HA-03	25	1.00	2.00	2.00	100.0	CAULKING SAMPLE
M2001-03	HA-04	26	1.00	2.00	2.00	100.0	CAULKING SAMPLE
M2001-04	HA-05	27	1.00	2.00	2.00	100.0	CAULKING SAMPLE
M2002-05	SVOC-GPC-BLANK	28	1.00	2.00	2.00	100.0	
M2002-06	PEST-GPC-BLANK	29	1.00	2.00	2.00	100.0	
M2002-07	PEST-GPC-BLANK-SPIKE	30	1.00	2.00	2.00	100.0	
M2002-08	PCB-GPC-BLANK	31	1.00	2.00	2.00	100.0	
M2002-09	PCB-GPC-BLANK-SPIKE	32	1.00	2.00	2.00	100.0	
M2002-10	SVOC-GCP2-BLANK	33	1.00	2.00	2.00	100.0	
M2002-11	PEST-GCP2-BLANK	34	1.00	2.00	2.00	100.0	
M2002-12	PEST-GCP2-BLANK-SPIKE	35	1.00	2.00	2.00	100.0	
M2002-13	PCB-GCP2-BLANK	36	1.00	2.00	2.00	100.0	
M2002-14	PCB-GCP2-BLANK-SPIKE	37	1.00	2.00	2.00	100.0	
M2003-01	TS-4	45	1.14	9.52	8.27	85.1	
M2003-01D	TS-4DUP	46	1.15	9.54	8.25	84.6	

$$\% \text{ Solid} = \frac{(C-A) * 100}{(B-A)}$$