



PERCENT SOLID

Supervisor: Iwona  
Analyst: jignesh  
Date: 8/15/2023

OVENTEMP IN Celsius(°C): 107  
Time IN: 17:00  
In Date: 08/14/2023  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
OvenID: M OVEN-1

OVENTEMP OUT Celsius(°C): 106  
Time OUT: 08:05  
Out Date: 08/15/2023  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
BalanceID: M SC-4  
Thermometer ID: %SOLIDS-OVEN

QC:LB126850

| Lab ID   | Client SampleID    | Dish # | Dish Wt(g) (A) | Sample Wt(g) | Dish + Sample Wt(g) (B) | Dish+Dry Sample Wt(g) (C) | % Solid | Comments        |
|----------|--------------------|--------|----------------|--------------|-------------------------|---------------------------|---------|-----------------|
| O3977-01 | WASTE              | 1      | 1.16           | 8.47         | 9.63                    | 8.09                      | 81.8    |                 |
| O3977-02 | VOC                | 2      | 1.19           | 8.52         | 9.71                    | 8.2                       | 82.3    |                 |
| O3977-03 | 1                  | 3      | 1.17           | 8.58         | 9.75                    | 8.43                      | 84.6    |                 |
| O3977-04 | 2                  | 4      | 1.19           | 8.60         | 9.79                    | 8.44                      | 84.3    |                 |
| O3977-05 | 3                  | 5      | 1.15           | 8.80         | 9.95                    | 8.36                      | 81.9    |                 |
| O3977-06 | 4                  | 6      | 1.15           | 8.82         | 9.97                    | 8.68                      | 85.4    |                 |
| O3977-07 | 5                  | 7      | 1.17           | 8.75         | 9.92                    | 8.35                      | 82.1    |                 |
| O3981-01 | WC081023           | 8      | 1.15           | 8.61         | 9.76                    | 9.17                      | 93.1    |                 |
| O3984-01 | BX5-1-23           | 9      | 1.00           | 1.00         | 2.00                    | 2.00                      | 100.0   | plastic sample  |
| O3984-02 | BX5-2-23           | 10     | 1.12           | 8.55         | 9.67                    | 9.44                      | 97.3    |                 |
| O3984-03 | BX6-1-23           | 11     | 1.00           | 1.00         | 2.00                    | 2.00                      | 100.0   | PLASTIC         |
| O3984-04 | BX6-2-23           | 12     | 1.18           | 8.59         | 9.77                    | 9.6                       | 98.0    |                 |
| O3984-05 | BX7-1-23           | 13     | 1.00           | 1.00         | 2.00                    | 2.00                      | 100.0   | plastic sample  |
| O3984-06 | BX7-2-23           | 14     | 1.15           | 8.47         | 9.62                    | 9.48                      | 98.3    |                 |
| O3985-01 | PNNL-APM2-0811-1   | 15     | 1.14           | 8.83         | 9.97                    | 9.46                      | 94.2    |                 |
| O3985-03 | PNNL-APM2-0811-2   | 16     | 1.16           | 8.50         | 9.66                    | 9.14                      | 93.9    |                 |
| O3994-01 | NEVINS-SB06-Z22-23 | 17     | 1.18           | 8.80         | 9.98                    | 8.64                      | 84.8    |                 |
| O3994-02 | NEVINS-SB06-Z36-37 | 18     | 1.16           | 8.64         | 9.8                     | 8.38                      | 83.6    |                 |
| O3998-01 | 01A-01B-01C        | 19     | 1.00           | 1.00         | 2.00                    | 2.00                      | 100.0   | CAULKING SAMPLE |
| O3998-02 | 02A-02B-02C        | 20     | 1.00           | 1.00         | 2.00                    | 2.00                      | 100.0   | CAULKING SAMPLE |
| O4000-01 | COMP-2             | 26     | 1.00           | 1.00         | 2.00                    | 2.00                      | 100.0   | debris          |
| O4000-02 | 5811               | 27     | 1.17           | 8.57         | 9.74                    | 6.72                      | 64.8    |                 |
| O4001-01 | BC2600785-1-1      | 28     | 1.00           | 1.00         | 2.00                    | 2.00                      | 100.0   | PILC REEL       |
| O4001-02 | BC2600785-1-2      | 29     | 1.00           | 1.00         | 2.00                    | 2.00                      | 100.0   | PILC REEL       |
| O4001-03 | KMH4876-1-1        | 30     | 1.00           | 1.00         | 2.00                    | 2.00                      | 100.0   | PILC REEL       |
| O4001-04 | KMH4876-1-2        | 31     | 1.00           | 1.00         | 2.00                    | 2.00                      | 100.0   | PILC REEL       |
| O4001-05 | BC271345-1-1       | 32     | 1.00           | 1.00         | 2.00                    | 2.00                      | 100.0   | PILC REEL       |
| O4001-06 | BC271345-1-2       | 33     | 1.00           | 1.00         | 2.00                    | 2.00                      | 100.0   | PILC REEL       |



PERCENT SOLID

Supervisor: Iwona  
Analyst: jignesh  
Date: 8/15/2023

OVENTEMP IN Celsius(°C): 107  
Time IN: 17:00  
In Date: 08/14/2023  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
OvenID: M OVEN-1

OVENTEMP OUT Celsius(°C): 106  
Time OUT: 08:05  
Out Date: 08/15/2023  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
BalanceID: M SC-4  
Thermometer ID: %SOLIDS-OVEN

QC:LB126850

| Lab ID   | Client SampleID    | Dish # | Dish Wt(g) (A) | Sample Wt(g) | Dish + Sample Wt(g) (B) | Dish+Dry Sample Wt(g) (C) | % Solid | Comments        |
|----------|--------------------|--------|----------------|--------------|-------------------------|---------------------------|---------|-----------------|
| O4002-01 | RB21147            | 34     | 1.17           | 8.59         | 9.76                    | 8.92                      | 90.2    |                 |
| O4006-01 | E-1                | 21     | 1.15           | 8.37         | 9.52                    | 8.57                      | 88.6    |                 |
| O4006-02 | E-1                | 22     | 1.15           | 8.37         | 9.52                    | 8.57                      | 88.6    |                 |
| O4009-01 | CONC-COMP          | 35     | 1.00           | 1.00         | 2.00                    | 2.00                      | 100.0   | CONCRETE SAMPLE |
| O4011-01 | SU-03-081423       | 36     | 1.18           | 8.40         | 9.58                    | 8.77                      | 90.4    |                 |
| O4011-02 | SU-03-081423-EPH-2 | 37     | 1.15           | 8.81         | 9.96                    | 9.09                      | 90.1    |                 |
| O4012-01 | HD-02-081423       | 38     | 1.15           | 8.84         | 9.99                    | 8.88                      | 87.4    |                 |
| O4012-02 | HD-02-081423-EPH-2 | 39     | 1.13           | 8.79         | 9.92                    | 8.64                      | 85.4    |                 |
| O4016-01 | B-PP15A            | 23     | 1.17           | 8.50         | 9.67                    | 8.95                      | 91.5    |                 |
| O4016-02 | B-PP15B            | 24     | 1.17           | 8.65         | 9.82                    | 9.32                      | 94.2    |                 |
| O4016-03 | P-PP12             | 25     | 1.12           | 8.87         | 9.99                    | 9.44                      | 93.8    |                 |

$$\% \text{ Solid} = \frac{(C-A) * 100}{(B-A)}$$