

# PERCENT SOLID

Supervisor: Iwona  
Analyst: jignesh  
Date: 7/29/2024

OVENTEMP IN Celsius(°C): 108  
Time IN: 17:00  
In Date: 07/26/2024  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
OvenID: M OVEN#1

OVENTEMP OUT Celsius(°C): 103  
Time OUT: 08:11  
Out Date: 07/27/2024  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
BalanceID: M SC-4  
Thermometer ID: % SOLID- OVEN

QC:LB131747

| Lab ID   | Client SampleID                | Dish # | Dish Wt (g) (A) | Sample Wt (g) | Dish + Sample Wt (g) (B) | Dish+Dry Sample Wt (g) (C) | % Solid | Comments        |
|----------|--------------------------------|--------|-----------------|---------------|--------------------------|----------------------------|---------|-----------------|
| P3328-17 | E20M2                          | 1      | 1.14            | 8.48          | 9.62                     | 8.24                       | 83.7    |                 |
| P3367-01 | TR-06-07252024                 | 2      | 1.16            | 8.50          | 9.66                     | 9.13                       | 93.8    |                 |
| P3367-02 | TR-06-07252024-E2              | 3      | 1.13            | 8.56          | 9.69                     | 9.22                       | 94.5    |                 |
| P3368-01 | CONC-1                         | 53     | 1.00            | 1.00          | 2.00                     | 2.00                       | 100.0   | CONCRETE sample |
| P3368-03 | CONC-2                         | 54     | 1.00            | 1.00          | 2.00                     | 2.00                       | 100.0   | CONCRETE sample |
| P3368-05 | CONC-3                         | 55     | 1.00            | 1.00          | 2.00                     | 2.00                       | 100.0   | CONCRETE sample |
| P3368-07 | CONC-4                         | 56     | 1.00            | 1.00          | 2.00                     | 2.00                       | 100.0   | CONCRETE sample |
| P3372-01 | OR-03-07252024                 | 57     | 1.15            | 8.42          | 9.57                     | 8.99                       | 93.1    |                 |
| P3372-02 | OR-03-07252024-E2              | 58     | 1.17            | 8.59          | 9.76                     | 9.04                       | 91.6    |                 |
| P3374-01 | S-864-K2-SO-12-12.5-072024     | 4      | 1.18            | 8.42          | 9.6                      | 7.69                       | 77.3    |                 |
| P3374-02 | S-864-K2-SO-12.75-13.25-072024 | 5      | 1.18            | 8.45          | 9.63                     | 7.87                       | 79.2    |                 |
| P3374-03 | S-864-K2-SO-13.5-14-072024     | 6      | 1.15            | 8.42          | 9.57                     | 7.74                       | 78.3    |                 |
| P3374-04 | S-861-K2-SO-12-12.5-072024     | 7      | 1.19            | 8.52          | 9.71                     | 8.3                        | 83.5    |                 |
| P3374-05 | S-861-K2-SO-12.75-13.25-072024 | 8      | 1.15            | 8.53          | 9.68                     | 8.31                       | 83.9    |                 |
| P3374-06 | S-861-K2-SO-13.5-14-072024     | 9      | 1.15            | 8.51          | 9.66                     | 8.61                       | 87.7    |                 |
| P3374-07 | S-862-K2-SO-12-12.5-072024     | 10     | 1.17            | 8.47          | 9.64                     | 7.67                       | 76.7    |                 |
| P3374-08 | P3374-07MS                     | 11     | 1.17            | 8.47          | 9.64                     | 7.67                       | 76.7    |                 |
| P3374-09 | P3374-07MSD                    | 12     | 1.17            | 8.47          | 9.64                     | 7.67                       | 76.7    |                 |
| P3374-10 | S-862-K2-SO-12.75-13.25-072024 | 13     | 1.19            | 8.79          | 9.98                     | 8.78                       | 86.3    |                 |
| P3374-11 | S-862-K2-SO-13.5-14-072024     | 14     | 1.15            | 8.80          | 9.95                     | 8.61                       | 84.8    |                 |
| P3374-12 | S-861-K2-SO-13.5-14-072024-FD  | 15     | 1.14            | 8.82          | 9.96                     | 9.2                        | 91.4    |                 |
| P3374-13 | S-847-G1-SO-2.5-3.0-072024     | 16     | 1.18            | 8.56          | 9.74                     | 9.14                       | 93.0    |                 |

# PERCENT SOLID

Supervisor: Iwona  
Analyst: jignesh  
Date: 7/29/2024

OVENTEMP IN Celsius(°C): 108  
Time IN: 17:00  
In Date: 07/26/2024  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
OvenID: M OVEN#1

OVENTEMP OUT Celsius(°C): 103  
Time OUT: 08:11  
Out Date: 07/27/2024  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
BalanceID: M SC-4  
Thermometer ID: % SOLID- OVEN

QC:LB131747

| Lab ID   | Client SampleID                | Dish # | Dish Wt (g) (A) | Sample Wt (g) | Dish + Sample Wt (g) (B) | Dish+Dry Sample Wt (g) (C) | % Solid | Comments |
|----------|--------------------------------|--------|-----------------|---------------|--------------------------|----------------------------|---------|----------|
| P3374-14 | S-847-G1-SO-10-10.5-072024     | 17     | 1.15            | 8.40          | 9.55                     | 6.93                       | 68.8    |          |
| P3374-15 | S-847-G1-SO-12.5-13-072024     | 18     | 1.15            | 8.82          | 9.97                     | 7.56                       | 72.7    |          |
| P3374-16 | S-847-G1-SO-14.5-15-072024     | 19     | 1.16            | 8.42          | 9.58                     | 7.03                       | 69.7    |          |
| P3374-17 | S-863-G1-SO-13.5-14-072024     | 20     | 1.12            | 8.46          | 9.58                     | 8.66                       | 89.1    |          |
| P3374-18 | S-863-G1-SO-12.75-13.25-072024 | 21     | 1.14            | 8.65          | 9.79                     | 8.52                       | 85.3    |          |
| P3374-19 | P3374-18MS                     | 22     | 1.14            | 8.65          | 9.79                     | 8.52                       | 85.3    |          |
| P3374-20 | P3374-18MSD                    | 23     | 1.14            | 8.65          | 9.79                     | 8.52                       | 85.3    |          |
| P3374-21 | S-847-G1-SO-2.5-3.0-072024-FD  | 24     | 1.15            | 8.83          | 9.98                     | 9.44                       | 93.9    |          |
| P3374-22 | S-863-K2-SO-12-12.5-072024     | 25     | 1.13            | 8.76          | 9.89                     | 7.9                        | 77.3    |          |
| P3374-23 | S-862-K2-SO-13.5-14.0-072024   | 26     | 1.19            | 8.44          | 9.63                     | 8.4                        | 85.4    |          |
| P3376-01 | WC-6-VOC                       | 27     | 1.13            | 8.64          | 9.77                     | 9.12                       | 92.5    |          |
| P3376-04 | WC-6-Full Waste Class          | 28     | 1.15            | 8.62          | 9.77                     | 8.95                       | 90.5    |          |
| P3376-10 | WC-7-VOC                       | 29     | 1.13            | 8.71          | 9.84                     | 8.88                       | 89.0    |          |
| P3376-11 | WC-7-Full Waste Class          | 30     | 1.16            | 8.40          | 9.56                     | 8.61                       | 88.7    |          |
| P3376-13 | WC-8-VOC                       | 31     | 1.19            | 8.64          | 9.83                     | 9.08                       | 91.3    |          |
| P3376-14 | WC-8-Full Waste Class          | 32     | 1.19            | 8.48          | 9.67                     | 8.67                       | 88.2    |          |
| P3379-01 | OU4-PCS-01-072324              | 33     | 1.18            | 8.53          | 9.71                     | 8.05                       | 80.5    |          |
| P3379-03 | OU4-PCS-02-072324              | 34     | 1.12            | 8.67          | 9.79                     | 8.08                       | 80.3    |          |
| P3379-05 | OU4-PCS-03-072324              | 35     | 1.19            | 8.45          | 9.64                     | 8.00                       | 80.6    |          |
| P3379-07 | OU4-PCS-04-072324              | 36     | 1.19            | 8.72          | 9.91                     | 8.23                       | 80.7    |          |
| P3379-09 | OU4-PCS-05-072324              | 37     | 1.14            | 8.75          | 9.89                     | 8.08                       | 79.3    |          |
| P3379-11 | OU4-VSL-01-072324              | 38     | 1.15            | 8.54          | 9.69                     | 8.1                        | 81.4    |          |
| P3379-13 | OU4-VSL-02-072324              | 39     | 1.18            | 8.74          | 9.92                     | 8.2                        | 80.3    |          |
| P3379-15 | OU4-VSL-03-072324              | 40     | 1.18            | 8.46          | 9.64                     | 7.99                       | 80.5    |          |



PERCENT SOLID

Supervisor: Iwona  
Analyst: jignesh  
Date: 7/29/2024

OVENTEMP IN Celsius(°C): 108  
Time IN: 17:00  
In Date: 07/26/2024  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
OvenID: M OVEN#1

OVENTEMP OUT Celsius(°C): 103  
Time OUT: 08:11  
Out Date: 07/27/2024  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
BalanceID: M SC-4  
Thermometer ID: % SOLID- OVEN

QC:LB131747

| Lab ID   | Client SampleID       | Dish # | Dish Wt (g) (A) | Sample Wt (g) | Dish + Sample Wt (g) (B) | Dish+Dry Sample Wt (g) (C) | % Solid | Comments |
|----------|-----------------------|--------|-----------------|---------------|--------------------------|----------------------------|---------|----------|
| P3379-17 | OU4-VSL-04-072324     | 41     | 1.19            | 8.44          | 9.63                     | 8.06                       | 81.4    |          |
| P3379-19 | OU4-VSL-05-072324     | 42     | 1.13            | 8.84          | 9.97                     | 8.48                       | 83.1    |          |
| P3383-05 | SVOC-GPC-BLANK        | 43     | 1.00            | 1.00          | 2.00                     | 2.00                       | 100.0   |          |
| P3383-06 | PEST-GPC-BLANK        | 44     | 1.00            | 1.00          | 2.00                     | 2.00                       | 100.0   |          |
| P3383-07 | PEST-GPC-BLANK-SPIKE  | 45     | 1.00            | 1.00          | 2.00                     | 2.00                       | 100.0   |          |
| P3383-08 | PCB-GPC-BLANK         | 46     | 1.00            | 1.00          | 2.00                     | 2.00                       | 100.0   |          |
| P3383-09 | PCB-GPC-BLANK-SPIKE   | 47     | 1.00            | 1.00          | 2.00                     | 2.00                       | 100.0   |          |
| P3383-10 | SVOC-GPC2-BLANK       | 48     | 1.00            | 1.00          | 2.00                     | 2.00                       | 100.0   |          |
| P3383-11 | PEST-GPC2-BLANK       | 49     | 1.00            | 1.00          | 2.00                     | 2.00                       | 100.0   |          |
| P3383-12 | PEST-GPC2-BLANK-SPIKE | 50     | 1.00            | 1.00          | 2.00                     | 2.00                       | 100.0   |          |
| P3383-13 | PCB-GPC2-BLANK        | 51     | 1.00            | 1.00          | 2.00                     | 2.00                       | 100.0   |          |
| P3383-14 | PCB-GPC2-BLANK-SPIKE  | 52     | 1.00            | 1.00          | 2.00                     | 2.00                       | 100.0   |          |

$$\% \text{ Solid} = \frac{(C-A) * 100}{(B-A)}$$