



PERCENT SOLID

Supervisor: apatel  
Analyst: JIGNESH  
Date: 10/25/2018

OVENTEMP IN Celsius(°C): 107  
Time IN: 17:15  
In Date: 10/24/2018  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
OvenID: M Oven-1

OVENTEMP OUT Celsius(°C): 103  
Time OUT: 08:15  
Out Date: 10/25/2018  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
BalanceID: M Sc-1

QC:LB98819

| Lab ID   | Client Sample ID        | Dish# | Dish Wt(g)<br>(A) | Dish +<br>Sample Wt(g)<br>(B) | Dish + Dry<br>Sample Wt(g)<br>(C) | % Solid |
|----------|-------------------------|-------|-------------------|-------------------------------|-----------------------------------|---------|
| J5649-01 | DL-01A                  | 1     | 1.16              | 9.81                          | 8.66                              | 86.7    |
| J5649-02 | DL-01B                  | 2     | 1.18              | 9.83                          | 8.15                              | 80.6    |
| J5649-03 | DL-02A                  | 3     | 1.19              | 9.92                          | 8.34                              | 81.9    |
| J5649-04 | DL-02B                  | 4     | 1.17              | 9.77                          | 8.09                              | 80.5    |
| J5649-05 | DL-02C                  | 5     | 1.18              | 9.72                          | 7.86                              | 78.2    |
| J5649-06 | DL-03A                  | 6     | 1.15              | 9.95                          | 8.63                              | 85.0    |
| J5649-07 | J5649-06MS              | 7     | 1.15              | 9.95                          | 8.63                              | 85.0    |
| J5649-08 | J5649-06MSD             | 8     | 1.15              | 9.95                          | 8.63                              | 85.0    |
| J5649-09 | DL-03B                  | 9     | 1.17              | 9.79                          | 8.56                              | 85.7    |
| J5649-10 | DL-04A                  | 10    | 1.11              | 9.96                          | 8.52                              | 83.7    |
| J5649-11 | DL-04B                  | 11    | 1.13              | 9.54                          | 7.55                              | 76.3    |
| J5649-12 | DL-05A                  | 12    | 1.14              | 9.98                          | 9.14                              | 90.5    |
| J5649-13 | DL-05B                  | 13    | 1.12              | 9.59                          | 8.83                              | 91.0    |
| J5651-01 | RBR-200030              | 14    | 1.14              | 9.93                          | 8.63                              | 85.2    |
| J5651-02 | RBR-200030              | 15    | 1.14              | 9.93                          | 8.63                              | 85.2    |
| J5652-01 | CONCRETE-5060           | 16    | 1.00              | 2.00                          | 2.00                              | 100.0   |
| J5652-02 | VB16206-VB16207-V236-VB | 17    | 1.17              | 9.79                          | 4.57                              | 39.4    |
| J5652-03 | VB16206-VB16207-V236-VB | 18    | 1.17              | 9.79                          | 4.57                              | 39.4    |
| J5654-01 | SW2-01                  | 19    | 1.16              | 9.68                          | 9.02                              | 92.3    |
| J5654-02 | SW2-02                  | 20    | 1.18              | 9.64                          | 8.84                              | 90.5    |
| J5658-01 | JC-TS-001               | 21    | 1.19              | 9.82                          | 7.98                              | 78.7    |
| J5658-02 | JC-TS-002               | 22    | 1.19              | 9.94                          | 7.87                              | 76.3    |
| J5661-01 | VB44949                 | 23    | 1.13              | 9.86                          | 4.66                              | 40.4    |

$$\% \text{ Solid} = \frac{(C-A) * 100}{(B-A)}$$