



PERCENT SOLID

Supervisor: apatel  
Analyst: JIGNESH  
Date: 10/26/2018

OVENTEMP IN Celsius(°C): 108  
Time IN: 17:25  
In Date: 10/25/2018  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
OvenID: M Oven-1

OVENTEMP OUT Celsius(°C): 103  
Time OUT: 08:18  
Out Date: 10/26/2018  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
BalanceID: M Sc-1

QC:LB98853

| Lab ID   | Client Sample ID      | Dish# | Dish Wt(g)<br>(A) | Dish +<br>Sample Wt(g)<br>(B) | Dish + Dry<br>Sample Wt(g)<br>(C) | % Solid |
|----------|-----------------------|-------|-------------------|-------------------------------|-----------------------------------|---------|
| J5204-09 | SU-02-102518-A        | 1     | 1.13              | 9.92                          | 8.82                              | 87.5    |
| J5204-11 | SU-02-102518-B        | 2     | 1.13              | 9.58                          | 8.9                               | 92.0    |
| J5204-13 | SU-01-102518-A        | 3     | 1.1               | 9.64                          | 8.82                              | 90.4    |
| J5204-15 | SU-01-102518-B        | 4     | 1.14              | 9.87                          | 8.83                              | 88.1    |
| J5205-05 | TR-05-102518          | 5     | 1.16              | 9.93                          | 9.22                              | 91.9    |
| J5515-03 | AOC1-03A              | 6     | 1.18              | 9.77                          | 8.74                              | 88.0    |
| J5515-04 | AOC1-03B              | 7     | 1.18              | 9.67                          | 8.79                              | 89.6    |
| J5538-03 | WWT1-6                | 8     | 1.00              | 2.00                          | 2.00                              | 100.0   |
| J5658-03 | JC-TS-001             | 9     | 1.14              | 9.6                           | 7.92                              | 80.1    |
| J5658-04 | JC-TS-002             | 10    | 1.13              | 9.6                           | 7.63                              | 76.7    |
| J5658-05 | JC-TS-003             | 11    | 1.18              | 9.85                          | 8.12                              | 80.0    |
| J5658-06 | JC-TS-004             | 12    | 1.18              | 9.76                          | 8.12                              | 80.9    |
| J5658-07 | JC-TS-005             | 13    | 1.1               | 9.72                          | 8.09                              | 81.1    |
| J5658-08 | JC-TS-006             | 14    | 1.18              | 9.61                          | 7.75                              | 77.9    |
| J5658-09 | JC-TS-007             | 15    | 1.14              | 9.74                          | 8.02                              | 80.0    |
| J5665-01 | DL-06A                | 16    | 1.11              | 9.77                          | 7.82                              | 77.5    |
| J5665-02 | DL-06B                | 17    | 1.16              | 9.88                          | 8.21                              | 80.8    |
| J5665-03 | DL-07A                | 18    | 1.18              | 9.95                          | 8.37                              | 82.0    |
| J5665-04 | DL-07B                | 19    | 1.19              | 9.77                          | 8.7                               | 87.5    |
| J5665-05 | DL-08A                | 20    | 1.19              | 9.61                          | 8.73                              | 89.5    |
| J5665-06 | DL-08B                | 21    | 1.18              | 9.65                          | 7.88                              | 79.1    |
| J5666-01 | BS-OILY-DEBRI         | 22    | 1.00              | 2.00                          | 2.00                              | 100.0   |
| J5666-02 | BS-OIL                | 23    | 1.00              | 2.00                          | 2.00                              | 100.0   |
| J5675-01 | TP-5                  | 24    | 1.18              | 9.89                          | 8.69                              | 86.2    |
| J5675-02 | TP-5-A                | 25    | 1.18              | 9.89                          | 8.69                              | 86.2    |
| J5675-03 | TP-5-B                | 26    | 1.18              | 9.89                          | 8.69                              | 86.2    |
| J5675-04 | TP-5                  | 27    | 1.18              | 9.89                          | 8.69                              | 86.2    |
| J5675-05 | TP-13                 | 28    | 1.15              | 9.98                          | 9.03                              | 89.2    |
| J5675-06 | TP-13-A               | 29    | 1.15              | 9.98                          | 9.03                              | 89.2    |
| J5675-07 | TP-13-B               | 30    | 1.15              | 9.98                          | 9.03                              | 89.2    |
| J5675-08 | TP-13                 | 31    | 1.15              | 9.98                          | 9.03                              | 89.2    |
| J5676-01 | CB-1018-S-TCLP-GRID40 | 32    | 1.16              | 9.53                          | 8.56                              | 88.4    |
| J5683-01 | SP-SAMPLE             | 33    | 1.11              | 9.7                           | 9.16                              | 93.7    |
| J5683-02 | SP-SAMPLE             | 34    | 1.11              | 9.7                           | 9.16                              | 93.7    |
| J5685-01 | DOCUMENTATION-25      | 35    | 1.13              | 9.78                          | 8.87                              | 89.5    |
| J5685-02 | DOCUMENTATION-26      | 36    | 1.18              | 9.55                          | 8.75                              | 90.4    |
| J5685-03 | DOCUMENTATION-27      | 37    | 1.17              | 9.66                          | 8.94                              | 91.5    |
| J5685-04 | DOCUMENTATION-28      | 38    | 1.19              | 9.64                          | 8.95                              | 91.8    |
| J5685-05 | DOCUMENTATION-29      | 39    | 1.1               | 9.87                          | 8.92                              | 89.2    |



PERCENT SOLID

Supervisor: apatel  
Analyst: JIGNESH  
Date: 10/26/2018

OVENTEMP IN Celsius(°C): 108  
Time IN: 17:25  
In Date: 10/25/2018  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
OvenID: M Oven-1

OVENTEMP OUT Celsius(°C): 103  
Time OUT: 08:18  
Out Date: 10/26/2018  
Weight Check 1.0g: 1.00  
Weight Check 10g: 10.00  
BalanceID: M Sc-1

QC:LB98853

| Lab ID   | Client Sample ID | Dish# | Dish Wt(g)<br>(A) | Dish +<br>Sample Wt(g)<br>(B) | Dish + Dry<br>Sample Wt(g)<br>(C) | % Solid |
|----------|------------------|-------|-------------------|-------------------------------|-----------------------------------|---------|
| J5685-06 | DOCUMENTATION-30 | 40    | 1.15              | 9.96                          | 9.22                              | 91.6    |
| J5685-07 | DOCUMENTATION-31 | 41    | 1.1               | 9.85                          | 8.84                              | 88.5    |
| J5685-08 | DOCUMENTATION-32 | 42    | 1.19              | 9.98                          | 9.56                              | 95.2    |
| J5688-01 | DPC-91567-OD-01  | 43    | 1.00              | 2.00                          | 2.00                              | 100.0   |
| J5688-02 | DPC-91567-OD-01  | 44    | 1.00              | 2.00                          | 2.00                              | 100.0   |
| J5689-01 | A366521          | 45    | 1.00              | 2.00                          | 2.00                              | 100.0   |
| J5689-02 | B369737          | 46    | 1.00              | 2.00                          | 2.00                              | 100.0   |

$$\% \text{ Solid} = \frac{(C-A) * 100}{(B-A)}$$